

	DOOR CONTROLLER ACCO-KP2 SATEL	ACCESS CONTROLLER PR621 ROGER	AHD, HD-CVI, HD-TVI, PAL CAMERA HAC-HFW1200TLM-IL-A-0360B-S6 - 1080p 3.6 mm DAHUA
			
	176.55 AUD 176.55 AUD	173.44 AUD 173.44 AUD	121.99 AUD 121.99 AUD
Battery backup support	...	—	...
Keyboard built-in	...	—	...
Standard	AHD, HD-CVI, HD-TVI, CVBS
Input lines	12	3	...
Operation modes	<ul style="list-style-type: none"> Autonomous operation, Work in the ACCO/ACCO NET system
Sensor	Progressive Scan CMOS
Output lines	12	3	...
Matrix size	2.1 Mpx
Outputs rating	<ul style="list-style-type: none"> 50 mA / 12 V DC - (OUT 1-12) 0.5 A / 12 V DC - (+G 1-4)
Relay switching voltage	250 V AC, 30 V DC
Relay contacts load	8 A	1.5 A / 30 V	...
Communication	RS-485	<ul style="list-style-type: none"> RS-485 RACS (Roger) 	...
Resolution	1920 x 1080 - 1080p @ HD-CVI / HD-TVI / AHD @ 25 fps , 960 x 576 - 960H @ PAL @ 25 fps
Lens	3.6 mm
Environment class	...	IV	...
Operation temp	...	-25 °C ... 60 °C	...
View angle	<ul style="list-style-type: none"> 83 ° (manufacturer data) 84 ° (our tests result)
Range of IR illumination	40 m
White light LED illuminator range	40 m
IR illuminator power adjustment	Automatic
Video output	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω
Audio	<ul style="list-style-type: none"> Microphone built-in, Audio support via coaxial cable - HD-CVI only
OSD menu	✓

Main features	<ul style="list-style-type: none"> • 5 programmable input lines NO/NC • Additional dedicated inputs for connecting readers, monitoring the presence of readers, and connecting the tamper circuit • power input • 2 programmable low-current output lines OC • Additional outputs dedicated to connecting readers • Relay output to control the electromagnetic lock, gate controllers or other devices that activate the door • 4 power outputs 12 V/0.5 A • Support for single door with entry and exit authorization, • 1024 users • Possibility to add different privileges to the users • Identification: Card and/or PIN, Dallas iButton • History of 24 576 events • Recording of information about Time&Attendance • Up to 256 access calendars, weekly schedules, daily schedules, time frames • Holiday access schedules • Function to prevent of multiple use of the same code/card to gain access (anti-passback) • Scheduled door locking and unlocking • Limiting of accesses • Compliance with the EM-MARIN, Wiegand 26-56bit, DALLAS protocol • micro USB socket - The ability to firmware upgrade • Its own clock with battery backup • LED indicators displaying the device's operating status • APS power socket - SATEL power adapter (not included) 	<ul style="list-style-type: none"> • Unique EM 125kHz proximity reader built-in • PRT series readers support • 1000 indexed users • History of 250 000 events • 99 General Purpose Schedules • 250 access groups • Tamper detection - removing from mounting surface • Function to prevent of multiple use of the same code/card to gain access (anti-passback) 	...
---------------	---	---	-----



Current consumption	<ul style="list-style-type: none"> • 110 mA (Standby mode) • 480 mA (operation)
Main features	<ul style="list-style-type: none"> • Smart Dual Illumination technology - IR or LED illuminator works in night mode. White light will turn on automatically only when an object is detected in the monitored area, which effectively improves image quality • D-WDR - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • BLC/HLC - Back Light / High Light Compensation • ICR - Movable InfraRed filter • AGC - Automatic Gain Control • Privacy zones - max. 8 • Mirror - Mirror image • Auto White Balance • Sharpness - sharper image outlines
Power supply	12 V DC	10 ... 15 V DC	12 V DC / 340 mA
Power consumption	≤ 4.1 W
Permissible relative humidity	93 % ± 3 %	10 ... 95 % (non-condensing)	...
Housing	Compact Plastic + Metal
Color	White
"Index of Protection"	IP67
Vandal-proof	—
Operation temp	-40 °C ... 60 °C
Weight	0.11 kg	0.15 kg	0.3 kg
Dimensions	142 x 71 x 17 mm	85 x 85 x 27 mm	198 x 80 x 76 mm
Manufacturer / Brand	SATEL	ROGER	DAHUA
Guarantee	2 years	3 years	3 years