





	UPS VI-1500/LCD 1500 VA	AHD, HD-CVI, HD-TVI CAMERA APTI-H50C21-36W 2Mpx / 5Mpx 3.6 mm	CABLE PAIR DETECTOR WITH RJ-45 CABLE TESTER UT-682 UNI-T	EXPANSION PLUG KW-8/4X40 KLIMAS
				
	2104.45 DKK 2104.45 DKK	203.66 DKK 203.66 DKK	220.62 DKK 220.62 DKK	0.52 DKK 0.52 DKK
Nominal power	900 W
Apparent Power	1500 VA
Standard	...	AHD, HD-CVI, HD-TVI
Material	<ul style="list-style-type: none"> Expansion plug, Polypropylene Screw, Steel galvanized
Input voltage	162 ... 290 V AC
Tested cables	UTP, FTP, YTKSY - RJ45 (8P8C), RJ11 (6P4C)	...
Drilling diameter	8 mm
Sensor	...	1/3 " Progressive Scan CMOS
Expansion plug length	40 mm
Matrix size	...	5 Mpx
Output voltage	230 V AC (Approximated Sine Wave)
Screw dimensions	Ø 4 x 40 mm, PZ-2
Output frequency	50 / 60 Hz ± 1 %
Charging time (recover to 90% capacity)	4 ... 6 hours
Application	<ul style="list-style-type: none"> Concrete Solid clay brick Solid sand-lime brick
Estimated battery operation time	18 minutes
Battery	2 x 12V/9Ah
Number of outputs	2 pcs
Number of inputs	2 pcs
Operation temp	0 °C ... 40 °C	...
Transfer time	2 ... 6 ms (max. 10 ms)
Management software	ViewPower (Polish version - Windows 98/2000/XP/Vista/7/8, MAC, Linux, FreeBSD, Solaris)
Permissible relative humidity	20 % ... 75 %	...
Additional protection	RJ11, RJ45
Protections	<ul style="list-style-type: none"> Overcharge Discharge Short-circuit

Resolution	...	<ul style="list-style-type: none"> • 2592 x 1944 - 5 Mpx @ AHD / HD-TVI @ 20 fps / 12.5 fps, • 2560 x 1440 - 4 Mpx @ AHD / HD-CVI / HD-TVI @ 25, 30 fps, • 1920 x 1080 - 1080p @ AHD / HD-CVI / HD-TVI @ 25, 30 fps
Lens	...	3.6 mm
View angle	...	<ul style="list-style-type: none"> • 77 ° (manufacturer data) • 70 ° (our tests result)
Main features	<ul style="list-style-type: none"> • Auto restart while AC is recovering • Short-time charging • Excellent microprocessor control guarantees high reliability • Built-in AVR voltage stabilization system • Battery charging at power-off mode • "Cold Start" function • USB interface • Energy Saving function (possibility to deactivate from software) 	...	<ul style="list-style-type: none"> • Test for the presence of a short circuit, open circuit • Polarity indicator for telephone wire pairs : \pm (5V ... 52V) • The maximum length of the telephone line : 3000 m • Optical - sound signaling • Low battery indicator 	...
Range of IR illumination	...	30 m
Application	to Home & Small Office applications
IR illuminator power adjustment	...	Automatic
Operation state indication	LCD display: operation mode, battery charging level, in/out voltage level
Housing type	Tower
Video output	...	1 Vpp 75 Ω , AHD / HD-CVI / HD-TVI
Audio	...	—
OSD menu	...	✓
Main features	...	<ul style="list-style-type: none"> • D-WDR - Wide Dynamic Range • ICR - Movable InfraRed filter • DNR - Digital Noise Reduction • AGC - Automatic Gain Control • BLC - Back Light Compensation • Day/Night mode (color/b&w/auto) • Auto White Balance • Sharpness - sharper image outlines
Power supply	...	12 V DC / 220 mA	2 x 9V, type 6F22 battery (included)	...

Power consumption	...	≤ 2.6 W
Housing	...	Compact - Aluminum
Color	...	White
"Index of Protection"	...	IP67
Operation temp	...	-20 °C ... 60 °C
Weight	10.52 kg	0.39 kg	<ul style="list-style-type: none"> • 0.11 kg - Transmitter • 0.14 kg - Receiver 	...
Dimensions	397 x 147 x 205 mm	172 x 73 x 73 mm	<ul style="list-style-type: none"> • 125 x 48 x 29 mm - Transmitter • 194 x 50 x 30 - Receiver 	...
Supported languages	...	Polish, English, French, Spanish, Portuguese, Russian, Italian
Manufacturer / Brand	...	APTI	UNI-T	KLIMAS
Guarantee	2 years	2 years	2 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00