

	<a href="#">ACCESS POINT +ROUTER RG-M32 Wi-Fi 6, 2.4 GHz, 5 GHz, 800 Mbps + 2402 Mbps REYEE</a>	<a href="#">SIGNAL INDICATOR SF-100 TV-SAT RED EAGLE</a>	<a href="#">AHD, HD-CVI, HD-TVI CAMERA APTI-H50V2-36 2Mpx / 5Mpx 3.6 mm</a>
			
	1673.85 SEK 1673.85 SEK	71.02 SEK 71.02 SEK	349.33 SEK 349.33 SEK
Output and input	...	F socket	...
Standard	...	...	AHD, HD-CVI, HD-TVI
Sensor	...	...	1/2.7 " Progressive Scan CMOS
Signal level	...	-40 ... -10 dBm	...
Matrix size	...	...	5 Mpx
Frequency range	• 2.4 GHz, • 5 GHz ,	950 MHz ... 2150 MHz	...
Powering from receiver	...	DC 13 V / 18 V	...
Backlighting meter indications	...	✓	...
Sound signaling	...	✓	...
Impedance	...	75 Ω	...
Antenna type	4x4 MU-MIMO - built-in 4 pcs dual-band • 4 dBi @ 2.4 GHz • 4 dBi @ 5 GHz	...	...
Standards	IEEE 802.11ax Wi-Fi 6	...	...
Baud rates	800 Mbps @ 2.4 GHz + 2402 Mbps @ 5 GHz	...	...
LAN ports	3 x 10 / 100 / 1000 Mbps - RJ45	...	...
WAN interface	1 x 10 / 100 / 1000 Mbps - RJ45	...	...
Resolution	...	...	2592 x 1944 - 5 Mpx @ AHD / HD-TVI @ 20 fps, 12.5 fps , 2560 x 1440 - 4 Mpx @ AHD / HD-TVI / HD-CVI @ 25 fps, 30 fps , 1920 x 1080 - 1080p @ AHD / HD-CVI / HD-TVI
Range of IR illumination	...	...	20 m
Port USB	—	...	...
IR illuminator power adjustment	...	...	Automatic
Lens	...	...	3.6 mm
LED indicators	Power / System / Mesh, Signal indicator	...	...

DDNS	—	...	...
View angle	...	...	<ul style="list-style-type: none"> <li>• 83 ° (manufacturer data)</li> <li>• 70 ° (our tests result)</li> </ul>
DHCP server	✓	...	...
Firmware update	✓	...	...
Video output	...	...	1 Vpp 75 Ω, AHD / HD-CVI / HD-TVI - selectable by switch
Protections	<ul style="list-style-type: none"> <li>• WPA/WPA2</li> <li>• Black list</li> <li>• parental control</li> <li>• SSID hiding</li> <li>• Firewall</li> </ul>	...	...
OSD menu	...	...	✓
Operation modes	<ul style="list-style-type: none"> <li>• Repeater</li> <li>• Router</li> <li>• Access Point</li> <li>• WISP</li> </ul>	...	...
Management interface	<ul style="list-style-type: none"> <li>• Configuration using the Ruijie Reyee application</li> <li>• Remote management</li> <li>• Web browser</li> </ul>	...	...
Main features	...	...	<ul style="list-style-type: none"> <li>• D-WDR - Wide Dynamic Range</li> <li>• DNR - Digital Noise Reduction</li> <li>• ICR - Movable InfraRed filter</li> <li>• AGC - Automatic Gain Control</li> <li>• BLC - Back Light Compensation</li> <li>• Day/Night mode (color/b&amp;w/auto)</li> <li>• White Balance - ATW/Manual</li> <li>• Sharpness - sharper image outlines</li> </ul>
Mobile phones support	Android: Free application <a href="#">Ruijie Reyee</a> iOS (iPhone): Free application <a href="#">Ruijie Reyee</a>	...	...
Default IP address	192.168.110.1	...	...
Transmitter power	max. 20 dBm @ 2.4 GHz max. 27 dBm @ 5 GHz	...	...
"Index of Protection"	...	...	IP66
Vandal-proof	...	...	✓
Color	...	...	Graphite

Supported languages	...	...	Polish, English, French, Spanish, Portuguese, Russian, Italian
Operation temp	...	...	-20 °C ... 60 °C
Main features	<ul style="list-style-type: none"> <li>• Wi-Fi 6 support - a standard that offers higher speeds, better performance in high-traffic environments</li> <li>• OFDMA</li> <li>• Beamforming (TxBF) - technology that allows to create a beam of radio waves in order to improve the quality of connection with client devices located further away from the signal source</li> <li>• MU-MIMO - a multi-antenna transmission function that allows to increase the bandwidth and reliability of connection with the client of the network</li> <li>• Load balance</li> <li>• WLAN : max. 6 x BSSID</li> <li>• IPv4/IPv6 - Static routing</li> <li>• PPPoE</li> <li>• IPTV</li> <li>• WMM support (QoS mechanism of the 802.11e standard)</li> <li>• VPN support : PPTP VPN Server / Client</li> <li>• Guest Network - a separate and secure network for guests</li> <li>• Support for Reye Mesh technology</li> <li>• System logs</li> <li>• RESET button</li> <li>• MESH button</li> </ul>	...	...
Housing	Plastic	...	Dome - Metal
Power supply PoE	—	...	...
Power supply	12 V DC / 2.5 A (included)	...	12 V DC / 290 mA
Power consumption	max. 30 W	...	≤ 3.5 W
Operation temp	-10 °C ... 45 °C	...	...
Permissible relative humidity	5 % ... 95 % (non-condensing)	...	...
Weight	0.66 kg	0.08 kg	0.29 kg
Dimensions	119 x 119 x 200 mm	110 x 62 x 42 mm	Ø 93 x 77 mm
Manufacturer / Brand	RUIJIE / REYEE	RED EAGLE	APTI
Guarantee	3 years	2 years	2 years

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel.:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00