



	<a href="#">HDD ENCLOSURE Y-3036 UNITEK</a>	<a href="#">IP SPEED DOME CAMERA OUTDOOR SD6CE245U-HNI - 1080p 3.95 ... 177.7 mm DAHUA</a>
		
	306.73 CZK 306.73 CZK	47974.99 CZK 47974.99 CZK
Standard	...	TCP/IP
Sensor	...	1/2.8 " SONY Starvis™ Back-illuminated CMOS
Supported hard drives	1 x SATA III, 2.5 "	...
Matrix size	...	2.1 Mpx
Outputs	1 x USB 3.1, max. 5 Gb/s	...
Operation state indication	LED diodes	...
Resolution	...	1920 x 1080 - 1080p 1280 x 960 - 1.3 Mpx 1280 x 720 - 720p 704 x 576 - D1
Scanning system	...	Progressive
Lens	...	3.95 ... 177.7 mm
View angle	...	<ul style="list-style-type: none"> <li>• 70 ° ... 1.8 ° (manufacturer data)</li> <li>• 64 ° ... 1.9 ° (our tests result)</li> </ul>
Optical zoom	...	x 45
Digital zoom	...	x 16
Range of IR illumination	...	250 m
S/N ratio	...	> 55 dB (AGC off)
Video output	...	1 Vpp / 75 Ω
Preset rotation speed	...	max. 300 °/s (horizontal) max. 200 °/s (vertical)
Rotation speed (manual control)	...	0.1 °/s ... 200 °/s (horizontal) 0.1 °/s ... 120 °/s (vertical)
Horizontal rotation range	...	360 ° continuous
Vertical rotation range	...	-20 ° ... 90 °
RS-485 interface	...	✓
Protocols	...	Pelco-D, Pelco-P, DH-SD Auto detection
Number of presets	...	300
Horizontal scan	...	✓
Route settings	...	8
Image compression method	...	H.265+ / H.265 / H.264+ / H.264 / MJPEG
Bitrate	...	448 ... 8192 kbps
Alarm inputs / outputs	...	7 / 2
Audio	...	<ul style="list-style-type: none"> <li>• External microphone input</li> <li>• Audio output</li> <li>• Bi-directional audio streaming support</li> <li>• Audio detection</li> </ul>
Main stream frame rate	...	1 ... 50 fps - 1080p
Memory card slot	...	Micro SD memory cards up to 256GB support (possible local recording)

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Network interface	...	10/100 Base-T (RJ-45)
Network protocols	...	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPoE, DDNS, FTP, IP Filter, QoS, Bonjour, IEEE 802.1x
WEB Server	...	Built-in, NVR compliance
Max. number of on-line users	...	20
ONVIF	...	16.12
Mobile phones support	...	Port 37777 • Android: Free application <a href="#">DMSS</a> • iOS (iPhone): Free application <a href="#">DMSS</a>
Default IP address	...	192.168.1.108
Default admin user / password	...	admin / admin
Web browser access ports	...	80, 37777
PC client access ports	...	37777
Mobile client access ports	...	37777
Port ONVIF	...	80
RTSP URL	...	rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream
Main features	...	<ul style="list-style-type: none"> <li>• Intelligent Object Tracking</li> <li>• WDR - 120 dB - Wide Dynamic Range</li> <li>• EIS - Electronic Image Stabilization</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• F-DNR (Defog) - Reduction of image noise caused by precipitation</li> <li>• 2D-DNR, 3D-DNR - Digital Noise Reduction</li> <li>• BLC/HLC - Back Light / High Light Compensation</li> <li>• AGC - Automatic Gain Control</li> <li>• ICR - Movable InfraRed filter</li> <li>• Motion Detection</li> <li>• Configurable Privacy Zones - 24</li> <li>• Sharpness - sharper image outlines</li> <li>• Mirror - Mirror image</li> <li>• Day/night mode</li> <li>• The camera is equipped with a built-in heater with a thermostat</li> <li>• Heat map - the selection in the image by corresponding colors the areas with different traffic</li> <li>• IVS analysis, crossing the line (tripwire), intrusion, abandoned/missing object, face detection</li> </ul>
Power supply	Port USB	<ul style="list-style-type: none"> <li>• PoE (802.3at),</li> <li>• 24 V AC / 3 A (power adapter included)</li> </ul>
Power consumption	...	≤ 25 W
Housing	Desktop, Plastic	Speed Dome Metal
Color	...	White
Vandal-proof	...	IK10
"Index of Protection"	...	IP67
Operation temp	...	-40 °C ... 60 °C
Weight	0.08 kg	6.59 kg (with bracket)
Dimensions	131 x 83 x 35 mm	209 x 270 x 420 mm (with bracket)



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Supported languages	...	Polish, English, Arabic, Czech, French, Spanish, Dutch, Korean, German, Persian, Portuguese, Russian, Italian
Manufacturer / Brand	UNITEK	DAHUA
Guarantee	2 years	5 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00