

	SMART VALVE FOR THE IRRIGATION SYSTEM ATLO-VR1-BLE-TUYA Bluetooth BLE, Tuya Smart	VIDEO SEPARATOR SV-1000/4-G	TOOL BOX KHV40P
			
	179.56 DKK 179.56 DKK	718.93 DKK 718.93 DKK	60.61 DKK 60.61 DKK
Application	irrigation control
Material	Plastic - mixture of increased strength polymers
Type (size)	3/4 "
Standard	...	CVBS - PAL / NTSC	...
Number of inputs	...	4 pcs BNC	...
Number of outputs	...	4 pcs BNC	...
Input impedance	...	75 Ω	...
Output impedance	...	75 Ω	...
Working pressure	0.02 ... 0.8 MPa / 2.9 ... 116 psi
Galvanic (optical) isolation between signal inputs and outputs	...	1000 V peak	...
Opto-isolation between power and signal inputs / outputs	...	1000 V peak	...
Opening/closing time	5 ... 10 s
Galvanic isolation between signal inputs	...	1000 V peak	...
Wireless	Bluetooth
Galvanic isolation between signal outputs	...	1000 V peak	...
Radio communication range (at open area)	15 m
Gain adjustment	...	-5 ... +5 dB (adjust potentiometers are available after remove the cover)	...
Mobile phones support	<ul style="list-style-type: none"> • The Tuya Smart free application on Android • The Tuya Smart free application on iOS
Bandwidth	...	9 MHz / 1 Vpp	...
Transmission error	...	0.75 % (f=3.58MHz, Vin=1Vpp)	...
Assembly	...	To the wall	...
External dimensions	384 x 335 x 144 mm

Internal dimensions	365 x 245 x 110 mm
Manufacturer / Brand	...	DELTA	...
Main features	<ul style="list-style-type: none"> • schedule, • timer, • manual watering (app or button), • delay after rain : 24, 48, 72 h - the device will not turn on the sprinklers if it is raining, • remote access - Bluetooth/Wi-Fi gateway, • voice control • STATUS indicator • Low current consumption • Easy installation - the valve is mounted directly on the tap • 3/4" / 1/2" Adapter (included) 	...	<ul style="list-style-type: none"> • High-strength body, • Ergonomic handle, • Protective foam inside to protect tools, • Capacity : 10 kg, • 2 fasteners on the front to prevent accidental opening
Housing	Plastic (ABS) + Nylon, UV-resistant, Waterproof
"Index of Protection"	IP55
Color	Black	...	Black
Power supply	2 x 1.5V, type AA/LR6/FR6 battery (not included)	12 V DC / 300 mA	...
Operation temp	4.5 °C ... 45 °C
Weight	0.3 kg	0.310 kg	0.95 kg
Dimensions	138 x 110 x 47 mm	213 x 36 x 93 mm	...
Guarantee	2 years	3 years	2 years