





	ACCESS CONTROLLER MODULE MC16-PAC-ST-2 ROGER	COMPRESSION PLUG BNC: W/4781G-MTC*P10 RG6 Triset113 METACON	ACCESS CONTROLLER MC16-PAC-ST-4-KIT ROGER	DUMMY PLUG SC DUPLEX PPZO-2SC/B
				
	8403.87 CZK 8403.87 CZK	50.79 CZK 50.79 CZK	18651.27 CZK 18651.27 CZK	7.50 CZK 7.50 CZK
Application	SC duplex
Color	Black
Number of served transitions	2 (two-way)	...	4 (two-way)	...
Number of supported readers	8	...	16	...
In package	...	10 pcs The price for package
Number of users	unlimited (purchase of the appropriate license required)	...	unlimited (purchase of the appropriate license required)	...
Connector type	...	BNC Plug
Attachment of connector elements	...	Compression mounting
Number of media per ID	8 - Proximity card, PIN code, fingerprint, etc.	...	8 - Proximity card, PIN code, fingerprint, etc.	...
Application	...	Coaxial cable
Buffer memory	8 000 000 events buffer	...	8 000 000 events buffer	...
Dielectric diameter	...	max. 4.7 mm
Number of access zones	4	...	8	...
Wire mounting	...	Pressing
Number of alarm zones	4	...	8	...
Cable diameter	...	max. 8.1 mm
Shield fastening	...	Compression mounting
Battery backup support	12 V / 7 Ah	...	12 V / 20 Ah	...
Watertightness	...	✓
Example of application	...	<ul style="list-style-type: none"> • RG6 • HFEK • Triset113
Communication	<ul style="list-style-type: none"> • Ethernet - RJ-45 socket • RACS 5 v2 (Roger) • RS-485 interface 	...	<ul style="list-style-type: none"> • Ethernet - RJ-45 socket • RACS 5 v2 (Roger) • RS-485 interface 	...

Main features	<ul style="list-style-type: none"> • Integrated support in VISO ST software • Functions in the VISO ST system: <ul style="list-style-type: none"> - MSSQL database - work in distributed systems - multi-station work - monitoring of transitions with video preview - T&A event reporting - maximum number of transitions in the system : 128 	<ul style="list-style-type: none"> • Properly compressed connection is highly resistant to break • Watertightness of connector with cable connection • Very easy and quick assembly • Corrosion resistance • Very low loss in the whole operating band • To crimp use the crimping tool HT-5082R 	<ul style="list-style-type: none"> • Metal housing • The MCX4D I/O expander included • Integrated support in VISO ST software • Functions in the VISO ST system: <ul style="list-style-type: none"> - MSSQL database - work in distributed systems - multi-station work - monitoring of transitions with video preview - T&A event reporting - maximum number of transitions in the system : 128 	
Power supply	<ul style="list-style-type: none"> • 17 ... 22 V AC • 10 ... 15 V DC • 22 ... 26 V DC 	...	<ul style="list-style-type: none"> • 17 ... 22 V AC • 10 ... 15 V DC • 22 ... 26 V DC 	...
Operation temp	5 °C ... 40 °C	...	5 °C ... 40 °C	...
Permissible relative humidity	10 % ... 95 % (non-condensing)	...	10 % ... 95 % (non-condensing)	...
Weight	0.14 kg	0.160 kg	4.05 kg	...
Dimensions	175 x 72 x 30 mm	Ø 15 x 41 mm	405 x 365 x 120 mm	34 x 11 x 10 mm
Manufacturer / Brand	ROGER	METACON	ROGER	...
Guarantee	3 years	2 years	3 years	...