



	RS-485 KEYBOARD CONTROLLER KT-610	RELAY MODULE ESP12-4R-MV Wi-Fi
		
	560.00 PLN 560.00 PLN	61.73 PLN 61.73 PLN
PTZ control	...	Wi-Fi
Protocols	Pelco-D, Pelco-P, SAMSUNG, YAAN, SAE	...
Protocol	...	IEEE 802.11 b/g/n/e/i, Wi-Fi Direct (P2P), TCP, UDP
Number of inputs	...	—
Number of relay outputs	...	4 pcs
Baud rates	1200, 2400, 4800, 9600, 19200 bps	...
Cameras numbers (ID)	0 ... 255	...
Maximal control distance	1200 m	...
Relay maximal load	...	10 A / 250 V AC , 10 A / 30 V DC
Communication standard	RS-485	...
Output	...	4 x NO/NC
Manipulator	3-axis joystick, Speed proportional to the swing (possibility of zoom control by joystick)	...
Display	LCD 2x16 characters	...
Main features	<ul style="list-style-type: none"> • Speed Dome cameras, motor units, Motozoom cameras/lenses support • Admin password 	<ul style="list-style-type: none"> • LED indication • Programming with Arduino IDE or Eclipse tools • The module can be used as an element of IoT (Internet of Things) systems • The Wi-Fi module works in the 2.4 GHz band
Operation temp. / Relative humidity	-20 °C ... 55 °C / ≤ 90 %	...
Power supply	12 V DC / 2 A (power adapter included)	<ul style="list-style-type: none"> • 7 V ... 30 V DC, • 5 V DC, • 90 V ... 250 V AC (power adapter not included)
Weight	0.75 kg	0.09 kg
Dimensions	220 x 130 x 95 mm	93 x 90 x 19 mm
Guarantee	2 years	2 years