






	<a href="#">USB SWITCH US-221A ATEN</a>	<a href="#">TV OR MONITOR MOUNT AX-ORION RED EAGLE</a>	<a href="#">RFID PROXIMITY CARD ATLO-114N*P25</a>	<a href="#">EXTENDER EXT-POE2H IN A HERMETIC CASING PULSAR</a>	<a href="#">POWER DISTRIBUTION UNIT ACAR-S8-DUAL</a>
					
	917.66 CZK 917.66 CZK	445.85 CZK 445.85 CZK	332.31 CZK 332.31 CZK	1716.92 CZK 1716.92 CZK	612.68 CZK 612.68 CZK
Rated voltage	...	...	...	...	230 V AC / 50 Hz
Nominal load current	...	...	...	...	10 A (total)
Standards	...	...	...	PoE : IEEE 802.3at, IEEE 802.3af	...
In package	...	...	<b>25 pcs The price for package</b>	...	...
Input voltage	...	...	...	42 ... 57 V DC	...
Nominal voltage of surge suppressor	...	...	...	...	250 V / 50 Hz
Standard	...	...	Unique EM 125kHz	...	...
Output voltage	...	...	...	42 ... 57 V DC	...
Protection level of surge suppressor	...	...	...	...	≤ 1.3 kV (L/N)
Compatibility	...	...	EM4100/4102	...	...
Number of inputs	...	...	...	1	...
Connectors	...	...	...	...	...
	• 2 x socket USB 2.0 B - Computer interface • 1 x socket USB 2.0 A - Connecting to the device	...	...	...	...
Number of outlets	...	...	...	...	8 grounded outlets 10A/250V
Possibility of programming the serial number (ID)	...	...	—	...	...
Number of outputs	...	...	...	2	...
Length of the cable	180 cm	...	...	...	...
Automatic delayed fuse	...	...	...	...	✓
Ability to write to internal memory	...	...	—	...	...
Mounting standard	...	VESA, 200 x 200, 300 x 200, 300 x 300, 400 x 200, 400 x 300, 400 x 400, 600 x 400	...	...	...
Connector	...	...	...	3 x RJ-45 socket	...
USB standard	2.0	...	...	...	...
Serial Number overprint	...	...	✓	...	...
Nominal stroke current	...	...	...	...	2 kA (L/N) - 8/20 μs
Screen size range	...	37 " ... 70 "	...	...	...
LED indicators	...	...	...	LAN, PoE	...
Bearing capacity	...	40 kg	...	...	...
Maximum stroke current	...	...	...	...	6.5 kA (L/N) - 8/20 μs
Distance from mounting surface	...	33 mm	...	...	...
Color	...	Black	...	...	...
Response time	...	...	...	...	< 25 ns
Tilt adjustment	...	—	...	...	...
Horizontal rotation	...	—	...	...	...
Switch	...	...	...	...	two-way, with light indication
Rotation in the plane of the screen	...	± 3 °	...	...	...

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Main features	<ul style="list-style-type: none"> <li>• LED indication</li> <li>• Support for platforms: Windows, Linux, Mac, Sun</li> <li>• Overload protection</li> <li>• USB A / USB B cable included - 1.8 m</li> </ul>	...	<ul style="list-style-type: none"> <li>• Serial Number Format : 8H10D + WEG24A,</li> <li>• Range : ~ 15 cm,</li> <li>• The TK-4100 chip</li> </ul>	...	...
Length of the cable	...	...	...	...	1.4 m
Supported data rates	...	...	...	<ul style="list-style-type: none"> <li>• Range : 100 m - Input, 100 m - 2 x Output,</li> <li>• Supported data rates 10 / 100 Mbps - Fast Ethernet</li> </ul>	...
Output power	...	...	...	15.4 W / Port PoE OUT 1/2 , max. 20 W (total)	...
Protections	...	...	...	<ul style="list-style-type: none"> <li>• Overvoltage</li> <li>• Overload</li> <li>• Short-circuit</li> </ul>	...
Housing	...	...	...	Plastic, hermetic	Plastic - non-flammable
"Index of Protection"	...	...	...	IP56	...
Operation temp. / Relative humidity	...	...	...	-10 ... 40 °C / 10 ... 90 %	...
Weight	0.05 kg	1.34 kg	0.008 kg	0.55 kg	0.52 kg
Dimensions	72 x 66 x 25 mm	660 x 295 x 33 mm	86 x 54 x 2 mm	198 x 148 x 78 mm	445 x 54 x 55 mm
Manufacturer / Brand	ATEN	RED EAGLE	ATLO	PULSAR	...
Guarantee	2 years	2 years	2 years	2 years	2 years