

	<a href="#">CONNECTION BOX PUH-3P-M19/R</a>	<a href="#">CONNECTION BOX PUH-4P</a>	<a href="#">TV OR MONITOR MOUNT BRATECK-LP42-69T</a>	<a href="#">IP SPEED DOME CAMERA OUTDOOR OMEGA- AI50P18-15 - 5 Mpx 5.35 ... 96.3 mm</a>
				
	56.86 SEK 56.86 SEK	78.59 SEK 78.59 SEK	231.65 SEK 231.65 SEK	3236.79 SEK 3236.79 SEK
Number of intakes	2	2	...	...
Standard	...	...	...	TCP/IP
Sensor	...	...	...	1/2.8 " Progressive Scan CMOS
Number of terminals	2 x 3 pcs	2 x 4 pcs	...	...
Matrix size	...	...	...	5 Mpx
Voltage insulation	400 V	450 V	...	...
Cable diameter	Ø 5 ... Ø 8 mm	Ø 5 ... Ø 9 mm	...	...
Wire gauge	0.5 ... 1.5 mm <sup>2</sup>	0.5 ... 2.5 mm <sup>2</sup>	...	...
Resolution	...	...	...	2592 x 1944 - 5 Mpx , 2560 x 1440 - 4 Mpx , 1920 x 1080 - 1080p 1280 x 720 - 720p
Mounting standard	...	...	VESA 75, 100, 150, 200, 200x100, 300, 400x200 400x300, 400, 600x400, 600, 800x600, 900x600	...
Lens	...	...	...	5.35 ... 96.3 mm
Screen size range	...	...	60 " ... 100 "	...
Bearing capacity	...	...	75 kg	...
Distance from mounting surface	...	...	85 mm	...
Tilt adjustment	...	...	-10 ° ... 5 °	...
View angle	...	...	...	• 59 ° ... 3.6 ° (manufacturer data) • 46 ° ... 3.5 ° (our tests result)
Optical zoom	...	...	...	x 18
Auto IR illuminator	...	...	...	Adaptive adjusting of the IR illuminator power to the lens zoom and outdoor light conditions
Range of IR illumination	...	...	...	120 m
S/N ratio	...	...	...	≥ 50 dB (AGC off)
Video output	...	...	...	—
Rotation speed (manual control)	...	...	...	1 °/s ... 120 °/s (horizontal) 1 °/s ... 60 °/s (vertical)
Horizontal rotation range	...	...	...	360 ° continuous
Vertical rotation range	...	...	...	0 ° ... 93 °
RS-485 interface	...	...	...	—
Number of presets	...	...	...	255
Horizontal scan	...	...	...	✓
Image compression method	...	...	...	H.265 / H.264

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Protections	...	...	...	Overvoltage
Alarm inputs / outputs	...	...	...	—
Network interface	...	...	...	10/100 Base-T (RJ-45)
Network protocols	...	...	...	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, SMTP
Main stream frame rate	...	...	...	<ul style="list-style-type: none"> <li>• 20 fps @ 5 Mpx</li> <li>• 25 fps @ 4 Mpx</li> </ul>
WEB Server	...	...	...	Built-in
ONVIF	...	...	...	✓
Mobile phones support	...	...	...	Port no.: 80 or access by a cloud (P2P) <ul style="list-style-type: none"> <li>• Android: Free application <a href="#">BitVision</a></li> <li>• iOS (iPhone): Free application <a href="#">BitVision</a></li> </ul>
Default IP address	...	...	...	192.168.1.168
Default admin user / password	...	...	...	admin / admin
Web browser access ports	...	...	...	80
Port ONVIF	...	...	...	8999
RTSP URL	...	...	...	rtsp://ip_address/1/h264major - Main stream rtsp://ip_address/1/h264minor - Sub stream
Route settings	...	...	...	3
OSD menu	...	...	...	preset 95
Main features	...	...	...	<ul style="list-style-type: none"> <li>• Intelligent image analysis : intrusion, motion detection based on human detection, video tampering</li> <li>• D-WDR - Wide Dynamic Range</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• LDC - lens distortion correction</li> <li>• ICR - Movable InfraRed filter</li> <li>• BLC - configurable Back Light Compensation</li> <li>• Auto White Balance</li> <li>• IR illuminator optimization</li> <li>• Mirror - Mirror image</li> <li>• Privacy zones - max. 3</li> </ul>
Power supply	...	...	...	12 V DC / 3 A (power adapter included)
Power consumption	...	...	...	≤ 33 W
Housing	...	...	...	Speed Dome, Metal
Color	...	...	Black	White + Black
"Index of Protection"	IP65	IP68	...	IP66
Operation temp	...	...	...	-20 °C ... 60 °C



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Weight	0.036 kg	...	3.7 kg	2.34 kg (with bracket)
Dimensions	99 x 24 x 24 mm	68 x 23 x 23 mm	954 x 625 x 85 mm	340 x 275 x 188 mm (with bracket)
Supported languages	...	...	...	English
Manufacturer / Brand	...	...	...	OMEGA
Guarantee	2 years	2 years	2 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00