



	CRIMP SOCKET N-G/ZAC.H-155	Black body DS-2TE127-G4A Hikvision
		
	3.05 EUR 3.05 EUR	4401.88 EUR 4401.88 EUR
Connector type	"N" Socket	...
Adjusting the reference temperature	...	5 °C ... 50 °C
Attachment of connector elements	Crimping	...
Setting resolution	...	0.1 °C
Shield fastening	Crimping	...
Setting accuracy	...	± 0.1 °C
Wire mounting	Soldering	...
Setting stability	...	± 0.1 °C/h
Application	Coaxial cable	...
Cable diameter	max. 6.1 mm	...
Effective Emissivity	...	0.97 ± 0.02
Size of the reference surface	...	Ø 70 mm
Impedance	50 Ω	...
Material	Metal	...
Example of application	<ul style="list-style-type: none"> • TRI-LAN/100 • H-155 	...
Power supply	...	100 V ... 240 V AC
Power consumption	...	≤ 20 W
Operation temp	...	0 °C ... 40 °C
Main features	<ul style="list-style-type: none"> • Wide frequency range • Corrosion resistance • To crimp use the crimping tool HT-301C 	Possibility to mount on a tripod - 1/4" thread
Weight	0.040 kg	1.85 kg
Dimensions	...	177 x 120 x 120 mm
Manufacturer / Brand	...	Hikvision
SAP Code	...	315800009
Guarantee	2 years	3 years