





	<a href="#">PROGRAMMABLE ELECTRONIC TIME SWITCH GB-104</a>	<a href="#">INSULATION RESISTANCE METER + RCD TESTER UT-582+ UNI-T</a>	<a href="#">ACCESS CONTROLLER DS-K2604T Hikvision</a>	<a href="#">ACCESS POINT 4G LTE-A Wi-Fi 5, +ROUTER TCR100 2.4 GHz, 5 GHz, 433 Mbps</a>
				
	43.99 PLN 43.99 PLN	572.24 PLN 572.24 PLN	3215.00 PLN 3215.00 PLN	829.90 PLN 829.90 PLN
Number of relay outputs	1 pcs NC / NO	...	...	...
AC voltage measurement	...	30 V ... 600 V ± (3% + 3) @ 1 V	...	...
Number of supported readers	...	...	<ul style="list-style-type: none"> <li>• 8 pcs @ RS-485,</li> <li>• 4 pcs @ Wiegand</li> </ul>	...
Battery backup support	...	...	max. 7 Ah	...
Frequency measurement	...	45 Hz ... 65 Hz - frequencies displayed are for illustrative purposes	...	...
Frequency range	...	...	...	<ul style="list-style-type: none"> <li>• Wi-Fi : 2.4 GHz, 5 GHz,</li> <li>• 3G, 4G LTE-A</li> </ul>
Relay maximal load	16 A (max) / 250 V AC (max)	...	...	...
Antenna type	...	...	...	<ul style="list-style-type: none"> <li>• 3 x Omnidirectional antenna Wi-Fi - Internal antenna</li> <li>• 2 x Omnidirectional antenna 4G LTE / SMA connector for connecting an external antenna</li> </ul>
Minimal time interval	60 s	...	...	...
Error	≤ 2 s / 24 h	...	...	...
Standards	...	...	...	IEEE 802.11 b/g/n/ac @ 2.4 GHz IEEE 802.11ac @ 5 GHz
Input lines	...	...	4 pcs - Alarm inputs , 4 pcs - Reed switch , 4 pcs - Door/gate opening button , 9 pcs - Tamper	...
Assembly	DIN TS-35 rail	...	...	...
Output lines	...	...	4 pcs - Lock relay , 4 pcs - Relay	...
Baud rates	...	...	...	<ul style="list-style-type: none"> <li>• Wi-Fi 5 : 433 Mbps,</li> <li>• 4G LTE-A : 300 Mbps</li> </ul>
LAN ports	...	...	...	2 x 10/100 Mbps - LAN

Test of RCDs	...	<ul style="list-style-type: none"> <li>• Working voltage: 220V ± 10 %</li> <li>• Test current: 10mA / 20mA / 30mA / 100mA / 300mA / 500mA</li> <li>• Switch-off time ranges : <ul style="list-style-type: none"> <li>- x 1/2 - 10 / 20 / 30 / 100 / 300 / 500 mA @ 2000 ms</li> <li>- x 1 - 10 / 20 / 30 / 100 / 300 mA @ 1000 ms</li> <li>- x 5 - 500 mA @ 300 ms</li> <li>- AUTO RAMP - 10 / 20 / 30 / 100 / 300 / 500 mA @ 300 ms</li> </ul> </li> <li>• AUTO RAMP test: measurement of shutdown current (with simultaneous measurement of time)</li> </ul>	...	...
Automatic change of measuring ranges	...	—	...	...
RS-232	...	—	...	...
USB	...	—	...	...
LED indicators	...	...	...	INTERNET, WiFi, LTE, Link/Act
Communication	...	...	<ul style="list-style-type: none"> <li>• RS-485,</li> <li>• Ethernet,</li> <li>• Wiegand (w26 / w34),</li> <li>• Open Supervised Device Protocol (OSDP)</li> </ul>	...
SIM socket	...	...	...	1 x Mini SIM - 2FF
DDNS	...	...	...	✓
DHCP server	...	...	...	✓
Protections	...	...	...	WPA2/WPA3 DoS attacks protection, SPI network firewall, domain filtering, IP and MAC filtering, IP and MAC binding
Power supply	<ul style="list-style-type: none"> <li>• 230 V AC,</li> <li>• Battery backup : ≥ 360 h</li> </ul>	6 x 1.5V, type AA/LR6/FR6 battery - included	230 V AC	12 V DC / 1.5 A (power adapter included)
SAP Code	...	...	302913800	...



Main features	<ul style="list-style-type: none"> <li>• Weekly, or daily operation schedule</li> <li>• Ability do program up to 16 ON / OFF operating cycles in a repeated program</li> <li>• LCD display</li> </ul>	<ul style="list-style-type: none"> <li>• Phase switch 0° / 180° during RCD test,</li> <li>• Large, readable LCD display with backlight,</li> <li>• Buzzer,</li> <li>• Low battery level alarm,</li> <li>• Aesthetic and solid construction</li> </ul>	<ul style="list-style-type: none"> <li>• 100000 indexed users</li> <li>• History of 300000 events</li> <li>• Remote programming from PC</li> <li>• Metal housing</li> </ul>	<ul style="list-style-type: none"> <li>• Mini SIM socket</li> <li>The set includes adapters Nano SIM / Micro SIM</li> <li>• The WPS function allows to easy establish an encrypted connection</li> <li>• Internet access filtering</li> <li>• Static / dynamic routing</li> <li>• Wireless transmission statistics</li> <li>• The WPS function allows to easy establish an encrypted connection</li> <li>• Firewall</li> <li>• QoS / Smart Queue Management (SQM)</li> <li>• Rate limit</li> <li>• Remote management</li> <li>• Access control</li> <li>• DMZ</li> <li>• WireGuard VPN client and server support</li> <li>• DMVPN - a method for building scalable VPN IPsec networks</li> </ul>
Operation temp	-10 °C ... 55 °C	0 °C ... 40 °C	-20 °C ... 65 °C	-40 °C ... 75 °C
Permissible relative humidity	...	≤ 80 % (non-condensing)	10 % ... 95 % (non-condensing)	10 % ... 90 % (non-condensing)
Weight	0.12 kg	0.380 kg	4.7 kg	0.42 kg
Dimensions	89 x 65 x 36 mm	160 x 100 x 69 mm	373 x 345 x 98 mm	150 x 37 x 105 mm
Manufacturer / Brand	...	UNI-T	Hikvision	CUDY
Guarantee	2 years	2 years	3 years	2 years