




	<a href="#">SMART LIGHT SWITCH ATLO-WB1-TUYA Wi-Fi, Tuya Smart</a>	<a href="#">WORK GLOVES WG-422/S Bee-Smart WONDER GRIP</a>	<a href="#">MODULATOR TV MT-47</a>
			
	11.55 EUR 11.55 EUR	5.60 EUR 5.60 EUR	38.47 EUR 38.47 EUR
Inputs	...	...	1 pcs Video composite (Cinch) 1 pcs RF (F) 2 pcs audio (Cinch)
Output	...	...	1 pcs RF (F)
Rated voltage	100 ... 240 V AC, 50 / 60 Hz	...	...
Video input frequency range	...	...	20 Hz ... 6 MHz
Application	Works with lighting - switching on/off	<ul style="list-style-type: none"> <li>• Construction and public works,</li> <li>• Warehousing - packing and logistics,</li> <li>• DIY,</li> <li>• Assembly</li> </ul>	...
Maximum power	300 W (for each output)	...	...
Rated current	max. 10 A	...	...
Video input level / impedance	...	...	1 V ± 1 dB / 75 Ω
Number of buttons	1	...	...
Number of outputs	1	...	...
Audio input frequency range	...	...	20 Hz ... 15 kHz
Connector type	screw terminals	...	...
Material	...	Polyester + latex coating (palm coated)	...
Audio input level adjustment	...	...	1 ... -14 dB
Wireless	Wi-Fi, 2.4 GHz - IEEE 802.11 b/g/n	...	...
Audio input level / impedance / deviation	...	...	775 mV RMS / 10 kΩ / 50 kHz
Mobile phones support	<ul style="list-style-type: none"> <li>• The <a href="#">Tuya Smart</a> free application on Android</li> <li>• The <a href="#">Tuya Smart</a> free application on iOS</li> </ul>	...	...
Level (typical) / RF output impedance	...	...	85 dBμV / 75 Ω
RF output level adjustment	...	...	0 ... -20 dB
RF output PAL signal version	...	...	B/G/D/K/H/I/L/M/N/Australia

RF output frequency (channels) range	...	...	170 MHz ... 230 MHz 470 MHz ... 862 MHz (K6-12, K21-69)
Supported norms	...	<ul style="list-style-type: none"> <li>• EN 388:2016 - Mechanical protection 3131X</li> <li>• EN 407:2004 - Thermal protection X1XXXX</li> </ul>	...
Carrier frequency error	...	...	± 50 kHz
Size	...	7 / S	...
Manufacturer / Brand	...	WONDER GRIP	...
Main features	<ul style="list-style-type: none"> <li>• Local control by physical button,</li> <li>• schedule,</li> <li>• timer,</li> <li>• Setting scenarios by different events,</li> <li>• remote access,</li> <li>• voice control,</li> <li>• LED indication</li> </ul>	<ul style="list-style-type: none"> <li>• Thermal protection : 100 °C ( X1XXXX ),</li> <li>• Ergonomics and comfort</li> <li>• High grip</li> <li>• Soft coating</li> </ul>	...
Audio subcarrier frequency	...	...	4.5 ; 5.5 ; 6.0 ; 6.5 MHz
Housing	Plastic	...	...
Fine tuning range of video carrier frequency	...	...	± 2.25 MHz max. with 0.25 MHz step
Color	White	Black + Blue	...
SAT / Terr loop-through loss	...	...	2.5 dB / 1.5 dB
SAT / Terr loop-through frequency range	...	...	47 MHz ... 2150 MHz
Permissible relative humidity	≤ 80 %	...	...
Video frequency response	...	...	± 1 dB
A/V ratio	...	...	12 / 16 dB
Amplitude modulation depth (typical)	...	...	81 %
SNR (weighted)	...	...	≥ 55 dB
Power supply	...	...	230 V AC @ 50Hz
Power consumption	...	...	2.5 W
Operation temp	-20 °C ... 50 °C	...	-10 °C ... 50 °C
Main features	...	...	<ul style="list-style-type: none"> <li>• video carrier frequency adjustment</li> <li>• audio subcarrier modulation depth changing</li> <li>• audio subcarrier from video carrier frequency distance changing</li> <li>• deviation of audio carrier for input level adjustment</li> </ul>
Weight	0.09 kg	...	0.336 kg
Dimensions	87 x 86 x 41 mm	...	133 x 73 x 39 mm

Guarantee	2 years	...	2 years
-----------	---------	-----	---------



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00