

	SWITCH POE APTI-POE0802G-120W-V2 8-PORT	SWITCH POE GTX-A1-06-42 4-PORT
		
	473.29 DKK 473.29 DKK	272.50 DKK 272.50 DKK
LAN ports	10 x RJ45 (8 x PoE (802.3af/at))	<ul style="list-style-type: none"> • 4 x RJ45 (1 x Hi-PoE + 3 x PoE (802.3af/at)), • 2 x RJ45 - Uplink
Management	—	—
LED diodes	LAN, PoE	Power, V - VLAN (Port Isolation), S - Extend, PoE, Link/Act
Transmission speed	<ul style="list-style-type: none"> • 10 / 100 / 1000 Mbps : 2 x Port LAN, • 10 / 100 Mbps : 8 x LAN & PoE ports 	10 / 100 Mbps : 2 x Port LAN - Uplink + 4 x Port LAN & PoE
Manufacturer / Brand	APTI	...
Operation modes	...	<ul style="list-style-type: none"> • N - Normal - the device operates as normal PoE switch • V - VLAN (Port Isolation) - 1 ... 4 ports are isolated from each other and separately work with the 5, 6 ports • S - Extend - Range : 250 m @ 10 Mbps
Maximal output power	30 W / port PoE	<ul style="list-style-type: none"> • 60 W / port Hi-PoE - Port 1 • 30 W / port PoE - 2 ... 4 ports
Maximal total power	120 W	65 W
MAC addresses table	2k	1k

Main features	<ul style="list-style-type: none"> • 2 x Port Uplink • Range PoE : 250 m - The EXTEND mode enabled • Mounts for mounting the device in the RACK 10" system 	<ul style="list-style-type: none"> • MDI/MDI-X auto detection feature - auto detecting the data transmission mode • Full Duplex: IEEE802.3x, Half Duplex: Back Pressure • Auto-learning and Auto-aging functions support for MAC addresses • PD Alive mode - monitoring of the ports that power PoE devices and automatic restart by cutting off the power supply when an unresponsive device is detected • MTBF (Mean Time Between Faults) : 50000 h
Certificates	CE	CE, FCC Class B
Protections	...	Overvoltage ± 3 kV
Power supply	230 V AC	100 ... 265 V AC
Operation temp	-10 °C ... 55 °C	-10 °C ... 55 °C
Weight	0.84 kg	0.6 kg
Dimensions	200 x 118 x 44 mm	190 x 130 x 35 mm
Guarantee	2 years	2 years