



	NVR NVR502-09B 9 CHANNELS UNIVIEW	POWER CORD CABLE CEE-77/1.5M 1.5 m
		
	359.64 EUR 359.64 EUR	3.45 EUR 3.45 EUR
Standard	TCP/IP	...
Supported resolutions	max. 16 Mpx - 4608 x 3472 px	...
Cable	...	3 x 0.75 mm ² / Angular plug (Schuko)
Length of the cable	...	1.5 m
Voltage	...	max. 250 V
Video outputs	1 pcs HDMI 4K 1 pcs VGA There is a possibility to configure a SPOT function on one of the output	...
Current	...	max. 10 A
Main features	...	<ul style="list-style-type: none"> • Very easy and quick assembly • Solid workmanship
Audio support	<ul style="list-style-type: none"> • 9 Channels - Audio from cameras • Bi-directional audio streaming support • Audio detection 	...
Audio inputs	1 pcs CINCH	...
Audio outputs	1 pcs CINCH	...
Image compression method	Ultra 265 / H.265 / H.264	...
Bitrate	max. 320 Mbps	...
Supported hard drives	2 x 8 TB SATA	...
Recording modes	Manual, Sensor, Motion detection, Schedule	...
External storage devices backup	Backup to USB drive (pendrive, external drive)	...
Searching and playback the records	Records searching: by time and events type. Records playback: forward, backward, fast, slow Advanced searching (to the one second accuracy) Records playback from max. 9 channels in the same time	...
Network interface	2 x RJ-45 10/100/1000 Base-TX	...
Network functions	Full support via network, Remote records copying, Web-Server built-in max. 128 on-line users	...

Network protocols	TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE, HTTP, HTTPS, DNS, DDNS, SNMP, SMTP	...
ONVIF	✓	...
Default IP address	DHCP or 192.168.1.30	...
Default admin user / password	admin / 123456	...
Mobile phones support	Port no.: 80 or access by a cloud (P2P) • Android: Free application EZView • iOS (iPhone): Free application EZView	...
Web browser access ports	80, 554	...
PC client access ports	Port no.: 80 or access by a cloud (P2P) - PC: Free application EZStation	...
Mobile client access ports	80	...
RTSP URL	rtsp://192.168.1.30:554/unicast/c1/s0/live - Main stream rtsp://192.168.1.30:554/unicast/c1/s1/live - Sub stream	...
USB	2 x USB 2.0 1 x USB 3.0	...
Serial ports	RS-485	...
Alarm inputs / outputs	8 / 2	...
PTZ control	• PTZ Uniview cameras • RS-485 - PELCO-D/P and others	...
Motion Detection	✓	...
Intelligent image analysis	✓	...

Main features	<p>Functions implemented in cooperation between the recorder and cameras that support these functions</p> <ul style="list-style-type: none"> • Intelligent image analysis : crossing the line (tripwire), intrusion, entering the marked area, leaving the marked area, abandoned/missing object, scene changing, people counting, crowd gathering estimation, objects tracking • Smoke and temperature detection, fire detection • Motion detection with human/vehicle silhouette recognition • Intelligent recognition of the human figure and tracking the movement of a person • SMD PLUS - searching for an object classified as: human, motor vehicle, non-motor vehicle • Corridor mode - useful for monitoring corridors, entrance gates and narrow rooms • VIDEO signal loss alarm • ANR - Automatic Network <p>Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its</p>	...
Mouse support	✓	...
IR remote controller in the set	—	...
Switch PoE	—	...
Power supply	12 V DC / 3.33 A (power adapter included)	...
Power consumption	≤ 20 W (without HDD)	...
Operation temp	-10 °C ... 55 °C	...
Weight	1.7 kg	0.15 kg
Dimensions	380 x 321 x 53 mm	...
Supported languages	Polish, English, Czech, French, Spanish, Dutch, German, Portuguese, Slovak, Italian	...
Manufacturer / Brand	UNIVIEW	...
Guarantee	3 years	2 years