



	TV OR MONITOR MOUNT BRATECK-KL22-22F	IP CAMERA TC-C35XQ SPEC:13W/E/Y/2.8MM/V4.2 - 5 Mpx 2.8 mm TIANDY
		
	8.58 CHF 8.58 CHF	248.66 CHF 248.66 CHF
Standard	...	IP
Mounting standard	VESA : 50, 75, 100, 200 x 100, 200	...
Screen size range	23 " ... 42 "	...
Bearing capacity	35 kg	...
Distance from mounting surface	19.5 mm	...
Tilt adjustment	—	...
Horizontal rotation	—	...
Rotation in the plane of the screen	—	...
Resolution	...	2880 x 1620 - 5 Mpx , 2688 x 1520 - 4 Mpx , 2560 x 1440 - 3.7 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p , 1280 x 720 - 720p
Sensor	...	1/2.8 " Progressive Scan CMOS
Lens	...	2.8 mm
View angle	...	104 °
Range of IR illumination	...	30 m
White light LED illuminator range	...	15 m
Memory card slot	...	Micro SD card support up to 512GB
Image compression method	...	S+265 / H.265 / H.264
Alarm inputs / outputs	...	1 / 1
Audio	...	<ul style="list-style-type: none"> • Microphone built-in, • External microphone input • Audio output • Speaker built-in • Bi-directional audio streaming support • Compliance with the AAC standard
Main stream frame rate	...	<ul style="list-style-type: none"> • 25 fps @ 5 Mpx • 50 fps @ 2 Mpx
Interface	...	10/100 Base-TX (RJ-45)

WEB Server	...	Built-in
Max. number of on-line users	...	2
ONVIF	...	✓
Mobile phones support	...	Port no.: 3000 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application EasyLive Plus • iOS (iPhone): Free application EasyLive Plus
Access from PC	...	Port no.: 3000 or access by a cloud (P2P) - PC: Free application Easy7 Smart Client Express
Default IP address	...	192.168.1.2
Default admin user / password	...	admin / - The administrator password should be set at the first start
Web browser access ports	...	80, 443, 3000, 3002, 23002
Mobile client access ports	...	3000, 3001
PC client access ports	...	3000, 3001
Port ONVIF	...	80
Intelligent image analysis	...	<ul style="list-style-type: none"> • classification of people and vehicles • crossing the line (tripwire) • video tampering • face detection

Main features	...	<ul style="list-style-type: none"> • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • F-DNR (Defog) - Reduction of image noise caused by precipitation • ROI - improve the quality of selected parts of image • NAS - Network Attached Storage support - allows to connect memory resources directly to the computer network • ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its • Corridor mode • AGC - Automatic Gain Control • BLC/HLC - Back Light / High Light Compensation • ICR - Movable InfraRed filter • Day/night mode • Possibility to change the resolution, quality and bit rate • Early Warning (EW) - combination of white light warning with audio signals
Power supply	...	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 670 mA
Power consumption	...	≤ 8 W
Housing	...	Dome - Metal
Color	Black	White
"Index of Protection"	...	IP66
Mechanical protection class	...	—
Operation temp	...	-40 °C ... 65 °C
Weight	0.422 kg	0.52 kg
Dimensions	265 x 222 x 19.5 mm	Ø 117 x 96 mm

Supported languages	...	Polish, English, Albanian, Arabic, Hebrew, Spanish, Dutch, Korean, French, German, Portuguese, Russian, Thai, Turkish, Ukrainian, Vietnamese, Italian
Manufacturer / Brand	BRATECK	TIANDY
Guarantee	2 years	3 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00