




	TV OR MONITOR MOUNT BRATECK-PLB-6N	COAXIAL CABLE TRI- LAN-400 50 Ω	TV OR MONITOR MOUNT BRATECK-LPA78-446
			
	121.45 DKK 121.45 DKK	20.97 DKK 20.97 DKK	91.38 DKK 91.38 DKK
In section	...	100 m . Price for 1m when buying a whole roll	...
Inner conductor	...	Ø 2.7 mm Cu ± 0.02 mm Wire	...
Dielectric	...	Ø 7.2 mm Physical foam	...
Shield	...	Foil - Al/PET	...
Mounting standard	VESA 75, 100, 150, 200, 200x100, 300, 400, 400x200	...	VESA : 75, 100, 100x150, 150x150, 200x100, 200, 300x200, 300, 400x200, 400x300, 400
Screen size range	26 " ... 47 "	...	37 " ... 70 "
Braid	...	168 x Ø 0.15 mm Stranded wire CuSn	...
Bearing capacity	75 kg	...	40 kg
Impedance	...	50 Ω	...
Distance from mounting surface	77 mm	...	67 ... 355 mm
Outer coating	...	Ø 10.3 mm ± 0.20 mm PE	...
Color	Black	...	Black
Tilt adjustment	-15 ° ... 15 °	...	-15 ° ... 3 °
Horizontal rotation	-60 ° ... 60 °
Rotation in the plane of the screen	-3 ° ... 3 °
Weight	3.11 kg	...	3.36 kg
Main features	...	<ul style="list-style-type: none"> • low attenuation • perfect matched • high screening efficiency • it can be used in WLAN 2,4GHz and 5GHz installations • Operation temp : -40 °C ... 70 °C 	...
Dimensions	516 x 508 x 77 mm	...	440 x 420 x (67 ... 355) mm
Manufacturer / Brand	BRATECK

Cable attenuation at 100m section	...	Temperature : 20 °C 2.3 dB @ 30 MHz 3.0 dB @ 50 MHz 4.9 dB @ 150 MHz 6.0 dB @ 220 MHz 8.7 dB @ 450 MHz 12.8 dB @ 900 MHz 17.0 dB @ 1500 MHz 18.8 dB @ 1800 MHz 20.0 dB @ 2000 MHz 22.7 dB @ 2500 MHz 37.6 dB @ 5800 MHz	...
Maximum transmitted power	...	3.36 kW @ 30 MHz 2.59 kW @ 50 MHz 1.47 kW @ 150 MHz 1.20 kW @ 220 MHz 0.82 kW @ 450 MHz 0.57 kW @ 900 MHz 0.43 kW @ 1500 MHz 0.39 kW @ 1800 MHz 0.36 kW @ 2000 MHz 0.32 kW @ 2500 MHz 0.20 kW @ 5800 MHz	...
Guarantee	2 years	2 years	2 years

