



	<a href="#">INDUSTRIAL POE SWITCH GTX-P1-12-82G-V2 8-PORT SFP</a>	<a href="#">IP CAMERA APTI-AI508C3-28W-L Full-Color - 5 Mpx 2.8 mm</a>
		
	133.76 EUR 133.76 EUR	65.52 EUR 65.52 EUR
Standard	...	IP
Sensor	...	1/2.8 " SONY Starvis™ Back-illuminated CMOS
LAN ports	<ul style="list-style-type: none"> <li>• 8 x RJ45 10/100 Base-T ( 2 x Hi-PoE + 6 x PoE (802.3af/at) ),</li> <li>• 2 x RJ45 10/100/1000 Base-T - Uplink,</li> <li>• 2 x Port SFP 1000 Base-X - Uplink</li> </ul>	...
Resolution	...	2880 x 1620 - 5 Mpx , 2592 x 1944 - 5 Mpx , 2560 x 1440 - 3.7 Mpx , 1920 x 1080 - 1080p , 1280 x 720 - 720p
Lens	...	2.8 mm
View angle	...	106 °
Management	—	...
White light LED illuminator range	...	25 m
LED diodes	Power, PoE, Link/Act, Speed, SFP	...
Image compression method	...	H.265+ / H.265 / H.264+ / H.264 / MJPEG
Main stream frame rate	...	25 fps @ 5 Mpx
Network interface	...	10/100 Base-T (RJ-45)
Memory card slot	...	—
Alarm inputs / outputs	...	—
Audio	...	—
Transmission speed	<ul style="list-style-type: none"> <li>• 10 / 100 Mbps : 8 x Port LAN &amp; PoE,</li> <li>• 10 / 100 / 1000 Mbps : 2 x Port RJ45 (Uplink),</li> <li>• 1000 Mbps : 2 x Port SFP (Uplink)</li> </ul>	...
WEB Server	...	Built-in
Max. number of on-line users	...	10
ONVIF	...	✓

RS-485 interface	...	—
Mobile phones support	...	Port no.: 80 or access by a cloud (P2P) <ul style="list-style-type: none"> <li>• Android: Free application <a href="#">BitVision</a></li> <li>• iOS (iPhone): Free application <a href="#">BitVision</a></li> </ul>
Default IP address	...	192.168.1.168
Default admin user / password	...	admin / admin The administrator password should be set at the first start
Operation modes	<ul style="list-style-type: none"> <li>• 250 m ( Extend ) - Range : 250 m @ 10 Mbps</li> <li>• VLAN - 1 ... 8 ports are isolated from each other and separately work with the 9, 10 ports</li> <li>• PD Alive</li> <li>• Port PoE Priority</li> </ul>	...
Web browser access ports	...	80
PC client access ports	...	80
Mobile client access ports	...	80
Port ONVIF	...	80
Maximal output power	<ul style="list-style-type: none"> <li>• 60 W / port Hi-PoE - 1, 2 ports</li> <li>• 30 W / port PoE 802.3af/at - 3 ... 8 ports</li> </ul>	...
RTSP URL	...	rtsp://user:password@ip_address:80/0 - Main stream rtsp://user:password@ip_address:80/1 - Sub stream
Intelligent image analysis	...	<ul style="list-style-type: none"> <li>• intrusion - classification of people and vehicles</li> <li>• crossing the line (tripwire) - classification of people and vehicles</li> <li>• detection of people gathering</li> <li>• loitering detection</li> <li>• motion detection based on human detection</li> </ul>



Main features	<ul style="list-style-type: none"> <li>• Full Duplex: IEEE802.3x, Half Duplex: Back Pressure</li> <li>• MDI/MDI-X auto detection feature - auto detecting the data transmission mode</li> <li>• PD Alive mode - monitoring of the ports that power PoE devices and automatic restart by cutting off the power supply when an unresponsive device is detected</li> <li>• Ports 1 ... 8 support transmission priorities</li> <li>• The ability to connect two power adapters - redundant power supply</li> <li>• Industrial wide temperature design.</li> <li>• MTBF (Mean Time Between Faults) : 50000 h</li> <li>• "Index of Protection" : IP40</li> <li>• Devices for mounting on a DIN, TS-35 rail</li> </ul>	...
Certificates	CE, FCC, RoHS	...
Protections	<ul style="list-style-type: none"> <li>• Overvoltage : 6 kV</li> <li>• Contact/Air (ESD/EMP) : 6/8 kV</li> </ul>	...
Main features	...	<ul style="list-style-type: none"> <li>• WDR - 120 dB - Wide Dynamic Range</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• Anti-Flicker - The technology eliminates the tiring eyes flickering image effect</li> <li>• F-DNR (Defog) - Reduction of image noise caused by precipitation</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• BLC - Back Light Compensation</li> <li>• HLC - High Light Compensation (spot)</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• Possibility to change the resolution, quality and bit rate</li> <li>• ICR - Movable InfraRed filter</li> <li>• Motion Detection</li> <li>• Privacy zones</li> <li>• Mirror - Mirror image</li> <li>• Sharpness - sharper image outlines</li> </ul>



Power supply	48 ... 57 V DC - 2.1/5.5 mm socket or screw terminals (power adapter not included)	<ul style="list-style-type: none"> <li>• PoE (802.3af),</li> <li>• 12 V DC / 340 mA</li> </ul>
Power consumption	...	≤ 4.1 W
Operation temp	-30 °C ... 65 °C	...
Housing	...	Compact - Metal
Color	...	White
"Index of Protection"	...	IP67
Operation temp	...	-20 °C ... 60 °C
Weight	0.74 kg	0.42 kg
Dimensions	165 x 125 x 54 mm	172 x 73 x 73 mm
Supported languages	...	Polish, English, Bulgarian Czech, French, Spanish, Dutch, German, Portuguese, Russian, Turkish, Italian
Manufacturer / Brand	...	APTI
Guarantee	2 years	2 years