



	<a href="#">SET OF LED LUMINAIRES ZSO-01/3000 ZAMEL</a>	<a href="#">LED LIGHTING CONTROLLER FUT035S 2.4 GHz, CCT 12 ... 24 V DC MiBOXER / Mi-Light</a>
		
	76.70 EUR 76.70 EUR	4.75 EUR 4.75 EUR
Support	SUPLA	...
Rated voltage	...	12 ... 24 V DC
Maximal total load	...	<ul style="list-style-type: none"> <li>• 144 W @ 12 V,</li> <li>• 288 W @ 24 V</li> </ul>
Total maximal current	...	12 A
Wireless	Wi-Fi, 2.4 GHz - IEEE 802.11 b/g/n	2.4 GHz
Radio communication range (at open area)	...	30 m
Mobile phones support	<ul style="list-style-type: none"> <li>• The <a href="#">SUPLA</a> free application on Android</li> <li>• The <a href="#">SUPLA</a> free application on iOS</li> </ul>	Access by a cloud (P2P) <ul style="list-style-type: none"> <li>• The <a href="#">Tuya Smart</a> free application on Android</li> <li>• The <a href="#">Tuya Smart</a> free application on iOS</li> </ul>
Main features	<ul style="list-style-type: none"> <li>• Control from a Web browser,</li> <li>• Local control by physical button,</li> <li>• schedule,</li> <li>• timer,</li> <li>• remote access,</li> <li>• voice control,</li> <li>• Possibility to manually program scenarios from the built-in API</li> </ul>	The repeater function allows you to transfer control to subsequent FUT035S / FUT036S / FUT038S / FUT039 modules even beyond the direct range of the remote control
Housing	Plastic	Plastic
Application	Lighting control	Works with LED lighting - white LED strips with adjustable color temperature (CCT) 12-24V
Color	...	White
Number of outputs	1 pcs	2 (power)
Manufacturer / Brand	ZAMEL	MiBOXER / Mi-Light
Guarantee	2 years	2 years
Light color	Warm - 3000 K Warm - 3000 K	...
Illumination angle	120 ° 120 °	...

Seating depth of the luminaire	38 mm 38 mm	...
Montage hole diameter	Ø 75 mm ... 80 mm Ø 75 mm ... 80 mm	...
Number of inputs	1 pcs 1	1
Power voltage	24 V DC 24 V AC	...
Current consumption	350 lm / 3.5 W 350 lm / 3.3 W	...
Connector type	screw terminals screw terminals screw terminals	<ul style="list-style-type: none"> <li>• screw terminals,</li> <li>• 5.5/2.1 socket / screw terminals - power input</li> </ul>
"Index of Protection"	IP20 IP44	...
Operation temp	-10 °C ... 55 °C	-10 °C ... 40 °C
Number of elements	8 3 3	...
Material	Plastic	...
Weight	0.079 kg 0.068 kg 0.019 kg	0.03 kg
Dimensions	78 x 73 x 40 mm 78 x 72 x 35 mm Ø 105 x 7 mm	75 x 36 x 17 mm