




	STYROFOAM PLUG FISCHER FID-50	CHALK LINE REEL ST-0-47-100 STANLEY	POWER DISTRIBUTION UNIT ACAR-S8-DUAL
			
	0.82 EUR 0.82 EUR	11.10 EUR 11.10 EUR	24.15 EUR 24.15 EUR
Line length	...	30 m	...
Length	50 mm
Rated voltage	230 V AC / 50 Hz
Diameter	Ø 25 mm
Nominal load current	10 A (total)
Thickness of the Styrofoam	≥ 50 mm
Application	...	<ul style="list-style-type: none"> • For use in masonry work, • Electrical works, such as marking lines for pipes, trays or lines for lighting lamps 	...
Diameter of the screw	Ø 4.5 mm / Ø 5 mm
Nominal voltage of surge suppressor	250 V / 50 Hz
Protection level of surge suppressor	≤ 1.3 kV (L/N)
Main features	...	<ul style="list-style-type: none"> • Universal hook at the end of the line • Can be used as a vertical • A container for chalk powder 	...
Number of outlets	8 grounded outlets 10A/250V
Automatic delayed fuse	✓
Nominal stroke current	2 kA (L/N) - 8/20 µs
Maximum stroke current	6.5 kA (L/N) - 8/20 µs
Manufacturer / Brand	...	STANLEY	...
Response time	< 25 ns
Switch	two-way, with light indication
Length of the cable	1.4 m
Housing	...	Aluminum, Waterproof	Plastic - non-flammable
Weight	0.004 kg	0.3 kg	0.52 kg
Dimensions	...	120 x 75 x 44 mm	445 x 54 x 55 mm
Guarantee	2 years	2 years	2 years