

	EXTENDER VGA TRVGA-300-P	CABLE 2C-WJ-W2.5-1.5MB 1.5 m	ACCESS CONTROLLER WITH TEMPERATURE MEASUREMENT OPTI-AI70FRD-V2 4.5 mm - 1080p	SWITCH POE IP-9-11-L2 8-PORT ATTE	SET OF 2 PMR RADIOS MOTOROLA-T62/RED 446.1 MHz... 446.2 MHz
					
	123.42 EUR 123.42 EUR	3.31 EUR 3.31 EUR	58.25 EUR 58.25 EUR	182.77 EUR 182.77 EUR	56.83 EUR 56.83 EUR
In package	2 pcs
Frequency range	446.1 MHz ... 446.2 MHz
Scanning system	Progressive
Frequency step	12.5 kHz
Number of memory channels	16
Cable	...	2 x CINCH Plug / JACK 2.5 mm Plug STEREO
Optical zoom	—
Length of the cable	...	1.5 m
Output power	0.5 W
LAN ports	• 1 x RJ45 10/100 Base-T - Uplink • 9 x RJ45 10/100 Base-T + PoE (802.3af/at) / Passive PoE	...
Antenna connector	—
Speaker built-in	✓
Function offset (for repeater access)	—
Management	—	...
Selective call	✓
Sensor	1/2.8 " SONY Starvis™ Back-illuminated CMOS 1/5 " GC2145
Matrix size	2.1 Mpx 2 Mpx
Keyboard lock	✓
LED diodes	Power, LAN	...
Pixel pitch	1.75 µm
Modulation type	F3E (FM)
Lens	4.5 mm 2.4 mm
View angle	68 ° 70 °
Transmission speed	10 / 100 Mbps : 1 Port LAN + 9 LAN & PoE ports	...
Standard	TCP/IP
Range of IR illumination	5 m
White light LED illuminator range	5 m
Device type	Active / Transmitter Active / Receiver
Temperature measurement	✓
Number of channels	1 VGA 1 VGA
Temperature measurement range	35 °C ... 42 °C

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Accuracy of temperature measurement	± 0.3 °C
Video transmission range	max. 300 m max. 300 m
Symmetrical socket impedance	100 Ω 100 Ω
Maximal output power	<ul style="list-style-type: none"> • 40 W @ Passive PoE - 1 ... 4 ports, • 70 W @ Passive PoE - Port 5, • 30 W @ PoE (802.3af/at) - 1 ... 5 ports 	...
Maximal total power	96 W	...
Face recognition distance	0.5 m ... 1.5 m (max 30 000 faces in the database)
Connectors type	VGA Socket VGA Socket female
Symmetrical socket type	RJ-45 (8-pin, 4 pairs) Socket RJ-45 (8-pin, 4 pairs) Socket
Temperature measurement distance	0.5 m ... 1.3 m optimal distance : 0.75 m
Internal memory	Support storage of 25 000 records
Video output	—
RS-485 interface	✓
Wiegand interface	✓
Memory card slot	—
Operation modes	<ul style="list-style-type: none"> • Normal : 100 m @ 10/100 Mb/s - 1 ... 5 ports • Long Range : 280 m @ 10 Mb/s - 1 ... 4 ports ; 100 m @ 10/100 Mb/s - Port 5 	...
Alarm inputs / outputs	0 / 2 (bolt control, signaling of exceeding the temperature)
Audio	Speaker built-in
Resolution	<ul style="list-style-type: none"> • 1920 x 1200 / 80 Hz @ 100 m • 1024 x 768 / 60 Hz @ 300 m 	...	1920 x 1080 - 1080p 800 x 600 - 0.48 Mpx



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Main features	<ul style="list-style-type: none"> • Short-circuit protection • Signal correction 	<ul style="list-style-type: none"> • Very easy and quick assembly 	...	<ul style="list-style-type: none"> • Possible cascading device connection (power transmission between devices using Passive PoE via LAN 5 port) • The LAN 5 (PoE IN/OUT) port can be used to power PoE devices as well as to draw power from other devices • The output PoE voltage is equal to the input voltage • The ability to independently turn on and off the PoE power for each of the LAN 1 ... LAN 5 ports • The modular design streamlines service tasks and enables quick and easy system expansion • The raster system of module assembly facilitates the expansion of the device by further modules • The ABOX-L2 mounting enclosure is equipped with 11 cable entries with glands in the 10 x M16 + 1 x M20 arrangement 	...
Network interface	10/100 Base-T (RJ-45)
Network protocols	IPv4, HTTP, HTTPS, TCP/IP
WEB Server	Built-in
Max. number of on-line users	20
ONVIF	—
RS-485	✓
Default IP address	DHCP / 192.168.1.88
Default admin user / password	admin / 12345
Web browser access ports	7080
PC client access ports	7080
Main features	<ul style="list-style-type: none"> • Built-in LCD display showing the image from the video camera and the result of temperature measurement - 1024 x 600 px • Wiegand 26 • Day/Night mode (color/b&w/auto) • RESET button • Relay output operating modes: access control or notification of an exception 	...	<ul style="list-style-type: none"> • Battery charge indicator • Large, readable LCD display with backlight • Support for CTCSS and DCS codes • Channel scan function • Possibility to scan 2 channels at the same time • Voice operated transmission activation function (VOX) • Call sound • End of broadcast sound • Easy pairing function
Power supply	12 V / 70 mA (power adapter not included) 12 V / 170 mA (power adapter not included)	...	12 V DC	230 V AC - cable terminals	3 x 1.2 V Ni-MH batteries (included) or 3 x 1.5V, type AA/LR6/FR6 battery
Power consumption	≤ 12 W
Housing	Compact - Metal
Color	Silver	...	Black + Red
"Index of Protection"	IP66
Operation temp	15 °C ... 25 °C - temperature measurement only in closed rooms (stabilized temperature)

Weight	0.078 kg 0.078 kg	0.050 kg	0.94 kg	1.05 kg	0.15 kg
Dimensions	118 x 30 x 48 mm 118 x 30 x 54 mm	...	305 x 112 x 59 mm	248 x 222 x 96 mm	165 x 54 x 31 mm
Montage hole diameter	33 mm
Length of the cable	64 cm
Supported languages	Polish, English, French, Spanish, German, Portuguese, Russian, Turkish, Italian
Manufacturer / Brand	DELTA	...	APTI	ATTE	Motorola
Guarantee	3 years	2 years	3 years	3 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00