




	<a href="#">WIRED DOORBELL OR-DP-VD-145/W/8V ORNO</a>	<a href="#">EXTENDER VGA + USB CE-100</a>	<a href="#">EXTENDER ETHERNET+PoE LR1002-1ET-V3 TRANSMITTER DAHUA</a>
			
	121.27 NOK 121.27 NOK	1697.34 NOK 1697.34 NOK	301.87 NOK 301.87 NOK
LAN ports	...	...	1 pcs RJ45
Signaling mode	Sound signaling	...	...
Transmission ports	...	...	1 pcs BNC
Number of ring-tones	1 - Two alternating ring tones	...	...
Transmission speed	...	...	10 / 100 Mbps
Volume adjustment	—	...	...
Color	White	...	...
"Index of Protection"	IP20	...	...
Transmission range	...	...	max. 1000 m @ 10 Mbps max. 400 m @ 100 Mbps The range of data transfer and power supply is strongly dependent on the cable used and the power required to supply the receiver
Protections	...	...	Overvoltage
Manufacturer / Brand	ORNO	...	DAHUA
Device type	...	<b>Active / Transmitter</b>  <b>Active / Receiver</b>	...
Number of channels	...	1 x VGA 2 x USB 1 x VGA 2 x USB	...
Power supply	8 V AC	5 V / 1000 mA 5 V USB	• ePoE • PoE (802.3af/at)
Video transmission range	...	max. 100 m max. 100 m	...
Connectors type	...	1 x VGA Socket HDB-15 2 x USB-A Socket 1 x VGA Plug HDB-15 1 x USB-B Socket	...

Symmetrical socket type	...	RJ-45 (8-pin, 4 pairs) Socket RJ-45 (8-pin, 4 pairs) Socket	...
Weight	0.11 kg	0.170 kg 0.170 kg	0.07 kg
Dimensions	92 x 92 x 40 mm	91 x 56 x 25 mm 91 x 56 x 25 mm	79 x 64 x 23 mm
Main features	Simple and quick device installation	<ul style="list-style-type: none"> <li>• Real-time DDC communication support</li> <li>• Built-in ESD protection 8 / 15 kV</li> <li>• Manual compensation adjustment</li> <li>• Possibility to mount to the wall</li> </ul>	<ul style="list-style-type: none"> <li>• Plug &amp; Play</li> <li>• MDI/MDI-X auto detection feature - auto detecting the data transmission mode</li> <li>• Support for IP cameras and network devices</li> <li>• Easy installation - doesn't require any configuration of IP nor MAC address</li> <li>• Power supply PoE - pins 1, 2 and 3, 6</li> <li>• The device operates from the camera side</li> <li>• Possibility to mount on a wall, or on the DIN TS-35 rail</li> <li>• UTP cable length to the camera max. 2 m</li> </ul>
Resolution	...	<ul style="list-style-type: none"> <li>• 1920 x 1080 / 60 Hz @ 30 m</li> <li>• 1920 x 1200 / 60 Hz @ 30 m</li> <li>• 1280 x 1024 / 60 Hz @ 100 m</li> </ul>	...
Guarantee	2 years	2 years	3 years