



	ADAPTER AD-UTP-2W/2G 2 x RJ45	IP SPEED DOME CAMERA OUTDOOR DS-2DE4A225IWG-E - 1080p 4.8 ... 120 mm Hikvision
		
	9.01 AUD 9.01 AUD	1445.26 AUD 1445.26 AUD
Standard	...	TCP/IP
Sensor	...	1/2.8 " Progressive Scan CMOS
Matrix size	...	2.1 Mpx
Connectors type	<ul style="list-style-type: none"> • 1 Adapter : 2 x RJ-45 plug + 1 x RJ-45 socket • 2 Adapter : 3 x RJ-45 socket 	...
Length of the cable	3 cm	...
Resolution	...	1920 x 1080 - 1080p 1280 x 960 - 1.3 Mpx 1280 x 720 - 720p
Lens	...	4.8 ... 120 mm
View angle	...	55 ° ... 2.7 °
Optical zoom	...	x 25
Digital zoom	...	x 16
Range of IR illumination	...	50 m
Video output	...	—
Preset rotation speed	...	<ul style="list-style-type: none"> • 350 °/s (horizontal) • 200 °/s (vertical)
Rotation speed (manual control)	...	0.1 °/s ... 300 °/s (horizontal) 0.1 °/s ... 160 °/s (vertical)
Horizontal rotation range	...	360 ° - continuous
Vertical rotation range	...	-5 ° ... 90 °
RS-485 interface	...	—
Number of presets	...	300
Horizontal scan	...	✓
Route settings	...	8
Image compression method	...	H.265+ / H.265 / H.264+ / H.264 / MJPEG
Alarm inputs / outputs	...	2 / 2
Audio	...	<ul style="list-style-type: none"> • External microphone input • Audio output • Bi-directional audio streaming support • Audio detection
Main stream frame rate	...	50 fps @ 1080p
Network interface	...	10/100 Base-T (RJ-45)
WEB Server	...	Built-in, NVR compliance
Max. number of on-line users	...	20
ONVIF	...	—

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Memory card slot	...	Micro SD memory cards up to 256GB support (possible local recording)
Mobile phones support	...	Port no.: 8000 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application Hik-Connect • iOS (iPhone): Free application Hik-Connect
Default admin user / password	...	admin / - The administrator password should be set at the first start
Default IP address	...	192.168.1.64
Web browser access ports	...	80
PC client access ports	...	Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application
Mobile client access ports	...	8000
Port ONVIF	...	80
RTSP URL	...	<ul style="list-style-type: none"> • Main stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/ • Sub stream : rtsp://192.168.1.64:554/Streaming/Channels/102/ - RTSP - with authorization
Main features	...	<ul style="list-style-type: none"> • Intelligent Object Tracking • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • ROI - improve the quality of selected parts of image • F-DNR (Defog) - Reduction of image noise caused by precipitation • ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its • NAS - Network Attached Storage support - allows to connect memory resources directly to the computer network • BLC - Back Light Compensation • HLC - High Light Compensation (spot) • ICR - Movable InfraRed filter • Configurable Privacy Zones - 24 • Motion Detection • Sharpness - sharper image outlines • Day/Night mode (color/b&w/auto) • Parking action - this function enables to locate the camera to specific position automatically if operator doesn't operate the controller for some time • Intelligent image analysis : crossing the line (tripwire), intrusion, detection of entry into the area / exit from the area - classification of people and vehicles, abandoned/missing object, face detection, advanced face capture features
Power supply	...	<ul style="list-style-type: none"> • PoE (802.3at), • 12 V DC / 2 A (power adapter included)
Power consumption	...	≤ 24 W
Housing	...	Speed Dome, Metal
Color	...	White
Operation temp	...	-30 °C ... 65 °C

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

"Index of Protection"	...	IP66
Weight	0.05 kg (total)	2.6 kg
Dimensions	<ul style="list-style-type: none"> • 1 Adapter : 115 x 19 x 19 mm • 2 Adapter : 120 x 40 	Ø 169 x 161 mm
Supported languages	...	Polish, English
Manufacturer / Brand	...	Hikvision
SAP Code	...	327000854
Guarantee	2 years	3 years

