



	<a href="#">ACCESS CONTROLLER WITH TEMPERATURE MEASUREMENT DS-K1TA70MI-T - 1080p Hikvision</a>	<a href="#">VOLTAGE CONVERTER MOD-DC-12V ACO</a>
		
	1818.64 EUR 1818.64 EUR	15.24 EUR 15.24 EUR
Type	...	Decreasing the voltage
Power voltage	...	14 V ... 16 V DC
Scanning system	Progressive	...
Output voltage	...	12 V DC
Output current	...	0.5 A (max)
Resolution	1920 x 1080 - 1080p	...
Power	...	6 W (max)
Application	...	reversible electric door strikes
Sensor	CMOS Uncooled VOx microbolometer	...
Matrix size	2.1 Mpx 120 x 160 px	...
Temperature measurement	✓	...
Protections	...	<ul style="list-style-type: none"> <li>• Overheat</li> <li>• Overload</li> <li>• Short-circuit</li> </ul>
Temperature measurement range	30 °C ... 45 °C	...
Accuracy of temperature measurement	± 0.5 °C	...
Temperature measurement distance	0.3 ... 1.8 m	...
Cards support	13.56 MHz S50	...
Reading distance of prox-keys	~ 5 cm	...
Face recognition distance	0.3 m ... 1.8 m	...
Memory	Memory of 6000 face templates Memory of 6000 RFID cards Non-volatile log buffer of the last 100 000 events	...
Standard	TCP/IP	...

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

IR illuminator	✓	...
LED illuminator	✓	...
Video output	—	...
RS-485 interface	✓	...
Memory card slot	—	...
Alarm inputs / outputs	2 / 1	...
Audio	Speaker built-in	...
Network interface	10/100/1000 Base-T (RJ-45)	...
Network protocols	TCP/IP	...
WEB Server	—	...
ONVIF	—	...
RS-485	✓	...
Default IP address	192.168.1.64	...
Default admin user / password	admin / - The administrator password should be set at the first start	...
PC client access ports	port 8000	...
Main features	<ul style="list-style-type: none"> <li>• Detection of people without a mask - access denied or voice alerts</li> <li>• Temperature measurement</li> <li>• 7 " capacitive touch screen - 1024 x 600 px</li> <li>• Mechanical tamper protection</li> <li>• Wiegand 34/26</li> <li>• AGC - Automatic Gain Control</li> <li>• Sharpness - sharper image outlines</li> <li>• Day/Night mode (color/b&amp;w/auto)</li> <li>• AI detection : A solution dedicated to measuring temperature. The camera is able to detect increased object temperature</li> </ul>	...
Power supply	12 V DC / 2 A (power adapter not included)	...

Power consumption	≤ 24 W	...
Housing	Compact - Metal	...
Color	Silver + Black	...
"Index of Protection"	—	...
Operation temp	0 °C ... 50 °C	...
Weight	1.34 kg	0.018 kg
Dimensions	117 x 290 x 35 mm (without bracket)	54 x 31 x 15 mm
Supported languages	Polish, English, French, Spanish, Portuguese, Russian, Italian	...
Manufacturer / Brand	Hikvision	ACO
SAP Code	302917212	...
Guarantee	3 years	2 years