



	PANEL WITH CABLE ENTRY A19-PK-V2	SWITCH POE IP-5-11-M2 5-PORT ATTE
		
	5.38 EUR 5.38 EUR	114.06 EUR 114.06 EUR
Width	19 "	...
Height	1 U	...
Material	Steel - powder painted	...
Color	Black (RAL 9005)	...
Application	RACK 19"	...
LAN ports	...	<ul style="list-style-type: none"> • 1 x RJ45 10/100 Base-T - Uplink • 5 x RJ45 10/100 Base-T + PoE (802.3af/at) / Passive PoE
Management	...	—
LED diodes	...	Power, LAN
Transmission speed	...	10 / 100 Mbps : 1 Port LAN + 5 LAN & PoE ports
Maximal output power	...	<ul style="list-style-type: none"> • 40 W @ Passive PoE - 1 ... 4 ports, • 70 W @ Passive PoE - Port 5, • 30 W @ PoE (802.3af/at) - 1 ... 5 ports
Maximal total power	...	96 W
Operation modes	...	<ul style="list-style-type: none"> • Normal : 100 m @ 10/100 Mb/s - 1 ... 5 ports • Long Range : 280 m @ 10 Mb/s - 1 ... 4 ports ; 100 m @ 10/100 Mb/s - Port 5 • Port LAN 6 - Uplink

Main features	<ul style="list-style-type: none"> • Dimensions of the cable entry hole : 380 x 30 mm (one edge open) • The entry is covered with a brush • 4-point fixing to the front RACK rails • 4 pcs. of M6 screws with cage nuts included • Corrosion resistance 	<ul style="list-style-type: none"> • Possible cascading device connection (power transmission between devices using Passive PoE via LAN 5 port) • The ability to independently turn on and off the PoE power for each of the LAN 1 ... LAN 5 ports • The modular design streamlines service tasks and enables quick and easy system expansion • The raster system of module assembly facilitates the expansion of the device by further modules • The ABOX-M2 mounting enclosure is equipped with 7 cable entries with glands in the 6 x M16 + 1 x M20 arrangement
Power supply	...	230 V AC - cable terminals
Weight	0.21 kg	0.65 kg
Dimensions	483 x 44 x 12 mm	226 x 148 x 80 mm
Manufacturer / Brand	...	ATTE
Guarantee	2 years	3 years