

| | VANDALPROOF CAMERA DP-954HHDJRD STANDARD_PAL_1000 TVL 2.8 mm | TV OR MONITOR MOUNT AKXTYAN-ALUX | TOGGLE PLUG DUOTEK-10/SPH Fischer | TV OR MONITOR MOUNT BRATECKI-PA68-221 | DOOR FOR 96-MODULAR DISTRIBUTION CABINETS LE-387254 XL S 160 LEGRAND | DIGITAL TIMER OR PRE-409 ORNO | POWER DISTRIBUTION UNIT LE-049475 (4 OUTLETS) 1.5 m I.EGRAND | EXTENSION CABLE PS-2X1-5-30M ORANGE 30 m | POWER DISTRIBUTION UNIT LE-042484 (6 OUTLETS) 1.5 m I.EGRAND | SWITCH FOR RJ-9-11-12 RJ- PORT ATTE |
|-------------------------------------|---|---|---|---|---|---|--|---|---|--|
| |  |  |  |  |  |  |  |  |  |  |
| Standard | 49.11 EUR 49.11 EUR | 105.52 EUR 105.52 EUR | 1.13 EUR 1.13 EUR | 7.26 EUR 7.26 EUR | 80.21 EUR 80.21 EUR | 13.68 EUR 13.68 EUR | 12.55 EUR 12.55 EUR | 19.87 EUR 19.87 EUR | 16.41 EUR 16.41 EUR | 182.69 EUR 182.69 EUR |
| Device type | PAL | | | | | Digital timer | | | | |
| Sensor | 1/3" Sony EXMOR CMOS | | | | | | | | | |
| Maximal current | | | | | | 16 A | | | | |
| Transparent door | | | | | | | | | | |
| Maximal load | | | | | | 3680 W | | | | |
| Rated voltage | | | | | | | 230 V AC / 50 Hz | 230 V AC / 50 Hz | 230 V AC / 50 Hz | |
| Material | | | | | | | | | | |
| Matrix size | 1.3 Mpx | | | | | | | | | |
| Measuring accuracy | | | | | | | | | | |
| Total maximal current | | | | | | ≤ 1 minute / month | | | | |
| Drilling diameter | | | 10 mm | | | | 16 A | 10 A | 16 A | |
| Resolution | 1000 TVL | | | | | | | | | |
| Mounting standard | | VESA : 200, 300, 400 x 200, 400, 600 x 400 | | VESA : 100, 200, 200x100 | | | | | | |
| Maximal total load | | | | | | | 3680 W | 2500 W | 3680 W | |
| Expansion plug length | | | 40 mm | | | | | | | |
| Lens | 2.8 mm | | | | | | | | | |
| Number of outlets | | | | | | | 4 grounded outlets 16A/250V CEE 7/5 | 1 x CEE 7/17 | 6 grounded outlets 16A/250V CEE 7/5 | |
| Material | | | | | Steel | | | | | |
| LAN ports | | | | | | | | | | 1 x RJ45 10/100 Base-T - Uplink 9 x RJ45 10/100 Base-T + PoE (802.3af/at) / Passive PoE |
| Screen size range | | 37" ... 70" | | 23" ... 43" | | | | | | |
| Fuse | | | | | | | | | | |
| Screw dimensions | | | Ø 5 x 60 mm | | | | | | | |
| Timing range | | | | | | 1 minute ... 168 hours (7 days) | | | | |
| Bearing capacity | | 45 kg | | 30 kg | | | | | | |
| Switch | | | | | | | | | | |
| Wire gauge | | | | | | | 3 x 1.0 mm ² | 2 x 1.5 mm ² | 3 x 1.0 mm ² | |
| Length of the cable | | | | | | | 1.5 m | 30 m | 1.5 m | |
| Mounting panel thickness | | | 9.5 ... 55 mm | | | | | | | |
| Management | | | | | | | | | | |
| View angle | • 81° (manufacturer data) • 90° (our tests result) | | | | | | | | | |
| The maximum countdown time | | | | | | 99 hours 59 minutes | | | | |
| Distance from mounting surface | | 54 ... 448 mm | | 56 ... 204 mm | | | | | | |
| Safety class | | | | | Grade 2 | | | | | |
| Cavity depth | | | min. 40 mm | | | | | | | |
| Range of IR illumination | 20 m | | | | | | | | | |
| Compliance with standards | | | | | IEC 60695-2-1 | | | | | |
| LED diodes | | | | | | | | | | Power, LAN |
| Video output | 1 Vpp 75 Ω | | | | | | | | | |
| Tilt adjustment | ±15° ... 15° | | | ±8° ... 5° | | | | | | |
| Transmission speed | | | | | | | | | | 10 / 100 Mbps - 1 Port LAN + 9 LAN & PoE ports |
| Horizontal rotation | ±60° ... 60° | | | ±90° ... 90° | | | | | | |
| Rotation in the plane of the screen | ± 3° | | | | | | | | | |
| Application | | | | | Distribution cabinets 4 x 24-modular - XL S 160 | | | | | |
| Security class | | | | | | IP20 | | | | |
| Socket type | | | | | | 2P+Z, E type | | | | |
| Main features | • ICR - Movable InfraRed filter • DNR - Digital Noise Reduction • WDR - Wide Dynamic Range • Privacy zones - max. 8 • Motion Detection - max. 4 zones • Mirror - Mirror image • Auto White Balance • Sharpness - sharper image outlines • Day/Night mode (color/b&w/auto) | | | | | | | | | |
| OSD menu | ✓ | | | | | | | | | |
| Vandal-proof | ✓ | | | | | | | | | |
| Maximal output power | | | | | | | | | | • 40 W @ Passive PoE - 1 ... 4 ports • 70 W @ Passive PoE - Port 5 • 30 W @ PoE (802.3af/at) - 1 ... 5 ports |
| Maximal total power | | | | | | | | | | 96 W |
| Housing | Domed - Metal | | | | | | | | | |
| Color | Black | Silver / Black | | Black | White | Plastic | Plastic | White / Light gray | Orange | Plastic / Gray |
| "Index of Protection" | IP65 | | | | | | | | | |
| Operation voltage | | | | | | 175 ... 276 V AC, 45 ... 65 Hz | | | | |
| Operation temp | -10 °C ... 45 °C | | | | | 0 °C ... 50 °C | | | | |
| Operation modes | | | | | | | | | | • Normal : 100 m @ 10/100 Mbps - 1 ... 5 ports • Long Range : 280 m @ 10 Mbps - 1 ... 4 ports ; 100 m @ 10/100 Mbps - Port 5 |

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

| | | | | | | | | | | |
|----------------------|---------------|-----------------------------|---------|-----------------------------|---|---|------------------|---------|---|----------------------------|
| Main features | | | | | <ul style="list-style-type: none"> • Reversible door • 1 closing point • Supplied with handle in the kit | <ul style="list-style-type: none"> • Time settings for switching electrical devices on and off • 16 programs • Manual or random on / off • 16 weekday combinations • Daylight saving (summer) and winter time function • 12 or 24 hour mode • Count down function • Large, readable LCD display • built-in battery | | | <ul style="list-style-type: none"> • Possible cascading device connection (power transmission between devices using Passive PoE via LAN 5 port) • The LAN 5 (PoE IN/OUT) port can be used to power PoE devices as well as to draw power from other devices • The output PoE voltage is equal to the input voltage • The ability to independently turn on and off the PoE power for each of the LAN 1 ... LAN 5 ports • The modular design streamlines service tasks and enables quick and easy system expansion • The raster system of module assembly facilitates the expansion of the device by further modules • The ABOX-L2 mounting enclosure is equipped with 11 cable entries with glands in the 10 x M16 + 1 x M20 arrangement | |
| Power supply | 12 V / 270 mA | ... | ... | ... | ... | 230 V AC, 50 Hz • built-in battery | ... | ... | ... | 230 V AC - cable terminals |
| Weight | 0.37 kg | 4.76 kg | ... | 1.03 kg | 4.9 kg | 0.15 kg | 0.33 kg | 2.3 kg | 0.39 kg | 1.05 kg |
| Dimensions | Ø 94 x 70 mm | 720 x 435 x (54 ... 448) mm | ... | 230 x 230 x (56 ... 205) mm | 547 x 694 x 28 mm | 115 x 55 x 78 mm | 208 x 53 x 38 mm | ... | 295 x 54 x 37 mm | 248 x 222 x 96 mm |
| Manufacturer / Brand | ... | ... | Fischer | BRATECK | LEGRAND | ORNO | LEGRAND | LEGRAND | LEGRAND | ATTE |
| Guarantee | 2 years | 2 years | 2 years | 2 years | 2 years | 2 years | 2 years | 2 years | 2 years | 3 years |

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00