

| | MONITORING ARRIVAL FOR 15.1 x 150 mm (4x4x4) | MONITORING PANEL 150mm | PLATE METER FOR 150mm (1x1x1) | SMART 2 IN 1 PORTING MONITORING SW FOR 150mm (1x1x1) (4x4x4) | EXTRAPOLED SIGNAL (MAX 9.4m) | NEW 2 IN 1 PORTING MONITORING SW FOR 150mm (1x1x1) (4x4x4) | EXTENSION CONNECTOR DA (16x9.1 x 20x11x1) | EXTENSION CONNECTOR DA (16x9.1) | CORNER SUPPLY DAMPER (16x9.1x4.5) | HOOKING BRACKET (16x9.1x4.5) | AHD HD-CVI HD-TVI CVBS TCPIP (16x9.1x4.5) (4x4x4) | CABLE FEEDBACK (16x9.1x4.5) (4x4x4) | VIDEO PANEL EXTENSION (16x9.1x4.5) (4x4x4) | CABLE FEEDBACK (16x9.1x4.5) (4x4x4) |
|------------------------------|--|------------------------|-------------------------------|--|--|--|---|---------------------------------|-----------------------------------|------------------------------|---|-------------------------------------|--|-------------------------------------|
| Available for drawings | 117 46k CHF 117 46k CHF | 7613 CHF 7613 CHF | 59 90 CHF 59 90 CHF | 57 81 CHF 57 81 CHF | 6 72 CHF 6 72 CHF | 1177 02 CHF 1177 02 CHF | 12 14 CHF 12 14 CHF | 6 59 CHF 6 59 CHF | 6 55 CHF 6 55 CHF | 12 02 CHF 12 02 CHF | 802 80 CHF 802 80 CHF | 4 08 CHF 4 08 CHF | 11 75 CHF 11 75 CHF | 44 CHF 44 CHF |
| Material | Steel - powder painted | | | | | | | | STYRENE | | | | | |
| Compatibility | VIDOS 5 Analog Video Surveys | | | | | | | | | | | | | |
| Number of parts | | | | | | | | | | | | | | 24 pcs |
| Connector type | | | | | | | | 2x 45 standard socket | Socket (24x) | | | | | |
| Input voltage | | | | | | | | | 100 - 240 V AC | | | | | |
| Temperature protection | ANALOG switch indicating open the cover | | | | | | | | | | | | | |
| Suggested resolution | | | | | | max. 12 Mpx - 4000 x 3000 px | | | | | | | | |
| Max capacity | | | | | | | | | | max. 4 kg | | | | |
| Key closed | ✓ | | | | | | | | | | | | | 100 pcs The price for per kupa |
| In package | | | | | | | | | | | | | | 100 pcs The price for per kupa |
| Secure | Progressive Scan CMOS 1.1 Mpx, 1080p | | | | | | | | | | | | | |
| Wire mounting | | | | | | | | | | | | | | |
| AC input frequency | | | | | | | | | | | | | | |
| Standard | | | | | | TCFSP | | | | | | | | |
| Cable | | | | | 1177 cat. 5e - 16 45 Plug / RJ 45 Plug | | | | | | AHD, HD-CVI, HD-TVI, CVBS, TCPIP | | | |
| Mounting | 250° | | | | | | | | | | | | | |
| Adjustment | | | | | | | | | | in two phases | | | | |
| Class inputs | | | | | | | | | | | in two lines | | | |
| Output voltage | | | | | | | | | 2.5 V DC | | | | | |
| Class outputs | | | | | | | | | | | | | | |
| Rated voltage | | | | | | 220 - 24 V DC | | | | | | | | 2.5 mm² / AWG 15 |
| Rated current | | | | | | | | | | | | | | |
| IP Protection | ✓ | | | | | | | | | | | | | |
| Output current | | | | | | | | | 4.0 A | | | | | |
| Mounting external dimensions | 100 x 530 x 130 mm | | | | | | | | | | | | | |
| Class inputs | | | | | | | | | | | | | | |
| Max. power | | | | | | 100 W | | | | | | | | |
| Length of the cable | | | | | | 2.5 m | | | | | | | | |
| Application | | | | | | | | | | | | | | |
| Output power | | | | | | | | | | | | | | |
| Power factor | | | | | | | | | | | | | | |
| Efficiency | | | | | | | | | | | | | | |
| Video outputs | | | | | | | | | | | | | | |
| Contact material | | | | | | | | | | | | | | |
| Material | | | | | | | | | | | | | | |
| Material | | | | | | | | | | | | | | |
| Efficiency at low load (10%) | | | | | | | | | | | | | | |
| Features | | | | | | | | | | | | | | |
| Applications | | | | | | | | | | | | | | |
| Number of subscribers served | | | | | | | | | | | | | | |
| Available for DVRs | with dimensions below: 440 x 440 x 150 mm | | | | | | | | | | | | | |
| Max load power consumption | | | | | | | | | | | | | | |
| Class outputs current | | | | | | | | | | | | | | |
| Video output | compatible with VIDOS 5 analog video surveillance system | | | | | | | | | | | | | |
| Audio inputs | | | | | | | | | | | | | | |
| Protocols | | | | | | | | | | | | | | |
| Output voltage adjustment | | | | | | | | | | | | | | |
| Power consumption | ~ 0.25 W (operation) ~ 2.4 W (standby mode) | | | | | | | | | | | | | |
| DC voltage measurement | | | | | | | | | | | | | | |
| Image compression method | | | | | | | | | | | | | | |
| Power connectors type | | | | | | | | | | | | | | |
| Maximal outputs load | | | | | | | | | | | | | | |
| Standard type | | | | | | | | | | | | | | |
| Number of inputs | | | | | | | | | | | | | | |
| Number of outputs | | | | | | | | | | | | | | |
| Connector type | | | | | | | | | | | | | | |
| Maximal | | | | | | | | | | | | | | |
| AC voltage measurement | | | | | | | | | | | | | | |
| AC current measurement | | | | | | | | | | | | | | |
| Mounting | | | | | | | | | | | | | | |
| Index of Protection | | | | | | | | | | | | | | |
| Network protocols | | | | | | | | | | | | | | |
| Operation temp. | | | | | | | | | | | | | | |
| AC current measurement | | | | | | | | | | | | | | |
| Switch PSE | | | | | | | | | | | | | | |
| Storage | | | | | | | | | | | | | | |
| Storage records resolutions | | | | | | | | | | | | | | |
| Default IP address | | | | | | | | | | | | | | |
| Default user / password | | | | | | | | | | | | | | |
| Resistance measurement | | | | | | | | | | | | | | |
| Web browser access ports | | | | | | | | | | | | | | |
| AC current measurement | | | | | | | | | | | | | | |
| Mobile client access ports | | | | | | | | | | | | | | |
| FTP URL | | | | | | | | | | | | | | |

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

