

	<a href="#">PATCHCORD RJ45/5.0-PK/W 5.0 m</a>	<a href="#">DIRECTIONAL ANTENNA 19/21-48</a>	<a href="#">AHD, HD-CVI, HD-TVI, PAL CAMERA HAC-HFW1801CM-IL- A-0360B-S2 - 8.3 Mpx 4K UHD 3.6 mm DAHUA</a>
			
	32.17 SEK 32.17 SEK	171.64 SEK 171.64 SEK	1552.15 SEK 1552.15 SEK
Receiving channels	...	21 ... 48	...
Gain	...	9 ... 14 dB	...
Standard	...	...	AHD, HD-CVI, HD-TVI, CVBS
Polarization	...	Horizontal	...
Sensor	...	...	Progressive Scan CMOS
Cable	UTP cat. 5e : RJ-45 - Straight plug / RJ-45 - Angular plug	...	...
Impedance	...	75 Ω	...
Matrix size	...	...	8.3 Mpx
Length of the cable	5.0 m	...	...
Main features	<ul style="list-style-type: none"> <li>• Very easy and quick assembly</li> <li>• Corrosion resistance</li> </ul>	<ul style="list-style-type: none"> <li>• Number of elements : 19</li> <li>• Matching transformer included</li> </ul>	...
Resolution	...	...	3840 x 2160 - 8.3 Mpx 4K UHD @ HD-CVI / HD-TVI / AHD @ 15 fps , 2592 x 1944 - 5 Mpx @ HD-CVI @ 25 fps , 2560 x 1440 - 3.7 Mpx @ HD-CVI @ 25 fps , 1920 x 1080 - 1080p @ HD-CVI @ 25 fps , 960 x 576 - 960H @ PAL @ 25 fps
Lens	...	...	3.6 mm
View angle	...	...	<ul style="list-style-type: none"> <li>• 88 ° (manufacturer data)</li> <li>• 83 ° (our tests result)</li> </ul>
Range of IR illumination	...	...	20 m
White light LED illuminator range	...	...	20 m
IR illuminator power adjustment	...	...	Automatic
Video output	...	...	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω
Audio	...	...	<ul style="list-style-type: none"> <li>• Microphone built-in,</li> <li>• Audio support via coaxial cable - HD-CVI only</li> </ul>
OSD menu	...	...	✓

Main features	...	...	<ul style="list-style-type: none"> <li>• Smart Dual Illumination technology - IR or LED illuminator works in night mode. White light will turn on automatically only when an object is detected in the monitored area, which effectively improves image quality</li> <li>• WDR - 120 dB - Wide Dynamic Range</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• F-DNR (Defog) - Reduction of image noise caused by precipitation</li> <li>• BLC/HLC - Back Light / High Light Compensation</li> <li>• ICR - Movable InfraRed filter</li> <li>• AGC - Automatic Gain Control</li> <li>• Privacy zones - max. 8</li> <li>• Mirror - Mirror image</li> <li>• Auto White Balance</li> <li>• Sharpness - sharper image outlines</li> </ul>
Power supply	...	...	12 V DC / 350 mA
Power consumption	...	...	≤ 4.2 W
Housing	...	...	Compact - Metal
Color	White	...	White
"Index of Protection"	...	...	IP67
Vandal-proof	...	...	—
Operation temp	...	...	-40 °C ... 60 °C
Weight	0.10 kg	...	0.33 kg
Dimensions	...	1300 x 320 x 410 mm	167 x 70 x 70 mm
Manufacturer / Brand	...	...	DAHUA
Guarantee	2 years	2 years	3 years

