



	ISOPROPYL ALCOHOL CLEANSER-IPA/100 BOTTLE 100 ml	AHD, HD-CVI, HD-TVI, CVBS, TCP/IP DVR IDS-7108HUHI-M1/S(C) 8 CHANNELS Hikvision
		
	2.76 EUR 2.76 EUR	249.76 EUR 249.76 EUR
Package	Bottle 100 ml	...
Standard	...	AHD, HD-CVI, HD-TVI, CVBS, TCP/IP
Video inputs	...	8 pcs BNC - AHD / HD-CVI / HD-TVI / CVBS
Video outputs	...	1 pcs HDMI 4K 1 pcs VGA
Audio inputs	...	1 pcs CINCH, Coaxial audio - Audio from cameras
Audio outputs	...	1 pcs CINCH
Image compression method	...	H.265+ / H.265 / H.264+ / H.264
Image records resolutions	...	<ul style="list-style-type: none"> • HD-TVI : 8.3 Mpx - 3840 x 2160 , 5.0 Mpx - 2960 x 1665 (3K) , 5.0 Mpx - 2560 x 1944 , 3.7 Mpx - 2560 x 1440 , 3.0 Mpx - 1920 x 1536 , 1080p - 1920 x 1080 , 720p - 1280 x 720 , • AHD : 5 Mpx - 2560 x 1944 , 3.7 Mpx - 2560 x 1440 , 1080p - 1920 x 1080 , 720p - 1280 x 720 , • HD-CVI : 3.7 Mpx - 2560 x 1440 , 1080p - 1920 x 1080 , 720p - 1280 x 720 , • CVBS : 960H - 960 x 576 , D1 - 704 x 576 , • IP : max. 8 Mpx - 3840 x 2160

Recording speed adjustment	...	8 Mpx IP @ 1 ... 25 fps 8 Mpx @ 1 ... 8 fps 5 Mpx @ 1 ... 12 fps 3.7 Mpx @ 1 ... 15 fps 3 Mpx @ 1 ... 18 fps 1080p @ 1 ... 25 fps 720p @ 1 ... 25 fps 960H @ 1 ... 25 fps D1 @ 1 ... 25 fps for each channel
Operation modes	...	8 x HD-TVI / AHD / HD-CVI / CVBS / IP + 8 x IP
Recording modes	...	Manual, Motion Detection, Schedule
Supported hard drives	...	1 x 10 TB SATA
External storage devices backup	...	Backup to USB drive (pendrive, external drive)
Searching and playback the records	...	Records searching: timeline or file list. Playback: forward, fast, slow. Playback max. 8 cameras in the same time
Network interface	...	1 x RJ-45 - 10/100/1000 Base-TX
Bitrate	...	32 ... 10240 kbps
Network functions	...	Network Client Software and IE browser: live view, playback and backup of the records, partial configuration of the recorder parameters
Network protocols	...	TCP/IP, PPPoE, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, NFS, iSCSI, UPnP, HTTPS, ONVIF
Mobile phones support	...	Port no.: 8000 or access by a cloud (P2P) • Android: Free application Hik-Connect • iOS: Free application Hik-Connect
Default admin user / password	...	admin / - The administrator password should be set at the first start
Default IP address	...	DHCP or 192.168.1.64
Web browser access ports	...	80
PC client access ports	...	554 RTSP, 8000
Mobile client access ports	...	8000
Port ONVIF	...	80
RTSP URL	...	• rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no01/ - Main stream • rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no02/ - Sub stream
Alarm inputs / outputs	...	—
PTZ control	...	Control compatible with coax HD-TVI Hikvision
Motion Detection	...	2.0
USB	...	2 pcs USB 2.0
Mouse support	...	✓
IR remote controller in the set	...	—



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Main features	...	Intelligent Image Analysis - detection line violation and intrusion in an area previously designated, classification of people and vehicles
Power supply	...	12 V DC / 2 A (power adapter included)
Color	...	White
Weight	0.09 kg	0.59 kg
Dimensions	Ø 50 x 105 mm	200 x 210 x 48 mm
Supported languages	...	Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, Greek, Spanish, Dutch, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Hungarian, Italian
Manufacturer / Brand	...	Hikvision
SAP Code	...	300227956
Guarantee	...	3 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00