





	ROUTER AX30 Wi-Fi 6, 2.4 GHz, 5 GHz, 574 Mbps + 2402 Mbps DAHUA	STYROFOAM PLUG SM-50/EPN*P4 Elektro-Plast	CABLE RCA-2X2.6
			
	109.58 AUD 109.58 AUD	1.50 AUD 1.50 AUD	0.57 AUD 0.57 AUD
In package	...	4 pcs The price for package	...
In section	100 m . Price for 1m when buying a whole roll
Length	...	49 mm	...
Diameter	...	Ø 20 mm / Ø 24 mm	...
Thickness of the Styrofoam	...	≥ 50 mm	...
Inner conductor	2 x (10 x Ø 0.12 mm Cu Stranded wire)
Diameter of the screw	...	Ø 4 mm ... Ø 5 mm	...
Outer coating	2x Ø 2.5 mm PVC
Frequency range	<ul style="list-style-type: none"> • 2.4 GHz (2.412 ... 2.472 GHz), • 5 GHz (5.170 ... 5.330 GHz, 5.735 ... 5.835 GHz),
Shield	PVC
Braid	Cu Stranded wire
Coating color	Black
Antenna type	4 x Omnidirectional antenna 5 dBi - Integrated, 2x2 MU-MIMO
Standards	<ul style="list-style-type: none"> • IEEE 802.11 b/g/n/ax @ 2.4 GHz, • IEEE 802.11 a/b/g/n/ac/ax @ 5 GHz
Baud rates	574 Mbps @ 2.4 GHz + 2402 Mbps @ 5 GHz
LAN ports	<ul style="list-style-type: none"> • 1 x 10 / 100 / 1000 Mbps - WAN • 3 x 10 / 100 / 1000 Mbps - LAN
LED indicators	Power
DDNS	✓
DHCP server	✓
Firmware update	✓

Protections	<ul style="list-style-type: none"> • WPA-PSK, WPA2-PSK, WPA-PSK/WPA2-PSK, WPA3-PSK, WPA2-PSK/WPA3-PSK • NAT network firewall
Management interface	Web browser, WiLynk application
Operation modes	<ul style="list-style-type: none"> • Router, • Repeater
Transmitter power	< 24.5 dBm ± 2 dBm



Main features	<ul style="list-style-type: none"> • Wi-Fi 6 support - a standard that offers higher speeds, better performance in high-traffic environments • MU-MIMO - a multi-antenna transmission function that allows to increase the bandwidth and reliability of connection with the client of the network • OFDMA • Beamforming (TxBF) - technology that allows to create a beam of radio waves in order to improve the quality of connection with client devices located further away from the signal source • WPS/RESET button • The WPS function allows to easy establish an encrypted connection • Built-in 3-port switch • Guest Network - a separate and secure network for guests • View topology and network status • parental control • QoS - mechanisms, which provide the high quality of transmission • NAT : Port Mapping • Remote management • Target Wake Time (TWT) technology - lower energy costs • Port Security : Contact/Air (ESD/EMP) ± 6 kV / ± 8 kV • Protection against lightning discharges (common/differential) : 2 / 0.5 kV • Possibility to mount to the wall 	...	<ul style="list-style-type: none"> • Shielded cable
Housing	Plastic
Power supply	12 V DC / 1.5 A (power adapter included)
Power consumption	max. 18 W
Operation temp	0 °C ... 40 °C
Permissible relative humidity	10 % ... 95 % (non-condensing)

Weight	0.33 kg	0.004 kg / 1 pcs	...
Dimensions	236 x 150 x 46 mm
Manufacturer / Brand	DAHUA	Elektro-Plast Nasielsk	...
Guarantee	2 years	2 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00