



	WIRELESS TEMPERATURE DETECTOR ATLO-THD1-TUYA Wi-Fi, Tuya Smart	IP SPEED DOME CAMERA OUTDOOR P3AE-PV Picco A2 Wi-Fi - 3 Mpx 4 mm DAHUA
		
	17.72 EUR 17.72 EUR	51.28 EUR 51.28 EUR
Standard	...	IP
Support	Tuya Smart	...
Detection	Temperature / relative humidity	...
Measurement range	-10 °C ... 55 °C	...
Measurement of humidity	0 % ... 99 %	...
Resolution	...	2304 x 1296 - 3 Mpx , 1920 x 1080 1080p , 1280 x 720 - 720p
Alarm signaling	<ul style="list-style-type: none"> Buzzer, Signal to the Tuya Smart mobile application 	...
Sensor	...	1/2.8 " Progressive Scan CMOS
Frequency range	2.4 GHz WiFi IEEE 802.11 b/g/n	...
Lens	...	4 mm
Radio communication range	The range limited only by the availability of the Wi-Fi network	...
View angle	...	87 °
Optical zoom	...	—
Digital zoom	...	—
Range of IR illumination	...	30 m
White light LED illuminator range	...	30 m
Alarm inputs	—	...
Video output	...	—
Rotation speed (manual control)	...	<ul style="list-style-type: none"> 0.1 °/s ... 74 °/s (horizontal) 0.1 °/s ... 36 °/s (vertical)
Current consumption	max. 60 mA	...
Preset rotation speed	...	max. 62 °/s (horizontal) max. 36 °/s (vertical)
Horizontal rotation range	...	0 ° ... 345 ° - Rotation of the head is limited by stops
Vertical rotation range	...	0 ° ... 80 °
RS-485 interface	...	—
Number of presets	...	300
Horizontal scan	...	—
Route settings	...	—

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Main features	<ul style="list-style-type: none"> • LCD display • Digital detector • Signal indicator • Battery charge indicator • Two programmable temperature thresholds (upper and lower) • Two programmable humidity thresholds (upper and lower) • Selectable measurement unit: °C / °F • Low battery level alarm \leq 2.2 V • Sound signaling : 55 dB • Wall mounting 	...
Image compression method	...	H.265+ / H.264 / H.265 / MJPEG / H.264+
Alarm inputs / outputs	...	—
Operation temp	-10 °C ... 60 °C	...
Main stream frame rate	...	25 fps - 5 Mpx
Permissible relative humidity	max. 90 % (non-condensing)	...
Memory card slot	...	Micro SD card support up to 256GB
Interface	...	<ul style="list-style-type: none"> • Wi-Fi - 2.4 GHz IEEE 802.11 b/g/n, • 10/100 Base-T (RJ-45)
WEB Server	...	Built-in, NVR compliance
Max. number of on-line users	...	20
ONVIF	...	—
Audio	...	<ul style="list-style-type: none"> • Microphone built-in • Speaker built-in • Audio detection • Bi-directional audio streaming support
Mobile phones support	<p>It is possible to operate via the Wi-Fi network from the mobile application on the iOS, Android systems :</p> <ul style="list-style-type: none"> • The Tuya Smart free application on Android • The Tuya Smart free application on iOS 	<p>Port 37777</p> <ul style="list-style-type: none"> • Android: Free application DMSS • iOS (iPhone): Free application DMSS
Default admin user / password	...	admin / - The administrator password should be set at the first start
Default IP address	...	192.168.1.108
Web browser access ports	...	80, 37777
PC client access ports	...	37777
Mobile client access ports	...	37777
Port ONVIF	...	80

RTSP URL	...	rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream
Intelligent image analysis	...	<ul style="list-style-type: none"> • intrusion • linkage tracking • crossing the line (tripwire)
Main features	...	<ul style="list-style-type: none"> • When Smart Dual Light is active, the white light will turn on automatically only when an object is detected in the monitored area, which effectively improves the image quality • Active deterrence function - Light and sound alarm • Intelligent Object Tracking • Wi-Fi Module - IEEE 802.11 b/g/n, • D-WDR - Wide Dynamic Range • Day/night mode • BLC - Back Light Compensation • HLC - High Light Compensation (spot) • ICR - Movable InfraRed filter • motion detection based on human detection • SMD 3.0 - searching for an object classified as: human, motor vehicle
Power supply	<ul style="list-style-type: none"> • 2 x battery LR3 (AAA) 1.5 V (included) • micro USB socket 5 V / 2 A 	12 V DC / 1 A
Power consumption	...	≤ 11 W
Housing	...	Speed Dome, Plastic
Color	White	White
"Index of Protection"	...	IP66
Operation temp	...	-30 °C ... 55 °C
Weight	0.05 kg	0.44 kg
Dimensions	Ø 61 x 27 mm	Ø 111 x 141 mm (without bracket)
Supported languages	...	English
Manufacturer / Brand	...	DAHUA
Guarantee	2 years	3 years