





	IP CAMERA IPC-HUM8531M-V-LED-0360B - 5 Mpx 3.6 mm DAHUA	EXTENDER HDMI-EX-4	STYROFOAM PLUG SM-140/EPN*P4 Elektro-Plast	SMART PROXIMITY LED LIGHT CONTROLLER PROXIDIMMER/BLEBOX 12 ... 24 V DC
				
	450.72 EUR 450.72 EUR	48.52 EUR 48.52 EUR	3.10 EUR 3.10 EUR	13.61 EUR 13.61 EUR
Standard	TCP/IP
Application	Touchless lighting control
Sensor	1/2.7 " Progressive Scan CMOS
Matrix size	5 Mpx
Rated voltage	12 ... 24 V DC
In package	4 pcs The price for package	...
Maximal total load	120 W
Length	140 mm	...
Total maximal current	5 A
Number of inputs	0
Supported HDMI resolutions	...	1080p, 1080i, 720p, 576p, 576i, 480p, 480i
Number of outputs	1
Connector type	screw terminals
Diameter	Ø 20 mm / Ø 24 mm	...
Wireless	—
Thickness of the Styrofoam	≥ 140 mm	...
Diameter of the screw	Ø 4 mm ... Ø 5 mm	...
Main features	<ul style="list-style-type: none"> • Non-contact switching on and off, lighting brightness control, • Detection range : 7 cm • Possibility to hide the sensor • Automatic calibration • LED indication
Maximal transmission range	...	<ul style="list-style-type: none"> • 40 m @ 720p / 1080p - UTP cat. 6 (manufacturer data) • 60 m @ 1080p - UTP cat. 6 (our tests result) • 50 m @ 1080p - UTP cat. 5e (our tests result)
Resolution	2560 x 1920 - 5 Mpx , 2688 x 1520 - 4 Mpx , 2560 x 1440 - 3.7 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p , 1280 x 960 - 1.3 Mpx 1280 x 720 - 720p
Lens	3.6 mm
View angle	79 °
Supported audio formats	...	DTS-HD, Dolby true HD, LPCM7.1, AC3, DTS, DSD
White light LED illuminator range	0.5 m
Operation temp	...	-10 °C ... 55 °C	...	-20 °C ... 50 °C
Permissible relative humidity	...	5 % ... 90 %
Min. illumination	<ul style="list-style-type: none"> • 0.02 Lux @ F2.0 / 30IRE (color), • 0.0002 Lux @ F2.0 / 30IRE (B/W) • 0 Lux @ LED
Audio	<ul style="list-style-type: none"> • Microphone built-in, • Audio detection
RS-485 interface	—
RS-232 interface	—
Alarm inputs / outputs	—
Image compression method	H.265+ / H.265 / H.264+ / H.264 / H.264H / H.264B / MJPEG
Main stream frame rate	25 fps @ 5 Mpx
Network interface	10/100 Base-T (RJ-45)

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Network protocols	IPv4/IPv6, HTTP, TCP, UDP, ARP, RTP, RTSP, RTCP, RTMP, SMTP, FTP, SFTP, DHCP, DNS, DDNS, QoS, UPnP, NTP, Multicast, ICMP, IGMP, NFS, PPPoE
ONVIF	21.12
WEB Server	✓
Max. number of on-line users	20
Mobile phones support	Port no.: 37777 or access by a cloud (P2P) • Android: Free application DMSS • iOS (iPhone): Free application DMSS	—
Default admin user / password	admin / - The administrator password should be set at the first start
Default IP address	192.168.1.108
Web browser access ports	80, 37777
PC client access ports	37777
Mobile client access ports	37777
Port ONVIF	80
RTSP URL	rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream
Memory card slot	Micro SD memory cards up to 256GB support (possible local recording)
Main features	<ul style="list-style-type: none"> • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • ROI - improve the quality of selected parts of image • BLC - Back Light Compensation • HLC - High Light Compensation (spot) • Configurable Privacy Zones • Motion Detection • scene changing • video tampering • Mirror - Mirror image • WB - White Balance (ATW/AWB/manual/indoor/outdoor) • AGC - Automatic Gain Control • Day/Night mode (color/b&w) • SSA - Smart Scene Adaptive - intelligent scene adaptation by automatically adjusting the exposure parameters to obtain a better image • Light filtering system (polarizing filters) effectively reduces the reflection of light to deliver clear image • Heated Glass quickly removes water, ice, snow and mist from the glass to keep the clear image (Heater built-in) • Mounting bracket included - Height adjustment
Housing	Mini - Metal	Plastic
"Index of Protection"	IP67	IP20
Color	Black	Black
Power supply	• 12 V DC / 420 mA, • PoE (802.3af)	5 V DC / 1000 mA - 2 pcs of power adapters included
Power consumption	max. 5.0 W @ 12 V max. 5.8 W @ PoE
Operation temp	-40 °C ... 60 °C
Weight	• 0.21 kg (camera) • 0.39 kg (with bracket)	0.045 kg	0.015 kg / 1 pcs	0.02 kg
Dimensions	• 66 x 65 x 32 mm (camera) • 50 cm (cable length) • 150 x 70 x 88 mm (Bracket) • 70 ... 115 mm (Mounting hole diameter for the meter)	67 x 56 x 22 mm	...	39 x 39 x 16 mm
Supported languages	English
Manufacturer / Brand	DAHUA	...	Elektro-Plast Nasielsk	BleBox
Guarantee	5 years	2 years	2 years	2 years

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00