



	SMART LED LIGHTING CONTROLLER WLIGHTBOX-V3/BLEBOX Wi-Fi, 12... 24 V DC	AHD, HD-CVI, HD-TVI, CVBS, TCP/IP DVR IDS-E04HQHI-B 4 CHANNELS ACUSENSE Hikvision
		
	29.72 EUR 29.72 EUR	238.94 EUR 238.94 EUR
Application	Works with LED lighting - (RGB/RGBW/RGBCCT/CCT/MONO) 12-24V LED strips	...
Standard	...	AHD, HD-CVI, HD-TVI, CVBS, TCP/IP
Rated voltage	12 ... 24 V DC	...
Maximal total load	360 W	...
Video inputs	...	4 pcs BNC - AHD / HD-CVI / HD-TVI / CVBS
Total maximal current	15 A (3 A / Channel)	...
Number of inputs	1	...
Video outputs	...	1 pcs HDMI 1 pcs VGA
Number of outputs	5	...
Connector type	screw terminals	...
Audio inputs	...	4 - Audio support via coaxial cable
Audio outputs	...	—
Wireless	Wi-Fi, 2.4 GHz - IEEE 802.11g	...
Image compression method	...	H.265+ / H.265
Image records resolutions	...	<ul style="list-style-type: none"> • HD-TVI / HD-CVI / AHD : 4M-N - 1280 x 1440 , 1080p - 1920 x 1080 , 1080N - 960 x 1080 , 720p - 1280 x 720 , • CVBS : 960H - 960 x 576 , • IP : max. 6 Mpx - 3072 x 2048
Recording speed adjustment	...	6 Mpx IP @ 1 ... 25 fps 4M-N @ 1 ... 15 fps 1080p @ 1 ... 15 fps 1080N @ 1 ... 25 fps 720p @ 1 ... 25 fps 960H @ 1 ... 25 fps for each channel

Main features	<ul style="list-style-type: none"> • Local control by physical button, • schedule, • timer, • sunrise and sunset mode, • remote access, • voice control, • Controlling the color, color temperature, brightness, effect, changing time allows any interior arrangement • predefined effects, • effects modification, • Operation modes : <ul style="list-style-type: none"> - 1 x RGB (color) - 1 x RGBW (color + white - brightness control) - 1 x RGBWW / RGBCCT (color + white - brightness and color temperature control) - 1 x RGB (color) + 1 x MONO (single color) - 1 x CCT (white - brightness and color temperature control) - 2 x CCT (white - brightness and color temperature control) - 1 x RGB (color) + 1 x CCT (white - brightness and color temperature control) - 5 x MONO (single color) / halogen bulb • µWiFi technology support 	...
Operation modes	...	• 4 x HD-TVI / AHD / HD-CVI / PAL + 1 x IP
Housing	Plastic	...
Recording modes	...	Manual, Motion Detection, Schedule
"Index of Protection"	IP20	...
Operation temp	-20 °C ... 50 °C	...
Supported hard drives	...	1 x 512 GB eSSD - Built-in, Space available for records : 480 GB
External storage devices backup	...	Backup to USB drive (pendrive, external drive)
Searching and playback the records	...	Records searching: timeline or file list. Playback: forward, fast, slow. Playback max. 4 cameras in the same time
Network interface	...	1 x RJ-45 - 10/100 Base-T
Network functions	...	Network Client Software and IE browser: live view, playback and backup of the records, partial configuration of the recorder parameters
Network protocols	...	TCP/IP, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, SMTP, NFS, UPnP, HTTPS
Mobile phones support	<ul style="list-style-type: none"> • The wBox free application on Android • The wBox free application on iOS 	Port no.: 8000 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application Hik-Connect • iOS (iPhone): Free application Hik-Connect
Default IP address	...	DHCP or 192.168.1.64



Default admin user / password	...	admin / -
Web browser access ports	...	80
PC client access ports	...	554 RTSP, 8000
Mobile client access ports	...	8000
Port ONVIF	...	80
RTSP URL	...	<ul style="list-style-type: none"> • rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no01/ - Main stream • rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no02/ - Sub stream
Alarm inputs / outputs	...	—
PTZ control	...	Control compatible with coax HD-TVI Hikvision
Motion Detection	...	2.0
Main features	...	<ul style="list-style-type: none"> • DVR from the AcuSense series • Intelligent image analysis : intrusion, crossing the line (tripwire), Deep Learning technology • Smart motion detection (with recognizing people and vehicles) • Filtering of false alarms based on the recognition of persons and vehicles
USB	...	2 pcs USB 2.0
Mouse support	...	✓
IR remote controller in the set	...	—
Power supply	...	12 V DC / 1 A (power adapter included)
Color	Black	Black
Weight	0.026 kg	0.42 kg
Dimensions	43 x 35 x 18 mm	152 x 122 x 46 mm
Supported languages	...	Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, Greek, Spanish, Dutch, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Hungarian, Italian
Manufacturer / Brand	BleBox	Hikvision
SAP Code	...	300228637
Guarantee	2 years	3 years