



	EXPANSION PLUG KS-10/6X80 KLIMAS	SWITCH POE HS4408-4ET-96 4-PORT + 4 x SFP DAHUA
		
	0.19 CHF 0.19 CHF	112.01 CHF 112.01 CHF
Material	<ul style="list-style-type: none"> Expansion plug, Polypropylene Screw, Steel galvanized 	...
Drilling diameter	10 mm	...
Expansion plug length	60 mm	...
Screw dimensions	Ø 6 x 80 mm, SW-10	...
Application	<ul style="list-style-type: none"> Concrete Solid clay brick Solid sand-lime brick 	...
LAN ports	...	<ul style="list-style-type: none"> 4 x RJ45 (10/100/1000 Base-T, 3 PoE (802.3af/at) + 1 PoE (802.3bt) / Hi-PoE / PoE (802.3af/at)) 4 x Uplink (port SFP - 1000 Base-X)
Transmission speed	...	<ul style="list-style-type: none"> 10 / 100 LAN & PoE ports 1000 SFP ports
Management	...	✓
Maximal output power	...	<ul style="list-style-type: none"> 30 W / port PoE 802.3af/at 90 W / port PoE 802.3bt
Maximal total power	...	96 W
Operation modes	...	<ul style="list-style-type: none"> Extend On : 250 m, 10 Mbps Extend Off : 100 m, 10 / 100 Mbps

Main features	...	<ul style="list-style-type: none"> • DIN, TS-35 rail mounting • Data Flow Control • protection against lightning discharges and voltage differences and strokes between devices • Industrial wide temperature design. • Intelligent management of Power Supply Unit power's output stage • PoE (802.3af), PoE (802.3at), Hi-PoE, PoE (802.3bt) • PoE Watchdog / PD Alive mode - monitoring of the ports that power PoE devices and automatic restart by cutting off the power supply when an unresponsive device is detected • The ability to connect two power adapters - redundant power supply • The device supports 8-pin power supply
LED diodes	...	Power, Link/Act, PoE
Certificates	...	CE
Power supply	...	48 ... 57 V DC (power adapter included)
Housing type	...	DIN
Operation temp	...	-30 °C ... 65 °C
Weight	...	0.618 kg
Dimensions	...	150 x 110 x 42 mm
Manufacturer / Brand	KLIMAS	DAHUA
Guarantee	2 years	3 years