




	AHD, HD-CVI, HD-TVI, PAL CAMERA BCS-B-MT22800 - 1080p 2.8 mm BCS BASIC	AHD, HD-CVI, HD-TVI, CVBS, TCP/IP DVR BCS-L-XVR1601-V 16 CHANNELS BCS Line	PATCHCORD RJ45/7/2.0-FL 2.0 m UNITEK
			
	26.24 EUR 26.24 EUR	408.08 EUR 408.08 EUR	3.96 EUR 3.96 EUR
Cable	SSTP cat. 7 : RJ-45 - Plug / RJ-45 - Plug
Standard	AHD, HD-CVI, HD-TVI, PAL	AHD, HD-CVI, HD-TVI, CVBS, TCP/IP	...
Sensor	1/2.9 " CMOS
Video inputs	...	16 pcs BNC	...
Length of the cable	2.0 m
Matrix size	2.1 Mpx
Video outputs	...	1 pcs HDMI 4K 1 pcs VGA	...
Audio inputs	...	1 pcs CINCH 16 Channels - Audio support via coaxial cable, HD-CVI only	...
Audio outputs	...	1 pcs CINCH	...
Resolution	1920 x 1080 - 1080p 1280 x 720 - 720p 960 x 576 - 960H, PAL
Main features	<ul style="list-style-type: none"> • 10 Gigabit Ethernet • Very flexible • Ultra-thin 2.3 mm thick patchcord • 100% copper conductor • Gold-plated connector prevents the oxidation of contacts • SSTP - double shielded twisted-pair cable • Corrosion resistance • Environmental immunity
Lens	2.8 mm, F1.2
Image compression method	...	AI Coding / H.265+ / H.265 / H.264+ / H.264	...
View angle	<ul style="list-style-type: none"> • 91 ° (manufacturer data) • 103 ° (our tests result)
Range of IR illumination	30 m
IR illuminator power adjustment	Automatic

Video output	AHD / HD-CVI / HD-TVI / PAL, 1 Vpp / 75 Ω
OSD menu	✓
Power consumption	≤ 5 W
Housing	Compact, Metal
"Index of Protection"	IP66
Operation temp	-20 °C ... 60 °C
Image records resolutions	...	<ul style="list-style-type: none"> • AHD / HD-CVI / HD-TVI : 5M-N - 1296 x 1944 , 4M-N - 1280 x 1440 , 1080p - 1920 x 1080 , 1080N - 960 x 1080 , 720p - 1280 x 720 • CVBS : 960H - 960 x 576 , • IP : max. 6 Mpx - 3072 x 2048 	...
Recording speed adjustment	...	6 Mpx IP @ 1 ... 25 fps 5M-N @ 1 ... 10 fps 4M-N @ 1 ... 15 fps 1080p @ 1 ... 15 fps 1080N @ 1 ... 25 fps 720p @ 1 ... 25 fps 960H @ 1 ... 25 fps for each channel	...
Operation modes	...	16 x AHD / HD-CVI / HD-TVI / CVBS / IP + 8 x IP	...
Recording modes	...	Manual, Motion Detection, Schedule	...
Supported hard drives	...	1 x 16 TB SATA	...
External storage devices backup	...	Save single frames and whole records from DVR drive to the USB drive	...
Searching and playback the records	...	Records searching: by time + timeline with record type. Playback: forward, fast, slow, step Advanced searching (to the one second accuracy) All channels synchronous playback, Smart Search function 1/4/9/16 channel synchronous playback	...

Network functions	...	Full support via network, Remote records copying, Web-Server built-in max. 128 on-line users	...
USB	...	1 x USB 2.0 1 x USB 3.0	...
Mobile phones support	...	Port no.: 37777 or access by a cloud (P2P) • Android: Free application BCS Manager • iOS (iPhone): Free application BCS Manager	...
Alarm inputs / outputs	...	—	...
PTZ control	...	IP Speed Dome Cameras Control compatible with coax PTZ HD-CVI RS-485 - PELCO-D/P	...
Motion Detection	...	Split the screen into zones : 22 x 18 motion zones	...
Main features	<ul style="list-style-type: none"> • D-WDR - Wide Dynamic Range • 2D-DNR, 3D-DNR - Digital Noise Reduction • BLC - Back Light Compensation • FLC - The technology eliminates the tiring eyes flickering image effect • ICR - Movable InfraRed filter • Sharpness - sharper image outlines • AGC - Automatic Gain Control • Auto White Balance 	<ul style="list-style-type: none"> • Privacy zones - max. 4 • SMD PLUS - searching for an object classified as: human, motor vehicle, • POS - support the machines installed in the points of sales and displaying the date from them as overlaid text on selected channel window, • Intelligent image analysis : crossing the line (tripwire), intrusion - classification of people and vehicles, face detection 	...
Mouse support	...	✓	...
IR remote controller in the set	...	—	...
Power supply	12 V DC / 420 mA	12 V DC / 2 A (power adapter included)	...
Color	Graphite	Black	Black
Weight	0.33 kg	1.02 kg	0.05 kg
Dimensions	165 x 64 x 62 mm	260 x 240 x 47 mm, RACK 19", 1U	...
Supported languages	...	Polish, English	...
Manufacturer / Brand	BCS BASIC	BCS Line	UNITEK
Guarantee	3 years	3 years	2 years