

	<a href="#">AHD, HD-CVI, HD-TVI, CVBS, TCP/IP DVR BCS-XVR3202-II 32 CHANNELS</a>	<a href="#">IP VANDALPROOF CAMERA DS-2CD2545FWD-IS(BLACK)(2.8MM) - 4 Mpx Hikvision</a>	<a href="#">ELECTRIC STRIKE XS12UPW Hartte BIRA</a>
			
	437.50 EUR 437.50 EUR	299.52 EUR 299.52 EUR	19.89 EUR 19.89 EUR
Rated voltage	...	...	10 ... 14 V AC/DC
Sensor	...	1/2.5 " Progressive Scan CMOS	...
Matrix size	...	4 Mpx	...
Scanning system	...	Progressive	...
Standard	AHD, HD-CVI, HD-TVI, CVBS, TCP/IP	TCP/IP	...
Video inputs	32 pcs BNC	...	...
Current consumption	...	...	480 mA @ 12 V AC 680 mA @ 12 V DC
Application	...	...	right-side door / left-side door
Ratched lock	...	...	Ability to release the lock permanently
Video outputs	1 pcs HDMI 1 pcs VGA 1 pcs BNC socket - CVBS	...	...
Memory function	...	...	✓
Reverse action	...	...	—
Audio inputs	1 pcs CINCH	...	...
Clearance adjustment	...	...	3.5 mm
Audio outputs	1 pcs CINCH	...	...
Allowable load of the door impacting the lock	...	...	3000 N
Resolution	...	2688 x 1520 - 4 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p , 1280 x 720 - 720p	...
Allowable uninterrupted operation time	...	...	—
Number of compression levels	6	...	...
Lens	...	2.8 mm	...
View angle	...	• 109 ° (manufacturer data) • 104 ° (our tests result)	...
Range of IR illumination	...	10 m	...
RS-485 interface	...	—	...
Image compression method	H.264+ / H.264	H.265+ / H.265 / H.264+ / H.264 / MJPEG	...
Main features	...	...	<ul style="list-style-type: none"> <li>• Symmetrical housing</li> <li>• Narrow profile : 16.2 mm,</li> <li>• Operation mode : NC</li> <li>• Resistance : 17.6 Ω</li> <li>• Number of opening cycles : 200000</li> <li>• Radial shape of the latch - when opening the latch is not going beyond the outline of electric strike</li> </ul>

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Audio	...	<ul style="list-style-type: none"> <li>• Microphone built-in,</li> <li>• External microphone input,</li> <li>• Audio output,</li> <li>• Bi-directional audio streaming support</li> </ul>	...
Memory card slot	...	Micro SD memory cards up to 128GB support (possible local recording)	...
Main stream frame rate	...	25 fps @ 4 Mpx	...
Image records resolutions	<ul style="list-style-type: none"> <li>• AHD / HD-CVI / HD-TVI : 1080p - 1920 x 1080 4M-N 1280 x 1440 1080N - 960 x 1080 720p - 1280 x 720</li> <li>• CVBS : 960H - 960 x 576 ,</li> <li>• IP : max. 5 Mpx - 2592 x 1944</li> </ul>	...	...
Network interface	...	10/100 Base-T (RJ-45)	...
Recording speed adjustment	<ul style="list-style-type: none"> <li>5 Mpx IP @ 1 ... 25 fps</li> <li>1080p @ 1 ... 15 fps</li> <li>4M-N @ 1 ... 15 fps</li> <li>720p @ 1 ... 25 fps</li> <li>1080N @ 1 ... 25 fps</li> <li>960H @ 1 ... 25 fps</li> </ul> for each channel	...	...
Operation modes	32 x AHD / HD-CVI / HD-TVI / CVBS / IP	...	...
Recording modes	Manual, Motion Detection, Schedule	...	...
Supported hard drives	2 x 8 TB SATA	...	...
External storage devices backup	Save single frames and whole records from DVR drive to the USB drive	...	...
Searching and playback the records	Records searching: by time + timeline with record type. Playback: forward, fast, slow, step Advanced searching (to the one second accuracy)	...	...
Network protocols	...	TCP/IP, UDP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, IEEE 802.1x, QoS, IPv6 UDP Bonjour SSL / TLS	...
Network functions	Network Client Software and IE browser: live view, playback and backup of the records, partial configuration of the recorder parameters	...	...
WEB Server	...	Built-in	...
Max. number of on-line users	...	6	...
USB	1 pcs USB 2.0 1 pcs USB 3.0	...	...
ONVIF	...	18.12	...



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Mobile phones support	Port no.: 37777 or access by a cloud (P2P) • Android: Free application <a href="#">DMSS</a> • iOS (iPhone): Free application <a href="#">DMSS</a>	Port no.: 8000 or access by a cloud (P2P) • Android: Free application <a href="#">Hik-Connect</a> • iOS: Free application <a href="#">Hik-Connect</a>	...
Alarm inputs / outputs	—	1 / 1	...
Default admin user / password	...	admin / - The administrator password should be set at the first start	...
Default IP address	...	192.168.1.64	...
Web browser access ports	...	80	...
PTZ control	RS-485 - PELCO-D/P and others	...	...
PC client access ports	...	Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application	...
Motion Detection	Split the screen into zones : 22 x 18 motion zones	...	...
Mobile client access ports	...	8000	...
Mouse support	✓	...	...
Port ONVIF	...	80	...
IR remote controller in the set	✓	...	...
RTSP URL	...	• Main stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/ - with authorization • Sub stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/ - with authorization	...
Country of origin	China	...	...
Main features	...	<ul style="list-style-type: none"> <li>• WDR - 120 dB - Wide Dynamic Range</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• Anti-Flicker - The technology eliminates the tiring eyes flickering image effect</li> <li>• EXIR - high-efficiency infrared LEDs technology, which evenly covers the whole plan of both central vantage points of the scene as well as the corners</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• BLC - Back Light Compensation</li> <li>• HLC - High Light Compensation (spot)</li> <li>• Possibility to change the resolution, quality and bit rate</li> <li>• Motion Detection</li> <li>• Configurable Privacy Zones</li> <li>• Mirror - Mirror image</li> <li>• Sharpness - sharper image outlines</li> <li>• Intelligent image analysis : intrusion, crossing the line (tripwire), abandoned/missing object, scene changing, video tampering, face detection</li> </ul>	...
Power supply	12 V DC / 5 A (power adapter included)	• PoE (802.3af), • 12 V DC / 710 mA	...
Power consumption	...	≤ 10 W @ PoE (802.3af) ≤ 8.5 W @ 12 V DC	...
Housing	...	Dome, Metal + Plastic	...
Color	Black	Black	...
"Index of Protection"	...	IP66	...



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Vandal-proof	...	IK08	...
Operation temp	...	-30 °C ... 60 °C	...
Weight	2.1 kg	0.42 kg	0.136 kg
Dimensions	375 x 287 x 55 mm	Ø 120 x 67 mm	16.2 x 28 x 67 mm
Supported languages	English, Polish	Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, Finnish, French, Greek, Spanish, Dutch, Lithuanian, Latvian, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Hungarian, Vietnamese, Italian	...
Manufacturer / Brand	BCS	Hikvision	BIRA
SAP Code	...	311304737	...
Guarantee	2 years	3 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00