




	BATTERY 12V/7.2AH-MB	INSULATING GEL MAGIC-POWER-GEL-250 RayTech	IP CAMERA IPC2124LB-ADF28KM-H - 3.7 Mpx 2.8 mm UNIVIEW
			
	255.05 CZK 255.05 CZK	399.52 CZK 399.52 CZK	3819.92 CZK 3819.92 CZK
Standard	TCP/IP
Battery capacity	7.2 Ah
Voltage insulation	...	23 kV / mm	...
Rated voltage	12 V
Package capacity	...	2 x 125 ml	...
Sensor	1/2.9 " Progressive Scan CMOS
Battery charging current	max. 1.8 A
Matrix size	4 Mpx
Battery type	Maintenance-free AGM (Absorbent Glass Mat) battery
Connector	T1 type
Battery lifetime	3 ... 5 years
Main features	...	<ul style="list-style-type: none"> • Application : The product is dedicated to protecting electrical connections, • Gel color : Blue, Translucent 	...
Operation temp	...	-60 °C ... 200 °C	...
Resolution	2560 x 1440 - 3.7 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p , 1280 x 720 - 720p
Lens	2.8 mm
View angle	102 °
Range of IR illumination	30 m
S/N ratio	> 52 dB
RS-485 interface	—
Memory card slot	Micro SD memory cards up to 128GB support (possible local recording)
Image compression method	Ultra 265 / H.265 / H.264 / MJPEG
Alarm inputs / outputs	—
Audio	<ul style="list-style-type: none"> • Microphone built-in, • Audio transmission via network, • Audio detection
Main stream frame rate	20 fps @ 4 Mpx 25 fps @ 3 Mpx
Network interface	10/100 Base-T (RJ-45)
WEB Server	Built-in

Max. number of on-line users	32
ONVIF	✓
Mobile phones support	Access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application EZView • iOS (iPhone): Free application EZView
Default IP address	DHCP or 192.168.1.13
Default admin user / password	admin / 123456
Web browser access ports	80, 554
PC client access ports	Port no.: 80 or access by a cloud (P2P) - PC: Free application EZStation
Mobile client access ports	80
Port ONVIF	80
RTSP URL	rtsp://192.168.1.13:554/unicast/c1/s0/live - Main stream rtsp://192.168.1.13:554/unicast/c1/s1/live - Sub stream
Main features	<ul style="list-style-type: none"> • WDR - 120 dB - Wide Dynamic Range • 2D-DNR, 3D-DNR - Digital Noise Reduction • F-DNR (Defog) - Reduction of image noise caused by precipitation • ROI - improve the quality of selected parts of image • ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its • NAS - Network Attached Storage support • Corridor mode - useful for monitoring corridors, entrance gates and narrow rooms • BLC/HLC - Back Light / High Light Compensation • Possibility to change the resolution, quality and bit rate • Mirror - Mirror image • Privacy zones - max. 4 • Motion detection with human/vehicle silhouette recognition • Sharpness - sharper image outlines
Power supply	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 460 mA
Power consumption	≤ 5.5 W
Housing	Compact, Metal + Plastic
Color	White
"Index of Protection"	IP67

Vandal-proof	—
Operation temp	-30 °C ... 60 °C
Weight	1.8 kg	0.300 kg	0.38 kg
Dimensions	150 x 95 x 65 mm	80 x 74 x 100 mm	166 x 63 x 62 mm
Supported languages	Polish, English, Czech, Spanish, French, German, Portuguese, Slovak, Hungarian, Italian
Manufacturer / Brand	...	RayTech	UNIVIEW
Guarantee	2 years	2 years	3 years