






	EXTENDER USB-EX-50	ELECTRIC STRIKE XS12R-B REVERSIBLE Hartte BIRA	AHD, HD-CVI, HD-TVI CAMERA APTI-H50V3-2812 2Mpx / 5Mpx 2.8 ... 12 mm	CONNECTOR FOR LED STRIPS AD-TL-6499/Z/T/RGBW 12 mm ORNO	LED LIGHTING CONTROLLER ZigBee, ZL5 Wi-Fi, 2.4 GHz, RGB CCT (RGBWW) 12 ... 48 V DC MiBOXER / Mi-Light
					
	102.42 SEK 102.42 SEK	317.34 SEK 317.34 SEK	529.92 SEK 529.92 SEK	14.72 SEK 14.72 SEK	181.60 SEK 181.60 SEK
Strip width	12 mm	...
Connectors	• USB 1.1 • RJ45
Standard	AHD, HD-CVI, HD-TVI
Range	50 m
Sensor	1/2.7 " CMOS
Rated voltage	...	10 ... 14 V AC/DC	12 ... 48 V DC
Matrix size	5 Mpx
Current consumption	...	480 mA @ 12 V AC 680 mA @ 12 V DC
Maximal power voltage	48 V	...
UTP category	5 / 5e / 6
Application	...	right-side door / left-side door - for doors with lock latch pressing on electric strikes	...	Works with LED lighting RGBW	Works with LED lighting - (RGB/RGBW/RGBCCT/CCT/MONO) 12-24V LED strips
Ratched lock	...	—
Maximal total load	• 180 W @ 12 V, • 360 W @ 24 V
Memory function	...	—
Reverse action	...	✓
Clearance adjustment	...	3.5 mm
Total maximal current	6 A / Channel, 15 A (total)
Number of inputs	1
Allowable load of the door impacting the lock	...	3000 N
Number of outputs	5 (power)
Allowable uninterrupted operation time	...	—
Connector type	• screw terminals, • 5.5/2.1 socket / screw terminals - power input
Resolution	2592 x 1944 - 5 Mpx @ AHD / HD-TVI @ 20 fps, 12.5 fps , 2560 x 1440 - 4 Mpx @ AHD / HD-CVI / HD-TVI @ 25 fps, 30 fps , 1920 x 1080 - 1080p @ AHD / HD-CVI / HD-TVI
Range of IR illumination	30 m
Wireless	• 2.4 GHz, • ZigBee 3.0
IR illuminator power adjustment	Automatic
Radio communication range (at open area)	30 m
Lens	2.8 ... 12 mm
Mobile phones support	• Android: Free application MiBoxer , • iOS (iPhone): Free application MiBoxer Access by a cloud (P2P) • The Tuya Smart free application on Android • The Tuya Smart free application on iOS

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

View angle	<ul style="list-style-type: none"> • 88 ° ... 31 ° (manufacturer data) • 93 ° ... 35 ° (our tests result)
Main features	...	<ul style="list-style-type: none"> • Symmetrical housing • Narrow profile : 16.2 mm, • Strengthen spring, • Operation mode : NO • Resistance : 17.6 Ω • Number of opening cycles : 200000 • Radial shape of the latch - when opening the latch is not going beyond the outline of electric strike 	<ul style="list-style-type: none"> • The repeater function allows you to transfer control to subsequent FUT035S / FUT036S / FUT038S / FUT039 modules even beyond the direct range of the remote control, • The LED ZigBee 3.0 controller has the ability to change PWM frequency modulation, • Ability to work with any type of LED strip
Video output	1 Vpp 75 Ω, AHD / HD-CVI / HD-TVI - Via OSD, selectable by switch
Operation temp	-10 °C ... 40 °C
Main features	<ul style="list-style-type: none"> • D-WDR - Wide Dynamic Range • DNR - Digital Noise Reduction • ICR - Movable InfraRed filter • AGC - Automatic Gain Control • Auto White Balance • Day/Night mode - configurable • Sharpness - sharper image outlines
OSD menu	✓
Vandal-proof	—
"Index of Protection"	IP66	—	...
Power supply	12 V DC / 400 mA
Power consumption	≤ 4.8 W
Housing	Dome - Metal	...	Plastic
Color	Graphite	White	White
Operation temp	-20 °C ... 60 °C
Weight	0.05 kg (total)	0.136 kg	0.55 kg	0.002 kg	0.06 kg
Dimensions	54 x 32 x 22 mm	16.2 x 28 x 67 mm	Ø 120 x 100 mm	28 x 20 mm	124 x 37 x 22 mm
Supported languages	Polish, English, French, Spanish, Portuguese, Russian, Italian
Manufacturer / Brand	...	BIRA	APTI	ORNO	MiBOXER / Mi-Light
Guarantee	2 years	2 years	2 years	2 years	2 years