





	ROUTER RG-EG210G-P 8 PoE REYEE	DOUBLE-SIDED MARKER MARKER/0.5-1.0/BLACK	LED STRIP CABLE AD-TL-6498/RGB/25M 25 m ORNO	TOOL FOR CLEANING FIBER OPTIC CONNECTORS WUN-015 MU / LC	POWER DISTRIBUTION UNIT ACAR-S8/FA/RACK
					
	236.76 EUR 236.76 EUR	0.76 EUR 0.76 EUR	14.09 EUR 14.09 EUR	21.48 EUR 21.48 EUR	29.72 EUR 29.72 EUR
Rated voltage	230 V AC / 50 Hz
Nominal load current	10 A (total)
Nominal voltage of surge suppressor	250 V / 50 Hz
Standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3x, 802.3z, IEEE 802.3af, IEEE 802.3at
Protection level of surge suppressor	≤ 1.3 kV (L/N)
Inner conductor	4 x Ø 0.35 mm - Stranded wire
Number of outlets	8 grounded outlets 10A/250V
Application	...	Any surface : Wood, Fabric, Glass, Metal, Plastic, Ceramics, CD/DVD discs	LED strips - RGB	Ideal for removing dirt from optical components Connector type : MU / LC	...
Automatic delayed fuse	✓
LAN ports	• 8 x LAN & PoE 10/100/1000 Mbps (RJ-45) • 1 x LAN/WAN 10/100/1000 Mbps (RJ-45)
Nominal stroke current	2 kA (L/N) - 8/20 µs
Outer coating	4 x Ø 1.6 mm - PVC
WAN interface	• 1 x WAN 10/100/1000 Mbps (RJ-45)
Maximum stroke current	6.5 kA (L/N) - 8/20 µs
Leak current	< 0.5 mA
Response time	< 25 ns
LED indicators	Status, Link/Act
DDNS	✓
Switch	two-way, with light indication
Ink color	...	Black
Coating color	Black + Green + Red + Blue
DHCP server	✓
Length of the cable	25 m	...	2.9 m
Port USB	—
Firmware update	✓
Housing	RACK 19", 1U, Plastic - non-flammable
Power supply PoE	Power output - LAN ports : PoE (802.3af/at) max. 70 W (total)
Protections	• ACL • IP-MAC Binding • MAC addresses filtering • Support for dynamic ARP mapping and static table • NAT / NAPT • Port Mapping

Management interface	<ul style="list-style-type: none"> • Ruijie Cloud Central Management System • Configuration using the Ruijie Reyeer application • Remote management • Web browser
Mobile phones support	<p>Android: Free application Ruijie Reyeer</p> <p>iOS (iPhone): Free application Ruijie Reyeer</p>
Main features	<ul style="list-style-type: none"> • VPN networks: IPsec VPN, Open VPN, L2TP VPN, PPTP VPN, etc. • Static / dynamic routing • WAN : PPPoE, PPTP, L2TP • DHCP client/server support • Access Control List - ACL • package filtering based on source and destination IP addresses • Rate limit • Load balance • NAT • Reboot schedule • View topology and network status • RESET button 	<ul style="list-style-type: none"> • high quality • 2 line thicknesses, • round tips : 0.5 mm, 1 mm • waterproof permanent ink 	For indoor use
Power supply	100 ... 240 V AC, 50 / 60 Hz
Power consumption	≤ 80 W (at full load)
Operation temp	0 °C ... 40 °C
Permissible relative humidity	10 % ... 90 % (non-condensing)
Weight	0.53 kg	0.02 kg	0.61 kg
Dimensions	207 x 109 x 27 mm	141 x 15 x 11 mm	...	183 x 18 x 18 mm	445 x 54 x 55 mm
Manufacturer / Brand	RUIJIE / REYEE	...	ORNO
Guarantee	2 years	...	2 years	...	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00