



	<a href="#">SWITCH POE PFS3006-4ET-36 4-PORT DAHUA</a>	<a href="#">AHD, HD-CVI, HD-TVI, PAL CAMERA BCS-EA15FR3- G(H2) - 5 Mpx 3.6 mm</a>
		
	506.54 SEK 506.54 SEK	403.56 SEK 403.56 SEK
Standard	...	AHD / HD-CVI / HD-TVI / PAL
LAN ports	<ul style="list-style-type: none"> <li>• 2 x RJ45 10/100 Base-TX - Uplink,</li> <li>• 4 x RJ45 10/100 Base-TX ( 4 x PoE (802.3af/at) )</li> </ul>	...
Resolution	...	2704 x 1950 - 5 Mpx , 2560 x 1440 - 3.7 Mpx , 1920 x 1080 - 1080p
Standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3x, IEEE 802.3af, IEEE 802.3at	...
Sensor	...	1/2.5 " Progressive Scan CMOS
Management	—	...
Lens	...	3.6 mm, F1.2
View angle	...	• 100 °
Range of IR illumination	...	30 m
IR illuminator power adjustment	...	Automatic
LED diodes	Power, Link/Act, PoE	...
Transmission speed	10 / 100 Mbps : 2 LAN ports + 4 LAN & PoE ports	...
Maximal output power	30 W / port PoE	...
Video output	...	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω
Maximal total power	36 W	...
OSD menu	...	OSD menu available via BCS-XVR recorder
MAC addresses table	2k	...
Operation modes	<ul style="list-style-type: none"> <li>• Extend On : 250 m, 10 Mbps</li> <li>• Extend Off : 100 m, 100 Mbps</li> </ul>	...

Main features	...	<ul style="list-style-type: none"> <li>• D-WDR - Wide Dynamic Range</li> <li>• BLC - Back Light Compensation</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• HLC - High Light Compensation (spot)</li> <li>• ICR - Movable InfraRed filter</li> <li>• AGC - Automatic Gain Control</li> <li>• Auto White Balance</li> </ul>
Power consumption	...	< 5 W
Housing	...	Dome, Metal
Color	...	Graphite
Main features	<ul style="list-style-type: none"> <li>• PoE power mode : The device supports 8-pin power supply</li> <li>• EXTEND mode - ports PoE1, PoE2, PoE3, PoE4 support transmission up to 250 m</li> <li>• Watchdog PoE / PD Alive mode - monitoring of the ports that power PoE devices and automatic restart by cutting off the power supply when an unresponsive device is detected</li> <li>• protection against lightning discharges and voltage differences and strokes between devices</li> <li>• Kensington Lock</li> </ul>	...
"Index of Protection"	...	IP66
Mechanical protection class	...	—
Certificates	CE, FCC	...
Operation temp	...	-20 °C ... 60 °C
Power supply	100 V ... 240 V AC	12 V DC / 420 mA
Operation temp	-10 °C ... 55 °C	...
Weight	0.56 kg	0.3 kg
Dimensions	194 x 108 x 35 mm	Ø 80 x 94 mm
Manufacturer / Brand	DAHUA	BCS
Guarantee	3 years	3 years