





	TV OR MONITOR MOUNT BRATECK-LEA49-686	IP CAMERA DS-2CD1623G0-IZ(2.8-12MM) - 1080p - AutoFocus Hikvision	SURVEILLANCE KIT KIT/NVR1104HS-W-S2/4-F22 Wi-Fi. 4 CHANNELS HDD 1TB - 1080p 2.8 mm IMOU	AHD, HD-CVI, HD-TVI, PAL CAMERA HAC- HDW1200TRQ-0280B-S6 - 1080p 2.8 mm DAHUA
				
	125.78 AUD 125.78 AUD	400.22 AUD 400.22 AUD	383.16 AUD 383.16 AUD	65.67 AUD 65.67 AUD
Supported resolutions	max. 1080p - 1920 x 1080 px	...
Video outputs	1 pcs HDMI 1 pcs VGA	...
Audio support	4 Channels - Audio from cameras	...
Audio inputs	1 pcs CINCH	...
Audio outputs	1 pcs CINCH	...
Mounting standard	VESA 200, 300 x 200, 300, 400 x 200, 400 x 300, 400, 600 x 400, 800 x 400, 800 x 600
Screen size range	50 " ... 90 "
Bearing capacity	75 kg
IR illuminator power adjustment	Automatic
Distance from mounting surface	69 ... 635 mm
Tilt adjustment	-15 ° ... 5 °
Horizontal rotation	-60 ° ... 60 °
Rotation in the plane of the screen	± 3 °
Supported hard drives	• 1 x 8 TB SATA, • HDD : 1 TB (included)	...
Recording modes	Manual, Motion Detection, Schedule	...
External storage devices backup	Backup to USB drive (pendrive, external drive)	...
Video output	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω
Searching and playback the records	Records searching: by time and events type. Records playback: forward, backward, fast, slow Advanced searching (to the one second accuracy) 1/4 channel synchronous playback	...
Compression	...	H.265 / H.265+ / H.264 / H.264+ / MJPEG
OSD menu	OSD menu available via DAHUA recorder
Network functions	• Built-in Wi-Fi module - Imou cameras support : Smart, auto-pairing, Remote configuration, Remote management • Full support via network, Remote records copying, Web-Server built-in	...
Bitrate	...	32 ... 8192 kbps	max. 40 Mbps max. 16 Mbps Wi-Fi	...
Vandal-proof	—
USB	2 pcs USB 2.0	...
Serial ports	—	...
Alarm inputs / outputs	...	—	—	...
PTZ control	—	...
Motion Detection	✓	...
Intelligent image analysis	—	...
Mouse support	✓	...
IR remote controller in the set	—	...
Operation temp	-10 °C ... 45 °C	...
RS-485 interface	...	—
Max. number of on-line users	...	6
Standard	...	TCP/IP	TCP/IP TCP/IP	HD-CVI, HD-TVI, AHD, CVBS
Sensor	...	1/2.8 " Progressive Scan CMOS	1/2.8 " Progressive Scan CMOS	Progressive Scan CMOS
Matrix size	...	2.1 Mpx	2.1 Mpx	2 Mpx
Resolution	...	1920 x 1080 - 1080p 1280 x 960 - 1.3 Mpx 1280 x 720 - 720p	1920 x 1080 - 1080p	1920 x 1080 - 1080p, 960 x 576 - 960H, PAL
Lens	...	2.8 ... 12 mm - AutoFocus	2.8 mm	2.8 mm
View angle	...	• 98 ° ... 34 ° (manufacturer data) • 90 ° ... 35 ° (our tests result)	102 °	• 102 ° (manufacturer data) • 103 ° (our tests result)
Range of IR illumination	...	30 m	30 m	25 m

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Audio	...	—	• Microphone built-in, • Audio transmission via network	—
Image compression method	Smart H.265+ / H.265 / Smart H.264+ / H.264 H.265 / H.264	...
Main stream frame rate	...	25 fps @ 1080p	25 fps @ 1080p	...
Network protocols	...	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, UPnP, SMTP, IGMP, IEEE 802.1x, QoS, IPv6, UDP, Bonjour	HTTP, HTTPS, TCP/IP, IPv4, RTSP, UDP, NTP, DHCP, DNS, Alarm Server, P2P TCP, DHCP	...
ONVIF	✓ ✓	...
Operation temp	...	-30 °C ... 60 °C	...	-40 °C ... 60 °C
Network interface	...	10/100 Base-T (RJ-45)	• 1 x RJ-45 10/100 Base-TX • 2.4 GHz Wi-Fi - IEEE 802.11 b/g/n • Ethernet : 100 Mbps • Wi-Fi IEEE 802.11 b/g/n - 2.4 GHz	...
WEB Server	...	Built-in, NVR compliance	—	...
Housing	...	Compact, Metal	...	Dome, Plastic
Color	Black	White	...	White
Mobile phones support	...	Port no.: 8000 or access by a cloud (P2P) • Android: Free application iVMS-4500 or Hik-Connect • iOS (iPhone): Free application iVMS-4500 or Hik-Connect	Port no.: 37777 or access by a cloud (P2P) • Android: Free application IMOU • iOS (iPhone): Free application IMOU • Access by a cloud (P2P) • Android: Free application IMOU • iOS (iPhone): Free application IMOU	...
Default admin user / password	...	admin / -	admin / - The administrator password should be set at the first start admin / - The administrator password should be set at the first start	...
Default IP address	...	192.168.1.64	192.168.1.108 DHCP	...
Web browser access ports	...	80	80, 37777 —	...
PC client access ports	...	Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application	37777 —	...
Mobile client access ports	...	8000	37777 —	...
Port ONVIF	...	80	—	...
RTSP URL	...	• Main stream rtsp://192.168.1.64:554/Streaming/Channels/101/ - RTSP - without authorization rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/ - with authorization • Sub stream rtsp://192.168.1.64:554/Streaming/Channels/102/ - RTSP - without authorization rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/ - with authorization	rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream —	...
Memory card slot	...	Micro SD memory cards up to 128GB support (possible local recording)	Micro SD memory cards up to 256GB support (possible local recording)	...
SAP Code	...	311300897
Main features	...	• D-WDR - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • ROI - improve the quality of selected parts of image • Anti-Flicker - The technology eliminates the tiring eyes flickering image effect • WB - White Balance (ATW/AWB/manual/indoor/outdoor) • BLC - configurable Back Light Compensation • AGC - Automatic Gain Control • ICR - Movable InfraRed filter • Day/Night mode (color/b&w/auto) • Motion Detection • Configurable Privacy Zones • Mirror - Mirror image • Sharpness - sharper image outlines	• Smart, auto-paring < 120 s • Alarm notifications • 2x2 MIMO - MIMO technology - increases the throughput of wireless link (multiple antennas transmission) • Operating range in open area : 100 m • Wi-Fi Module - IEEE 802.11 b/g/n, Range : 50 m (open area) • Motion Detection • People detection • D-ZOOM - Digital Zoom : 16x	• D-WDR - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • BLC/HLC - Back Light / High Light Compensation • Day/night mode • AGC - Automatic Gain Control • ICR - Movable InfraRed filter • Auto White Balance • Privacy zones - max. 8 • Mirror - Mirror image • Sharpness - sharper image outlines
Power supply	...	• PoE (802.3af), • 12 V DC / 900 mA	12 V DC / 1.5 A (power adapter included) 12 V DC / 0.5 A (power adapter included)	12 V DC / 220 mA
Power consumption	...	≤ 12.9 W @ PoE (802.3af) ≤ 11 W @ 12 V DC	≤ 10 W (without HDD) < 3.5 W	≤ 2.7 W
"Index of Protection"	...	IP67	IP67	IP50
Weight	10.6 kg	0.72 kg	1.3 kg (Recorder with HDD) 0.25 kg	0.15 kg
Dimensions	885 x 630 x (69 ... 635) mm	Ø 105 x 245	260 x 248 x 48 mm 148 x 74 x 74 mm	Ø 97 x 93 mm
Supported languages	...	Polish, English, French, Spanish, Portuguese, Russian, Turkish, Italian	Polish, English —	...

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Connecting cable	-	...
Manufacturer / Brand	...	Hikvision	IMOU	DAHUA
Guarantee	2 years	3 years	2 years	3 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00