



	EXPANSION PLUG KW-10/5X80 KLIMAS	IP CAMERA IPC-HFW2241S-S-0280B WizSense - 1080p 2.8 mm DAHUA
		
	0.57 PLN 0.57 PLN	789.00 PLN 789.00 PLN
Standard	...	TCP/IP
Sensor	...	1/2.8 " Progressive Scan CMOS
Matrix size	...	2.1 Mpx
Material	<ul style="list-style-type: none"> • Expansion plug, Polypropylene • Screw, Steel galvanized 	...
Drilling diameter	10 mm	...
Expansion plug length	50 mm	...
Screw dimensions	Ø 5 x 80 mm, PZ-2	...
Resolution	...	1920 x 1080 - 1080p 1280 x 960 - 1.3 Mpx 1280 x 720 - 720p
Lens	...	2.8 mm
Application	<ul style="list-style-type: none"> • Concrete • Solid clay brick • Solid sand-lime brick 	...
View angle	...	<ul style="list-style-type: none"> • 107 ° (manufacturer data) • 102 (our tests result)
Range of IR illumination	...	30 m
RS-485 interface	...	—
Memory card slot	...	Micro SD memory cards up to 256GB support (possible local recording)
Image compression method	...	H.265+ / H.265 / H.264+ / H.264 / MJPEG
Alarm inputs / outputs	...	—
Audio	...	<ul style="list-style-type: none"> • Microphone built-in • Audio detection
Main stream frame rate	...	25 fps @ 1080p
Network interface	...	10/100 Base-T (RJ-45)
Network protocols	...	IPv4/IPv6, HTTP, TCP, UDP, ARP, RTP, RTSP, RTCP, RTMP, SMTP, FTP, SFTP, DHCP, DNS, DDNS, NTP, Multicast, ICMP, IGMP
WEB Server	...	Built-in
Max. number of on-line users	...	6
ONVIF	...	21.06
Mobile phones support	...	Port no.: 37777 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application DMSS • iOS (iPhone): Free application DMSS
Default IP address	...	192.168.1.108
Default admin user / password	...	admin / - The administrator password should be set at the first start
Web browser access ports	...	80, 37777

PC client access ports	...	37777
Mobile client access ports	...	37777
Port ONVIF	...	80
RTSP URL	...	rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream
Main features	...	<ul style="list-style-type: none"> • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • ROI - improve the quality of selected parts of image • BLC/HLC - Back Light / High Light Compensation • ICR - Movable InfraRed filter • Day/Night mode (color/b&w/auto) • WB - White Balance (ATW/AWB/manual/indoor/outdoor) • AGC - Automatic Gain Control • Possibility to change the resolution, quality and bit rate • Configurable Privacy Zones • Mirror - Mirror image • Motion Detection • Privacy zones • SMD PLUS - searching for an object classified as: human, motor vehicle • IVS analysis : intrusion, crossing the line (tripwire) - classification of people and vehicles
Power supply	...	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 350 mA
Power consumption	...	max. 5.1 W @ PoE max. 4.2 W @ 12 V DC
Housing	...	Compact - Metal
Color	...	White
"Index of Protection"	...	IP67
Operation temp	...	-40 °C ... 60 °C
Weight	...	0.47 kg
Dimensions	...	Ø 70 x 166 mm
Supported languages	...	Polish, English, Czech, French, Spanish, Dutch, German, Portuguese, Russian, Romanian, Turkish, Ukrainian, Hungarian, Vietnamese, Italian
Manufacturer / Brand	KLIMAS	DAHUA
Guarantee	2 years	3 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00