





	TV OR MONITOR MOUNT BRATECK-LPA68-221	AHD, HD-CVI, HD-TVI, CVBS CAMERA HAC-HFW1500CL-IL- A-0360B-S2 - 5 Mpx 3.6 mm DAHUA	TOOL FOR CLEANING FIBER OPTIC CONNECTORS WUN-XK25 SC-APC / SC-UPC	SAT AMPLIFIER SVS-2-01 20 dB AXING
				
	7.18 EUR 7.18 EUR	77.80 EUR 77.80 EUR	7.47 EUR 7.47 EUR	5.81 EUR 5.81 EUR
Application	Ideal for removing dirt from optical components	...
Frequency range	950 MHz ... 2400 MHz
Gain	20 dB
Connector type	SC-APC / SC-UPC	...
Correction in satellite frequencies range	—
Mounting standard	VESA : 100, 200, 200x100
Standard	...	AHD, HD-CVI, HD-TVI, CVBS
Output level	106 dB μ V
Sensor	...	Progressive Scan CMOS
Connectors type	"F"
Screen size range	23 " ... 43 "
Matrix size	...	5 Mpx
DC voltage passing	✓
Bearing capacity	30 kg
Distance from mounting surface	56 ... 204 mm
Current consumption	≤ 80 mA (without LNB powering)
Tilt adjustment	-8 ° ... 5 °
Horizontal rotation	-90 ° ... 90 °
Rotation in the plane of the screen	—
Resolution	...	<ul style="list-style-type: none"> • 2880 x 1620 - 5 Mpx @ HD-CVI @ 25 fps - Aspect Ratio 16 : 9, • 2560 x 1440 - 4 Mpx @ AHD / HD-CVI / HD-TVI @ 25 fps, • 1920 x 1080 - 1080p @ HD-CVI @ 25 fps, • 960 x 576 - 960H @ PAL
Lens	...	3.6 mm
View angle	...	<ul style="list-style-type: none"> • 92 ° (manufacturer data) • 86 ° (our tests result)
Range of IR illumination	...	20 m
White light LED illuminator range	...	20 m
Video output	...	AHD / HD-CVI / HD-TVI / CVBS, 1 V _{pp} / 75 Ω
Audio	...	<ul style="list-style-type: none"> • Microphone built-in, • Audio support via coaxial cable - HD-CVI only
OSD menu	...	OSD menu available via DAHUA recorder

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Main features	...	<ul style="list-style-type: none"> • Smart Dual Illumination technology - IR or LED illuminator works in night mode. White light will turn on automatically only when an object is detected in the monitored area, which effectively improves image quality • D-WDR - Wide Dynamic Range • AGC - Automatic Gain Control • ICR - Movable InfraRed filter • BLC/HLC - Back Light / High Light Compensation • 2D-DNR - Digital Noise Reduction • Privacy zones - max. 8 • Mirror - Mirror image • Auto White Balance • Sharpness - sharper image outlines
"Index of Protection"	...	IP67
Power supply	...	12 V DC / 380 mA	...	14 ... 18 V DC (from the SAT receiver or the multiswitch)
Power consumption	...	≤ 4.5 W
Housing	...	Compact, Plastic
Vandal-proof	...	—
Color	Black	White + Black
Operation temp	...	-40 °C ... 60 °C
Weight	1.03 kg	0.18 kg	0.02 kg	...
Dimensions	230 x 230 x (56 ... 205) mm	163 x 70 x 70 mm	178 x 17 x 17 mm	...
Manufacturer / Brand	BRATECK	DAHUA	...	AXING
Guarantee	2 years	3 years	...	2 years

