



	<a href="#">EXTENDER USB-EX-150/4-USB</a>	<a href="#">MODULAR CONTACTOR KMC-20-20 20 A 230 V AC IDEAL</a>
		
	62.14 EUR 62.14 EUR	8.62 EUR 8.62 EUR
Device type	...	Contactor - NO, One-phase
Connectors	<ul style="list-style-type: none"> <li>• Transmitter :</li> <li>- 1 x USB-A</li> <li>- 1 x RJ-45 shielded socket</li> <li>• Receiver :</li> <li>- 4 x USB-A</li> <li>- 1 x RJ-45 shielded socket</li> </ul>	...
Nominal load current	...	<ul style="list-style-type: none"> <li>• 20 A @ AC7A / AC1,</li> <li>• 7 A @ AC7B</li> </ul>
Rated load voltage	...	230 V AC
Nominal power voltage	...	230 V AC
Range	<ul style="list-style-type: none"> <li>• 150 m - USB 2.0 @ UTP cat. 6,</li> <li>• 100 m - USB 2.0 @ UTP cat. 5e</li> </ul>	...
UTP category	5e / 6 / 6A / 7	...
Nominal power	...	<ul style="list-style-type: none"> <li>• 4000 W @ 230 V AC7A</li> <li>• 1200 W @ 230 V AC7B</li> </ul>
Number of NO/NC contacts	...	2 / 0
Category of use	...	AC1, AC7A, AC7B
Connectors type	...	screw terminals
Main features	<ul style="list-style-type: none"> <li>• USB 2.0 - High-Speed (480 Mb/s) (compatible with older)</li> <li>• Supports 4 USB 2.0 inputs and 1 USB 2.0 output</li> <li>• The transmitter is powered from the source device - no additional power supply is required</li> <li>• The device supports a cascade of gigabit switches, which allows to increase the transmission distance</li> <li>• Lightning protection, surge protection, ESD protection</li> <li>• Easy installation - Plug&amp;Play USB device type</li> </ul>	<ul style="list-style-type: none"> <li>• Operation temp : -25 °C ... 40 °C</li> <li>• Supported norms : PN-EN 60947-4-1, PN/EN 61095</li> </ul>

Power supply	5 V DC / 1 A (power adapter included) - Receiver	...
Operation temp	-20 °C ... 60 °C	...
Housing	Metal	Plastic, DIN, TH-35 rail mounting
"Index of Protection"	...	IP20
Width in 17.5 mm modules	...	1
Weight	0.12 kg	0.13 kg
Dimensions	77 x 61 x 21 mm	67 x 82 x 17.5 mm
Manufacturer / Brand	...	IDEAL
Guarantee	2 years	5 years