





	INVERTER POWER GENERATOR F-2001/IS 1800 W FOGO	AHD, HD-CVI, HD-TVI, PAL CAMERA APTI-H52V21-36W - 8.3 Mpx 4K UHD 3.6 mm	ALKALINE BATTERY BAT-AA-MAXPLUS*P4 1.5 V LR6 (AA) ENERGIZER	AHD, HD-CVI, HD-TVI, PAL CAMERA HAC-HDW2802T-A-0280B-S2-DIP - 8.3 Mpx, 4K UHD 2.8 mm DAHUA
				
	673.11 EUR 673.11 EUR	36.88 EUR 36.88 EUR	3.03 EUR 3.03 EUR	175.06 EUR 175.06 EUR
Nominal power	1800 W
Maximum power	2000 W
Output voltage	230 V AC
Standard	...	AHD, HD-CVI, HD-TVI, PAL	...	AHD, HD-CVI, HD-TVI, PAL
In package	4 pcs The price for package	...
Number of outlets	1 pcs - single-phase
Rated voltage	1.5 V	...
Built-in voltmeter	—
Matrix size	...	8.3 Mpx
Type (size)	LR6 (AA)	...
Output frequency	50 Hz
Voltage stabilization	Inverter (provides full voltage stabilization)
12V DC output	✓
Engine capacity	79.7 cm ³
Engine type	Rato R 80 I 1 cylinder, 4 stroke, gasoline, air cooled
Starting the engine	Manual
Noise level during operation	89 dB
Average fuel consumption	• 0.67 l/h - 50 % power • 1.1 l/h - 100 % power
Fuel tank capacity	4 l
Fuel gauge	✓
Main features	<ul style="list-style-type: none"> • Low oil level indicator light • Overload signaling • Overload protection • Battery charging possible • Save fuel by automatically reducing the revs as the load decreases • Possibility to combine two F-2001/IS power generators into one generator set 	...	<ul style="list-style-type: none"> • Longest Lasting Alkaline Batteries, • Powerful and high performance, • Holds power for up to 12 years of shelf life, • Leak-proof construction 	...
Sensor	...	1/2.5 " Progressive Scan CMOS	...	" Progressive Scan CMOS

Resolution	...	<ul style="list-style-type: none"> • 3840 x 2160 - 8.3 Mpx 4K UHD @ AHD / HD-CVI / HD-TVI 12.5 fps, 15 fps, • 2592 x 1944 - 5 Mpx @ AHD / HD-TVI 12.5 fps, 20 fps, • 2560 x 1440 - 4 Mpx @ AHD / HD-CVI / HD-TVI @ 15 fps, 25 fps, 30 fps, • 1920 x 1080 - 1080p @ AHD / HD-TVI / HD-CVI @ 25 fps, 30 fps, • 960 x 576 - 960H @ PAL 	...	<ul style="list-style-type: none"> • HD-CVI : 3840 x 2160 - 8.3 Mpx, 4K UHD @ 15 fps , 3072 x 2048 - 6.3 @ 20 fps , 2560 x 1440 - 3.7 Mpx @ 25 fps , • AHD / HD-TVI : 2592 x 1944 - 5 Mpx , 2560 x 1440 - 3.7 Mpx @ 25 fps , • CVBS : 960 x 576 - 960H, PAL
Range of IR illumination	...	20 m	...	60 m
IR illuminator power adjustment	...	Automatic	...	Automatic
Lens	...	3.6 mm	...	2.8 mm
View angle	...	<ul style="list-style-type: none"> • 77 ° (manufacturer data) • 84 ° (our tests result) 	...	111 °
S/N ratio	...	> 50 dB	...	> 65 dB
Audio	Microphone built-in - HD-CVI only
Video output	...	1 Vpp 75 Ω, AHD / HD-CVI / HD-TVI / PAL - selectable by switch	...	AHD / HD-CVI / HD-TVI / PAL, 1 Vpp / 75 Ω
Main features	...	<ul style="list-style-type: none"> • D-WDR - Wide Dynamic Range • DNR - Digital Noise Reduction • ICR - Movable InfraRed filter • AGC - Automatic Gain Control • BLC - Back Light Compensation • Day/Night mode (color/b&w/auto) • Auto White Balance • Sharpness - sharper image outlines 	...	<ul style="list-style-type: none"> • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • F-DNR (Defog) - Reduction of image noise caused by precipitation • D-ZOOM - Digital Zoom x4 • BLC/HLC - Back Light / High Light Compensation • ICR - Movable InfraRed filter • Auto White Balance • AGC - Automatic Gain Control • Sharpness - sharper image outlines
OSD menu	...	✓	...	OSD menu available via DAHUA recorder
Power supply	...	12 V DC / 280 mA	...	12 V DC / 530 mA
Vandal-proof	—
Power consumption	...	≤ 3.3 W	...	≤ 6.4 W
Housing	...	Dome - Metal	...	Dome, Metal
Color	Red	White	...	White
"Index of Protection"	...	IP66	...	IP67
IK rating	...	—
Operation temp	...	-20 °C ... 50 °C	...	-40 °C ... 60 °C
Weight	21.1 kg	0.28 kg	0.024 kg	0.49 kg
Dimensions	498 x 290 x 459 mm	Ø 93 x 77 mm	...	Ø 106 x 94 mm
Supported languages	...	Polish, English, French, Spanish, Portuguese, Russian, Italian	...	Polish, English
Manufacturer / Brand	FOGO	APTI	ENERGIZER	DAHUA
Guarantee	12 months	2 years	2 years	3 years

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00