



	ACCESS CONTROLLER MODULE MC16-PAC-EX-1 ROGER	AHD, HD-CVI, HD-TVI, PAL CAMERA HAC-HFW1200CM-IL- A-0360B-S6 - 1080p 3.6 mm DAHUA
		
	340.07 EUR 340.07 EUR	76.03 EUR 76.03 EUR
Number of served transitions	1	...
Inputs	8	...
Outputs	8	...
Standard	...	AHD, HD-CVI, HD-TVI, CVBS
Sensor	...	Progressive Scan CMOS
Number of users	max. 12000 - Number of identifiers	...
Matrix size	...	2.1 Mpx
Number of media per ID	8 - Proximity card, PIN code, fingerprint, etc.	...
Number of permissions per ID	100	...
Buffer memory	8 000 000 events buffer	...
MCT readers support	16 pcs	...
Readers connections	4 pcs - Wiegand / PRT	...
Number of login points	2	...
Number of access terminals	4	...
Number of access zones	2	...
Number of alarm zones	2	...
Resolution	...	1920 x 1080 - 1080p @ AHD / HD-CVI / HD-TVI @ 25 fps , 960 x 576 - 960H @ PAL @ 25 fps
Number of automation nodes	2	...
Lens	...	3.6 mm
Battery backup support	12 V / 7 Ah	...
View angle	...	• 83 ° (manufacturer data) • 83 ° (our tests result)
Range of IR illumination	...	20 m
Communication	• Ethernet - RJ-45 socket • RS-485 interface • RACS 5 v2 (Roger)	...
White light LED illuminator range	...	20 m

IR illuminator power adjustment	...	Automatic
Video output	...	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω
Audio	...	<ul style="list-style-type: none"> • Microphone built-in, • Audio support via coaxial cable - HD-CVI only
Main features	<ul style="list-style-type: none"> • Integrated support in VISO EX software • Functions in the VISO EX system: <ul style="list-style-type: none"> - MSSQL database - work in distributed systems - multi-station work - monitoring of transitions with video preview - T&A event reporting - maximum number of transitions in the system - unlimited - division of the system into partitions operated by independent operators - tool for integration with RACS5 (API) systems - integration with many systems (elevator systems, building applications, SMS, BMS, PSIM, VMS, Active Directory systems) 	...
OSD menu	...	✓
Operation temp	5 °C ... 40 °C	...
Permissible relative humidity	10 % ... 95 % (non-condensing)	...



Main features	...	<ul style="list-style-type: none"> • Smart Dual Illumination technology - IR or LED illuminator works in night mode. White light will turn on automatically only when an object is detected in the monitored area, which effectively improves image quality • D-WDR - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • BLC/HLC - Back Light / High Light Compensation • ICR - Movable InfraRed filter • AGC - Automatic Gain Control • Privacy zones - max. 8 • Mirror - Mirror image • Auto White Balance • Sharpness - sharper image outlines
Power supply	<ul style="list-style-type: none"> • 17 ... 22 V AC • 10 ... 15 V DC • 22 ... 26 V DC 	12 V DC / 220 mA
Power consumption	...	≤ 2.6 W
Housing	...	Compact - Metal
Color	...	White
"Index of Protection"	...	IP67
Vandal-proof	...	—
Operation temp	...	-40 °C ... 60 °C
Weight	0.14 kg	0.33 kg
Dimensions	175 x 72 x 30 mm	167 x 70 x 70 mm
Manufacturer / Brand	ROGER	DAHUA
Guarantee	3 years	3 years