




	TRIPLE SMART SWITCH SWITCHBOX-T-PRO/BLEBOX Wi-Fi, 230 V AC	POWER SUPPLY ADAPTER RACK ZR12-150X2 2 x 12 V DC 2 x 12.5 A	CONNECTOR WITH ELASTIC SEALING F/6.8*P10
			
	831.46 NOK 831.46 NOK	936.67 NOK 936.67 NOK	20.21 NOK 20.21 NOK
Application	switching devices on/off
Rated voltage	230 V AC
Adapter type	...	Switching - 2 pcs	...
In package	10 pcs The price for package
Connector type	"F" Straight plug
Attachment of connector elements	Twisted-on
Shield fastening	Twisting-on
Power voltage	...	selectable by switch • 90 V ... 132 V AC, • 180 V ... 264 V AC	...
Wire mounting	—
Application	Coaxial cable
Voltage frequency range	...	47 ... 63 Hz	...
Cable diameter	max. 6.8 ± 0.05 mm
Output power	...	2 x 150 W	...
Maximal total load	• 3 x 3680 W (resistance load) - AC, • 3 x 500 W (inductive or capacitive load) - AC, • 3 x 380 W - DC
Impedance	75 Ω
Material	Metal
Output voltage	...	2 x 12 V DC	...
Total maximal current	3 x 16 A
Number of inputs	3
Output voltage adjustment	...	11.4 V ... 13.2 V DC	...
Number of outputs	3
Connector type	screw terminals
Maximal load	...	2 x 12.5 A	...
Efficiency	...	89 %	...
Wireless	Wi-Fi, 2.4 GHz - IEEE 802.11g
MTBF (Mean Time Between Faults)	...	> 700000 h - Telcordia SR-332	...

Mobile phones support	<ul style="list-style-type: none"> • The wBox free application on Android • The wBox free application on iOS
Protections	...	<ul style="list-style-type: none"> • Overvoltage • Short-circuit • Overload 	...
Housing type	...	1 U Rack 19"	...
Operation temp. / Relative humidity	...	-10 °C ... 70 °C / 10 % ... 95 %	...
Main features	<ul style="list-style-type: none"> • Supports max. 3 devices, • Local control by physical button, • schedule, • timer, • sunrise and sunset mode, • remote access, • voice control, • Keyboard built-in - 3 Touch control keys, • Backlit, touch control panel • Omnidirectional antenna Wi-Fi 5 dB, • SMA-RP socket • µWiFi technology support 	...	<ul style="list-style-type: none"> • Elastic sealing • Wide frequency range • Corrosion resistance
Housing	Self-extinguishing , Surface-mounted (box)
"Index of Protection"	IP44
Color	Gray / Black
Operation temp	-20 °C ... 50 °C
Weight	0.42 kg	1.17 kg	0.003 kg
Dimensions	<ul style="list-style-type: none"> • 129 x 96 x 57 mm - without antenna • 285 x 96 x 57 mm - with antenna, vertical • 197 mm - Antenna 	483 x 44 x 100 mm	Ø 11 mm x 20 mm
Manufacturer / Brand	BleBox	DELTA	...
Guarantee	2 years	5 years	2 years