



	IP CAMERA IPC-HFW2241S-S-0280B WizSense - 1080p 2.8 mm DAHUA	FOLDING ALUMINUM MAST M-1.5SA/40 1.5 m
		
	189.66 EUR 189.66 EUR	11.85 EUR 11.85 EUR
Standard	TCP/IP	...
Height of the mast	...	1.5 m
Mast diameter	...	Ø 40 mm
Sensor	1/2.8 " Progressive Scan CMOS	...
Number of sections	...	1
Matrix size	2.1 Mpx	...
Wall thickness	...	1.5 mm
Material	...	Aluminum
Possibility to combine to each other	...	✓
Resolution	1920 x 1080 - 1080p 1280 x 960 - 1.3 Mpx 1280 x 720 - 720p	...
Lens	2.8 mm	...
View angle	<ul style="list-style-type: none"> • 107 ° (manufacturer data) • 102 (our tests result) 	...
Range of IR illumination	30 m	...
RS-485 interface	—	...
Memory card slot	Micro SD memory cards up to 256GB support (possible local recording)	...
Image compression method	H.265+ / H.265 / H.264+ / H.264 / MJPEG	...
Alarm inputs / outputs	—	...
Audio	<ul style="list-style-type: none"> • Microphone built-in • Audio detection 	...
Main stream frame rate	25 fps @ 1080p	...
Network interface	10/100 Base-T (RJ-45)	...
Network protocols	IPv4/IPv6, HTTP, TCP, UDP, ARP, RTP, RTSP, RTCP, RTMP, SMTP, FTP, SFTP, DHCP, DNS, DDNS, NTP, Multicast, ICMP, IGMP	...
WEB Server	Built-in	...
Max. number of on-line users	6	...
ONVIF	21.06	...
Mobile phones support	Port no.: 37777 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application DMSS • iOS (iPhone): Free application DMSS 	...
Default IP address	192.168.1.108	...
Default admin user / password	admin / - The administrator password should be set at the first start	...
Web browser access ports	80, 37777	...
PC client access ports	37777	...

Mobile client access ports	37777	...
Port ONVIF	80	...
RTSP URL	rtsp://admin:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream	...
Main features	<ul style="list-style-type: none"> • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • ROI - improve the quality of selected parts of image • BLC/HLC - Back Light / High Light Compensation • ICR - Movable InfraRed filter • Day/Night mode (color/b&w/auto) • WB - White Balance (ATW/AWB/manual/indoor/outdoor) • AGC - Automatic Gain Control • Possibility to change the resolution, quality and bit rate • Configurable Privacy Zones • Mirror - Mirror image • Motion Detection • Privacy zones • SMD PLUS - searching for an object classified as: human, motor vehicle • IVS analysis : intrusion, crossing the line (tripwire) - classification of people and vehicles 	...
Power supply	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 350 mA 	...
Power consumption	max. 5.1 W @ PoE max. 4.2 W @ 12 V DC	...
Housing	Compact - Metal	...
Color	White	...
"Index of Protection"	IP67	...
Operation temp	-40 °C ... 60 °C	...
Weight	0.47 kg	0.72 kg
Dimensions	Ø 70 x 166 mm	...
Supported languages	Polish, English, Czech, French, Spanish, Dutch, German, Portuguese, Russian, Romanian, Turkish, Ukrainian, Hungarian, Vietnamese, Italian	...
Manufacturer / Brand	DAHUA	DELTA
Guarantee	3 years	3 years