




|                                 |  |  |   |
|---------------------------------|--|--|---|
|                                 | <a href="#">SMART SWITCH SWITCHBOX-LIGHT/BLEBOX</a><br>Wi-Fi, 230 V AC   | <a href="#">AHD, HD-CVI, HD-TVI, PAL CAMERA DS-2CE76H0T-ITPFS(2.8mm) - 5 Mpx</a><br>Hikvision  | <a href="#">AHD, HD-CVI, HD-TVI CAMERA APTI-H50PV21-28W 2Mpx / 5Mpx</a><br>2.8 mm   |
|                                 |   |   |    |
|                                 | 22.32 EUR<br>22.32 EUR   | 51.15 EUR<br>51.15 EUR   | 23.05 EUR<br>23.05 EUR  |
| Application                     | switching devices on/off   | ...  | ...   |
| Rated voltage                   | 230 V AC   | ...  | ...   |
| Maximal total load              | 1150 W / 1150 VA   | ...  | ...   |
| Standard                        | ...  | AHD / HD-CVI / HD-TVI / CVBS   | AHD, HD-CVI, HD-TVI   |
| Total maximal current           | 5 A  | ...  | ...   |
| Sensor                          | ...  | Progressive Scan CMOS  | 1/3 " Progressive Scan CMOS   |
| Number of inputs                | 1  | ...  | ...   |
| Matrix size                     | ...  | 5 Mpx  | 5 Mpx   |
| Number of outputs               | 1  | ...  | ...   |
| Connector type                  | screw terminals  | ...  | ...   |
| Wireless                        | Wi-Fi, 2.4 GHz - IEEE 802.11g  | ...  | ...   |
| Mobile phones support           | <ul style="list-style-type: none"> <li>The <a href="#">wBox</a> free application on Android</li> <li>The <a href="#">wBox</a> free application on iOS</li> </ul>   | ...  | ...   |
| Resolution                      | ...  | <ul style="list-style-type: none"> <li>• 2560 x 1944 - 5 Mpx @ AHD / HD-TVI - 20 fps</li> <li>• 2560 x 1440 - 4 Mpx @ AHD / HD-CVI / HD-TVI - 25 fps</li> <li>• 1920 x 1080 - 1080p @ HD-TVI - 25 fps</li> <li>• 960 x 576 - 960H @ PAL</li> </ul> | <ul style="list-style-type: none"> <li>• 2592 x 1944 - 5 Mpx @ AHD, HD-TVI,</li> <li>• 2560 x 1440 - 3.7 Mpx @ AHD, HD-TVI, HD-CVI,</li> <li>• 1920 x 1080 - 1080p @ AHD, HD-CVI, HD-TVI</li> </ul> |
| Range of IR illumination        | ...  | 20 m   | 20 m  |
| Main features                   | <ul style="list-style-type: none"> <li>• Local control by physical button,</li> <li>• schedule,</li> <li>• timer,</li> <li>• remote access,</li> <li>• voice control,</li> <li>• The ability to set the default status of the device after a power failure,</li> <li>• µWiFi technology support</li> </ul> | ...  | ...   |
| IR illuminator power adjustment | ...  | Automatic  | Automatic   |

|                        |                  |   |   |
|------------------------|------------------|---|---|
| Lens                   | ...              | 2.8 mm  | 2.8 mm  |
| View angle             | ...              | 86 °  | • 89 ° (manufacturer data)<br>• 83 ° (our tests result)   |
| Operation temp         | -20 °C ... 50 °C | ...   | ...   |
| IR illuminator support | ...              | ICR - Movable InfraRed filter   | ...   |
| Video output           | ...              | AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω  | 1 Vpp 75 Ω, AHD, HD-CVI, HD-TVI - selectable by switch  |
| Audio                  | ...              | • Microphone built-in<br>• Audio support via coaxial cable  | ...   |
| Main features          | ...              | <ul style="list-style-type: none"> <li>• D-WDR - Wide Dynamic Range</li> <li>• 2D-DNR - Digital Noise Reduction</li> <li>• EXIR - high-efficiency infrared LEDs technology, which evenly covers the whole plan of both central vantage points of the scene as well as the corners</li> <li>• AGC - Automatic Gain Control</li> <li>• BLC - Back Light Compensation</li> <li>• HLC - High Light Compensation (spot)</li> <li>• ICR - Movable InfraRed filter</li> <li>• Auto White Balance</li> <li>• Mirror - Mirror image</li> <li>• Sharpness - sharper image outlines</li> </ul> | <ul style="list-style-type: none"> <li>• D-WDR - Wide Dynamic Range</li> <li>• DNR - Digital Noise Reduction</li> <li>• ICR - Movable InfraRed filter</li> <li>• AGC - Automatic Gain Control</li> <li>• BLC - Back Light Compensation</li> <li>• Sharpness - sharper image outlines</li> <li>• Auto White Balance</li> </ul> |
| OSD menu               | ...              | OSD menu available via recorder   | OSD menu available via recorder   |
| Power supply           | ...              | 12 V DC / 310 mA  | 12 V DC / 180 mA  |
| Power consumption      | ...              | ≤ 3.7 W   | ≤ 2.2 W   |
| Housing                | Plastic          | Dome, Plastic   | Dome - Plastic  |
| Color                  | Black            | White   | White   |
| "Index of Protection"  | IP20             | —   | —   |
| Vandal-proof           | ...              | —   | —   |
| Operation temp         | ...              | -40 °C ... 60 °C  | -20 °C ... 60 °C  |
| Weight                 | 0.027 kg         | 0.15 kg   | 0.11 kg   |
| Supported languages    | ...              | ...   | Polish, English, French, Spanish, Portuguese, Russian, Italian  |
| Dimensions             | 38 x 25 x 23 mm  | Ø 85 x 79 mm  | Ø 84 x 69 mm  |
| Manufacturer / Brand   | BleBox           | Hikvision   | APTI  |
| SAP Code               | ...              | 300613327   | ...   |

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

|           |         |         |         |
|-----------|---------|---------|---------|
| Guarantee | 2 years | 3 years | 2 years |
|-----------|---------|---------|---------|



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00