

	IP SPEED DOME CAMERA OUTDOOR IPC6624SR-X33-VF LightHunter - 4 Mpx 4.5 ... 148.5 mm UNIVIEW	CONNECTION BOX PU-5	NETWORK ADAPTER TL-PA4010KIT TP-LINK
			
	1959.29 EUR 1959.29 EUR	1.86 EUR 1.86 EUR	47.78 EUR 47.78 EUR
LAN ports	1 Port LAN
Standard	TCP/IP
Material	...	PET	...
Modulation	OFDM
Sensor	1/2.8 " Progressive Scan CMOS
Protections	128-bit AES encryption
Matrix size	4 Mpx
Resolution	2688 x 1520 - 4 Mpx
LED diodes	Power supply, Link/Act, Power network
Transmission speed	500 Mbps
Lens	4.5 ... 148.5 mm
Range	300 m - Within a building
View angle	51 ° ... 2.5 °
Optical zoom	x 33
Digital zoom	x 16
Range of IR illumination	150 m
Video output	✓
Main features	...	<ul style="list-style-type: none"> • It is compatible with Category 5e • Krone type connectors 	<ul style="list-style-type: none"> • Plug & Play • HomePlug AV compliance • Low current consumption • Max. number of supported devices : 6 pcs • Pair button - Encryption activation
Preset rotation speed	<ul style="list-style-type: none"> • 300 °/s (horizontal) • 240 °/s (vertical)
Certificates	CE, FCC, RoHS
Operation temp	0 °C ... 40
Rotation speed (manual control)	<ul style="list-style-type: none"> • 0.1 °/s ... 200 °/s (horizontal) • 0.1 °/s ... 200 °/s (vertical)
Horizontal rotation range	360 ° - continuous
Vertical rotation range	-15 ° ... 90 °
RS-485 interface	✓
Number of presets	1024
Horizontal scan	✓
Route settings	16

Image compression method	Ultra H.265 / H.265 / H.264 / MJPEG
Alarm inputs / outputs	2 / 1
Audio	<ul style="list-style-type: none"> • External microphone input • Audio output • Bi-directional audio streaming support • Audio detection
Main stream frame rate	25 fps @ 4 Mpx
Network interface	10/100 Base-T (RJ-45)
WEB Server	Built-in
Max. number of on-line users	32
ONVIF	✓
Memory card slot	Micro SD memory cards up to 256GB support (possible local recording)
Mobile phones support	Access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application EZView • iOS (iPhone): Free application EZView
Default IP address	DHCP or 192.168.1.13
Default admin user / password	admin / 123456
Web browser access ports	80, 554
PC client access ports	Port no.: 80 or access by a cloud (P2P) - PC: Free application EZStation
Mobile client access ports	80
Port ONVIF	80
RTSP URL	rtsp://192.168.1.13:554/unicast/c1/s0/live - Main stream rtsp://192.168.1.13:554/unicast/c1/s1/live - Sub stream



Main features	<ul style="list-style-type: none"> • Intelligent Object Tracking • WDR - 120 dB - Wide Dynamic Range • 2D-DNR, 3D-DNR - Digital Noise Reduction • ROI - improve the quality of selected parts of image • F-DNR (Defog) - Reduction of image noise caused by precipitation • ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its • NAS - Network Attached Storage support - allows to connect memory resources directly to the computer network • BLC/HLC - Back Light / High Light Compensation • Day/night mode • ICR - Movable InfraRed filter • Auto White Balance • Configurable Privacy Zones - 24 • Motion Detection • Tamper signaling • Image rotation and mirror • Adaptive adjusting of the IR illuminator power to the lens zoom and outdoor light conditions • Home Position - set the camera to the specified position if no operator activity for a specified dwell time • Overvoltage protection : 6 kV • Filtering of false alarms based on the recognition of persons and vehicles • Intelligent image analysis : crossing the line (tripwire), intrusion, detection of entry into the area / exit from the area, crowd gathering estimation, people counting
Power supply	<ul style="list-style-type: none"> • PoE (802.3at), • 24 V DC / 2.5 A (power adapter included), • 24 V AC 	...	230 V AC
Power consumption	≤ 25 W	...	< 2 W
Housing	Speed Dome, Metal
Color	White	Black	...
Operation temp	-40 °C ... 70 °C
"Index of Protection"	IP66
Vandal-proof	—
Weight	5.31 kg	0.036 kg	0.075 kg
Dimensions	Ø 227 x 385 mm	66 x 36 x 26 mm	65 x 52 x 28 mm



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Supported languages	Polish, English, Czech, French, Spanish, Dutch, German, Portuguese, Slovenian, Hungarian, Italian
Manufacturer / Brand	UNIVIEW	...	TP-LINK
Guarantee	2 years	3 years	3 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00