




	WIRELESS REMOTE CONTROL WITH KEYBOARD KS-3 Air Mouse 2.4 GHz Blow	EXTENDER HDMI+USB-EX-70	CABLE FOR SOLAR INSTALLATIONS H1Z2Z2-K-1X4.0/RD
			
	10.90 EUR 10.90 EUR	100.20 EUR 100.20 EUR	0.91 EUR 0.91 EUR
Operating frequency	2.4 GHz
Operation range	~ 10 m
Supported HDMI resolutions	...	max. 1080p @ 60 Hz	...
Inner conductor	4.0 mm ² - Stranded wire Cu - Tin-plated
Maximal transmission range	...	<ul style="list-style-type: none"> • 70 m - UTP cat. 6, 6A, 7 @ 1080p • 60 m - UTP cat. 5e @ 1080p (our tests result) 	...
Rated voltage	600 V / 1000 V AC 1800 V DC
Outer coating	Ø 5.0 mm - Non-halogen plastic
Housing	Plastic
Main features	...	<ul style="list-style-type: none"> • Extender also allows to extend an USB 2.0 port, eg. in order to control the recorder using the mouse • Transition of the HDMI signal in the transmitter • EDID support • Audio transmission via network (Stereo) 	...
Color	Black
Current consumption	<ul style="list-style-type: none"> • 8 ... 16 mA (operation) • 6 mA (Standby mode)

Main features	<ul style="list-style-type: none"> • Air Mouse function - The built-in gravity sensor allows you to control the mouse cursor on the device screen by holding the remote control and making movements in the air - this solution does not require any flat surface • Backlit full keyboard in QWERTY standard • Remote control - Basic operation of functions such as: volume control, menu operation, channel selection, turning on and off the connected device • The ergonomic shape • Illuminated buttons • Plug & Play • Compatible with Windows, Mac OS, Linux, Android systems • Cooperation with DAHUA, HIKVISION recorders • USB cable included 	<ul style="list-style-type: none"> • Very good image quality with no visible distortions caused by compression, • No delays in video transmission, • No delays in mouse control operations • Designed to continuous operation 24/7 	<ul style="list-style-type: none"> • UV radiation resistance • Ozone resistance • Hydrolysis resistance • Resistant to oils and aggressive chemicals • Flame resistance (according to VDE 0482-332-2, DIN EN 60332-1) • The insulating layer is made of halogen-free material, which does not produce aggressive fumes during combustion • Increased mechanical strength of the outer coating • Expected lifetime : 25 years
Power supply	<ul style="list-style-type: none"> • built-in battery • Charging via micro USB port 	5 V DC / 1 A (included)	...
Coating color	Red
Operation temp	...	-20 °C ... 60 °C	...
Permissible relative humidity	...	0 % ... 90 % (non-condensing)	...
Manufacturer / Brand	Blow
Weight	0.053 kg	0.12 kg	...
Dimensions	<ul style="list-style-type: none"> • 151 x 45 x 14 mm • 0.5 m (cable length) 	85 x 75 x 20 mm - Transmitter or receiver dimensions	...
Guarantee	2 years	2 years	2 years